

```
[info] [35m[Appium][39m Welcome to Appium v1.22.3
[info] [35m[Appium][39m Non-default server args:
[info] [35m[Appium][39m   relaxedSecurityEnabled: true
[info] [35m[Appium][39m   allowInsecure: {
[info] [35m[Appium][39m   }
[info] [35m[Appium][39m   denyInsecure: {
[info] [35m[Appium][39m   }
[info] [35m[Appium][39m Appium REST http interface listener started
on 0.0.0.0:4723[info] [35m[HTTP][39m [37m-->[39m [37mPOST[39m [37m/
wd/hub/session[39m
[info] [35m[HTTP][39m [90m{"capabilities":{"alwaysMatch":
{"platformName":"iOS","appium:platformVersion":"17.1.2","appium:udid
":"00008110-001111392163801E","appium:deviceName":"iPhone
13","appium:automationName":"XCUITest","appium:bundleId":"org.uk.wwf
.myfootprint","appium:ignoreUnimportantViews":false,"appium:skipServ
erInstallation":false,"appium:useNewWDA":true,"appium:wdaStartupRetr
ies":4,"appium:iosInstallPause":0,"appium:wdaStartupRetryInterval":2
0000,"appium:newCommandTimeout":60,"appium:enableMultiWindows":false
,"appium:noReset":true,"appium:usePrebuiltWDA":true,"appium:includeS
afariInWebviews":true,"appium:connectHardwareKeyboard":true},"firstM
atch":{}}},"desiredCapabilities":
{"platformName":"iOS","appium:platformVersion":"17.1.2","appium:udid
":"00008110-001111392163801E","appium:deviceName":"iPhone
13","appium:automationName":"XCUITest","appium:bundleId":"org.uk.wwf
.myfootprint","appium:ignoreUnimportantViews":false,"appium:skipServ
erInstallation":false,"appium:useNewWDA":true,"appium:wdaStartupRetr
ies":4,"appium:iosInstal... [39m
[debug] [35m[W3C][39m Calling AppiumDriver.createSession() with
args:
[{"platformName":"iOS","appium:platformVersion":"17.1.2","appium:udi
d":"00008110-001111392163801E","appium:deviceName":"iPhone
13","appium:automationName":"XCUITest","appium:bundleId":"org.uk.wwf
.myfootprint","appium:ignoreUnimportantViews":false,"appium:skipServ
erInstallation":false,"appium:useNewWDA":true,"appium:wdaStartupRetr
ies":4,"appium:iosInstallPause":0,"appium:wdaStartupRetryInterval":2
0000,"appium:newCommandTimeout":60,"appium:enableMultiWindows":false
,"appium:noReset":true,"appium:usePrebuiltWDA":true,"appium:includeS
afariInWebviews":true,"appium:connectHardwareKeyboard":true},null,
{"alwaysMatch":
{"platformName":"iOS","appium:platformVersion":"17.1.2","appium:udid
":"00008110-001111392163801E","appium:deviceName":"iPhone
13","appium:automationName":"XCUITest","appium:bundleId":"org.uk.wwf
.myfootprint","appium:ignoreUnimportantViews":false,"appium:skipServ
erInstallation":false,"appium:useNewWDA":true,"appium:wdaStartupRetr
ies":4,"appium:iosInstallPause":0,"appium:wdaStartupRetryInterval":2
0000,"a...
[debug] [35m[BaseDriver][39m Event 'newSessionRequested' logged at
1702114942483 (15:12:22 GMT+0530 (India Standard Time))
[info] [35m[Appium][39m Appium v1.22.3 creating new XCUITestDriver
(v3.59.0) session
[info] [35m[Appium][39m Applying relaxed security to
'XCUITestDriver' as per server command line argument. All insecure
features will be enabled unless explicitly disabled by --deny-
insecure
```

```

[debug] [35m[BaseDriver][39m W3C capabilities and MJJSONWP desired
capabilities were provided
[debug] [35m[BaseDriver][39m Creating session with W3C capabilities:
{
[debug] [35m[BaseDriver][39m   "alwaysMatch": {
[debug] [35m[BaseDriver][39m     "platformName": "iOS",
[debug] [35m[BaseDriver][39m     "appium:platformVersion": "17.1.2",
[debug] [35m[BaseDriver][39m     "appium:udid":
"00008110-001111392163801E",
[debug] [35m[BaseDriver][39m     "appium:deviceName": "iPhone 13",
[debug] [35m[BaseDriver][39m     "appium:automationName":
"XCUITest",
[debug] [35m[BaseDriver][39m     "appium:bundleId":
"org.uk.wwf.myfootprint",
[debug] [35m[BaseDriver][39m     "appium:ignoreUnimportantViews":
false,
[debug] [35m[BaseDriver][39m     "appium:skipServerInstallation":
false,
[debug] [35m[BaseDriver][39m     "appium:useNewWDA": true,
[debug] [35m[BaseDriver][39m     "appium:wdaStartupRetries": 4,
[debug] [35m[BaseDriver][39m     "appium:iosInstallPause": 0,
[debug] [35m[BaseDriver][39m     "appium:wdaStartupRetryInterval":
20000,
[debug] [35m[BaseDriver][39m     "appium:newCommandTimeout": 60,
[debug] [35m[BaseDriver][39m     "appium:enableMultiWindows": false,
[debug] [35m[BaseDriver][39m     "appium:noReset": true,
[debug] [35m[BaseDriver][39m     "appium:usePrebuiltWDA": true,
[debug] [35m[BaseDriver][39m     "appium:includeSafariInWebviews":
true,
[debug] [35m[BaseDriver][39m     "appium:connectHardwareKeyboard":
true
[debug] [35m[BaseDriver][39m   },
[debug] [35m[BaseDriver][39m   "firstMatch": [
[debug] [35m[BaseDriver][39m     {}
[debug] [35m[BaseDriver][39m   ]
[debug] [35m[BaseDriver][39m }
[warn] [35m[BaseDriver][39m The following capabilities were
provided, but are not recognized by Appium:
[warn] [35m[BaseDriver][39m   ignoreUnimportantViews
[warn] [35m[BaseDriver][39m   skipServerInstallation
[warn] [35m[BaseDriver][39m   enableMultiWindows
[info] [35m[BaseDriver][39m Session created with session id:
efb6f477-c71c-45ce-8773-f461ddda565f[debug] [35m[XCUITest][39m
Current user: 'rohittripathi'
[debug] [35m[XCUITest][39m Available devices:
00008110-001111392163801E
[debug] [35m[XCUITest][39m Creating iDevice object with udid
'00008110-001111392163801E'
[info] [35m[XCUITest][39m Determining device to run tests on: udid:
'00008110-001111392163801E', real device: true
[info] [35m[XCUITest][39m Normalized platformVersion capability
value '17.1.2' to '17.1'
[debug] [35m[BaseDriver][39m Event 'xcodeDetailsRetrieved' logged at
1702114942819 (15:12:22 GMT+0530 (India Standard Time))

```

```
[debug] [35m[BaseDriver][39m Event 'appConfigured' logged at
1702114942821 (15:12:22 GMT+0530 (India Standard Time))
[debug] [35m[BaseDriver][39m Event 'resetStarted' logged at
1702114942822 (15:12:22 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Reset: fullReset not set. Leaving as is
[debug] [35m[BaseDriver][39m Event 'resetComplete' logged at
1702114942822 (15:12:22 GMT+0530 (India Standard Time))
[info] [35m[WebDriverAgent][39m Using WDA path: '/Applications/
Appium Server GUI 4729.app/Contents/Resources/app/node_modules/
appium/node_modules/appium-webdriveragent'
[info] [35m[WebDriverAgent][39m Using WDA agent: '/Applications/
Appium Server GUI 4729.app/Contents/Resources/app/node_modules/
appium/node_modules/appium-webdriveragent/
WebDriverAgent.xcodeproj'[debug] [35m[XCUITest][39m Crash reports
root '/Users/rohitrupathi/Library/Logs/CrashReporter/MobileDevice/
Pocketapp Admin's iPhone' does not exist. Got nothing to gather.
[debug] [35m[BaseDriver][39m Event 'logCaptureStarted' logged at
1702114943073 (15:12:23 GMT+0530 (India Standard Time))
[info] [35m[XCUITest][39m Setting up real device[debug]
[35m[WebDriverAgent][39m No obsolete cached processes from previous
WDA sessions listening on port 8100 have been found
[info] [35m[DevCon Factory][39m Requesting connection for device
00008110-001111392163801E on local port 8100, device port 8100
[debug] [35m[DevCon Factory][39m Cached connections count: 0
[info] [35m[DevCon Factory][39m Successfully requested the
connection for 00008110-001111392163801E:8100[debug]
[35m[WebDriverAgent][39m Parsed BUILD_DIR configuration value: '/
Users/rohitrupathi/Library/Developer/Xcode/DerivedData/
WebDriverAgent-hfzvtfpgjncqtwdkwzghybzlcqp/Build/Products'
[debug] [35m[WebDriverAgent][39m Got derived data root: '/Users/
rohitrupathi/Library/Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp'
[debug] [35m[XCUITest][39m Starting WebDriverAgent initialization
with the synchronization key '/Users/rohitrupathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp'
[debug] [35m[XCUITest][39m Capability 'useNewWDA' set to true, so
uninstalling WDA before proceeding
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug]
[35m[WebDriverAgent][39m No WDAs on the device.
[debug] [35m[BaseDriver][39m Event 'wdaUninstalled' logged at
1702114946172 (15:12:26 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Trying to start WebDriverAgent 4 times
with 20000ms interval
[debug] [35m[BaseDriver][39m Event 'wdaStartAttempted' logged at
1702114946173 (15:12:26 GMT+0530 (India Standard Time))
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if
```

```
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitripathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m
Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body[debug]
[35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
```

```
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
```

```
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]
[39m xcodebuild exited with code '65' and signal 'null'
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghyblzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
```

logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WD Proxy][39m Matched
'/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WebDriverAgent]
[39m Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body

```
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body[debug]
[35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]
[39m xcodebuild exited with code '65' and signal 'null'
[debug] [35m[BaseDriver][39m Event 'wdaStartFailed' logged at
1702114973899 (15:12:53 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Unable to launch WebDriverAgent because
of xcodebuild failure: xcodebuild failed with code 65
[debug] [35m[XCUITest][39m xcodebuild error message:
[debug] [35m[XCUITest][39m . Make sure you follow the tutorial at
https://github.com/appium/appium-xcuitest-driver/blob/master/docs/
real-device-config.md. Try to remove the WebDriverAgentRunner
application from the device if it is installed and reboot the
device.
[warn] [35m[XCUITest][39m Quitting and uninstalling WebDriverAgent
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug]
[35m[WebDriverAgent][39m No WDAs on the device.[debug]
[35m[BaseDriver][39m Event 'wdaStartAttempted' logged at
1702114994135 (15:13:14 GMT+0530 (India Standard Time))
[info] [35m[XCUITest][39m Retrying WDA startup (2 of 4)
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
```



```
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m
Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body[debug]
[35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
```

```
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]
[39m xcodebuild exited with code '65' and signal 'null'
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WD Proxy][39m Matched
'/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WebDriverAgent][39m Waiting up to 60000ms for
WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
```

```
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
```

```
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]
[39m xcodebuild exited with code '65' and signal 'null'
[debug] [35m[BaseDriver][39m Event 'wdaStartFailed' logged at
1702115008649 (15:13:28 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Unable to launch WebDriverAgent because
of xcodebuild failure: xcodebuild failed with code 65
[debug] [35m[XCUITest][39m xcodebuild error message:
[debug] [35m[XCUITest][39m . Make sure you follow the tutorial at
https://github.com/appium/appium-xcuitest-driver/blob/master/docs/
real-device-config.md. Try to remove the WebDriverAgentRunner
application from the device if it is installed and reboot the
device.
[warn] [35m[XCUITest][39m Quitting and uninstalling WebDriverAgent
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug]
[35m[WebDriverAgent][39m No WDAs on the device.[debug]
[35m[BaseDriver][39m Event 'wdaStartAttempted' logged at
1702115028882 (15:13:48 GMT+0530 (India Standard Time))
[info] [35m[XCUITest][39m Retrying WDA startup (3 of 4)
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...[debug] [35m[WebDriverAgent][39m 'pgrep
-if xcodebuild.*00008110-001111392163801E' didn't detect any
matching processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
```

```
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m
Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]
[39m xcodebuild exited with code '65' and signal 'null'
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
```

```
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlzcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WD Proxy][39m Matched
'/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WebDriverAgent]
[39m Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
```

```
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body[debug]
[35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
```

```
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]
[39m xcodebuild exited with code '65' and signal 'null'
[debug] [35m[BaseDriver][39m Event 'wdaStartFailed' logged at
1702115043674 (15:14:03 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Unable to launch WebDriverAgent because
of xcodebuild failure: xcodebuild failed with code 65
[debug] [35m[XCUITest][39m xcodebuild error message:
[debug] [35m[XCUITest][39m . Make sure you follow the tutorial at
https://github.com/appium/appium-xcuitest-driver/blob/master/docs/
real-device-config.md. Try to remove the WebDriverAgentRunner
application from the device if it is installed and reboot the
device.
[warn] [35m[XCUITest][39m Quitting and uninstalling WebDriverAgent
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug]
[35m[WebDriverAgent][39m No WDAs on the device.[debug]
[35m[BaseDriver][39m Event 'wdaStartAttempted' logged at
1702115063909 (15:14:23 GMT+0530 (India Standard Time))
[info] [35m[XCUITest][39m Retrying WDA startup (4 of 4)
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m
Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
```



```
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body[info] [35m[WD Proxy][39m socket
hang up[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body[debug]
[35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]
[39m xcodebuild exited with code '65' and signal 'null'
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
```

Resources/app/node_modules/appium/node_modules/appium-webdriveragent'

[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be logged if any errors are present there. To change this, use 'showXcodeLog' desired capability[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'

[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body

[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100

[info] [35m[WD Proxy][39m socket hang up

[debug] [35m[WebDriverAgent][39m Waiting up to 60000ms for WebDriverAgent to start

[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'

[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body

[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100

[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'

[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body

[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100

[info] [35m[WD Proxy][39m socket hang up

[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'

[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body

[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100

[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'

[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body

[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100

[info] [35m[WD Proxy][39m socket hang up

[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'

[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body

[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100

[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'

[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body

[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100

[info] [35m[WD Proxy][39m socket hang up

[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body[debug]
[35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body[debug]
[35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug]
[35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent][39m xcodebuild exited with code '65' and signal 'null'
[debug] [35m[BaseDriver][39m Event 'wdaStartFailed' logged at 1702115078904 (15:14:38 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Unable to launch WebDriverAgent because of xcodebuild failure: xcodebuild failed with code 65
[debug] [35m[XCUITest][39m xcodebuild error message:
[debug] [35m[XCUITest][39m . Make sure you follow the tutorial at https://github.com/appium/appium-xcuitest-driver/blob/master/docs/real-device-config.md. Try to remove the WebDriverAgentRunner application from the device if it is installed and reboot the device.
[warn] [35m[XCUITest][39m Quitting and uninstalling WebDriverAgent
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug]
[35m[WebDriverAgent][39m No WDAs on the device.
[error] [35m[XCUITest][39m {}
[info] [35m[DevCon Factory][39m Releasing connections for 00008110-001111392163801E device on any port number
[info] [35m[DevCon Factory][39m Found cached connections to release:
```

```
["00008110-001111392163801E:8100"]
[info] [35m[DevCon Factory][39m Releasing the listener for
'00008110-001111392163801E:8100'
[debug] [35m[iProxy@00008110:8100][39m Closing the connection
[debug] [35m[DevCon Factory][39m Cached connections count: 0
[debug] [35m[XCUITest][39m Not clearing log files. Use
`clearSystemFiles` capability to turn on.
[info] [35m[iProxy@00008110:8100][39m The connection has been closed
[debug] [35m[BaseDriver][39m Event 'newSessionStarted' logged at
1702115079146 (15:14:39 GMT+0530 (India Standard Time))
[debug] [35m[W3C][39m Encountered internal error running command:
Error: Unable to launch WebDriverAgent because of xcodebuild
failure: xcodebuild failed with code 65
[debug] [35m[W3C][39m xcodebuild error message:
[debug] [35m[W3C][39m . Make sure you follow the tutorial at
https://github.com/appium/appium-xcuitest-driver/blob/master/docs/
real-device-config.md. Try to remove the WebDriverAgentRunner
application from the device if it is installed and reboot the
device.
[debug] [35m[W3C][39m      at quitAndUninstall (/Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-xcuitest-driver/lib/driver.js:585:15)
[debug] [35m[W3C][39m      at /Applications/Appium Server GUI
4729.app/Contents/Resources/app/node_modules/appium/node_modules/
appium-xcuitest-driver/lib/driver.js:620:11
[debug] [35m[W3C][39m      at wrapped (/Applications/Appium Server
GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/asyncbox/lib/asyncbox.js:60:13)
[debug] [35m[W3C][39m      at retry (/Applications/Appium Server GUI
4729.app/Contents/Resources/app/node_modules/appium/node_modules/
asyncbox/lib/asyncbox.js:43:13)
[debug] [35m[W3C][39m      at retryInterval (/Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/asyncbox/lib/asyncbox.js:70:10)
[debug] [35m[W3C][39m      at /Applications/Appium Server GUI
4729.app/Contents/Resources/app/node_modules/appium/node_modules/
appium-xcuitest-driver/lib/driver.js:600:7
[info] [35m[HTTP][39m [37m<-- POST /wd/hub/session [39m[31m500[39m
[90m136713 ms - 1423[39m
[info] [35m[HTTP][39m [90m[39m[info] [35m[HTTP][39m [37m-->[39m
[37mPOST[39m [37m/wd/hub/session[39m
[info] [35m[HTTP][39m [90m{"capabilities":{"alwaysMatch":
{"platformName":"iOS","appium:platformVersion":"17.1.2","appium:udid
":"00008110-001111392163801E","appium:deviceName":"iPhone
13","appium:automationName":"XCUITest","appium:bundleId":"org.uk.wwf
.myfootprint","appium:ignoreUnimportantViews":false,"appium:skipServ
erInstallation":false,"appium:useNewWDA":true,"appium:wdaStartupRetr
ies":4,"appium:iosInstallPause":0,"appium:wdaStartupRetryInterval":2
0000,"appium:newCommandTimeout":60,"appium:enableMultiWindows":false
,"appium:noReset":true,"appium:usePrebuiltWDA":true,"appium:includeS
afariInWebviews":true,"appium:connectHardwareKeyboard":true},"firstM
atch":{}}},"desiredCapabilities":
{"platformName":"iOS","appium:platformVersion":"17.1.2","appium:udid
":"00008110-001111392163801E","appium:deviceName":"iPhone
```

```
13", "appium:automationName": "XCUITest", "appium:bundleId": "org.uk.wwf
.myfootprint", "appium:ignoreUnimportantViews": false, "appium:skipServ
erInstallation": false, "appium:useNewWDA": true, "appium:wdaStartupRetr
ies": 4, "appium:iosInstal... [39m
[debug] [35m[W3C][39m Calling AppiumDriver.createSession() with
args:
[{"platformName": "iOS", "appium:platformVersion": "17.1.2", "appium:udid": "00008110-001111392163801E", "appium:deviceName": "iPhone
13", "appium:automationName": "XCUITest", "appium:bundleId": "org.uk.wwf
.myfootprint", "appium:ignoreUnimportantViews": false, "appium:skipServ
erInstallation": false, "appium:useNewWDA": true, "appium:wdaStartupRetr
ies": 4, "appium:iosInstallPause": 0, "appium:wdaStartupRetryInterval": 2
0000, "appium:newCommandTimeout": 60, "appium:enableMultiWindows": false
, "appium:noReset": true, "appium:usePrebuiltWDA": true, "appium:includeS
afariInWebviews": true, "appium:connectHardwareKeyboard": true}, null,
{"alwaysMatch":
{"platformName": "iOS", "appium:platformVersion": "17.1.2", "appium:udid": "00008110-001111392163801E", "appium:deviceName": "iPhone
13", "appium:automationName": "XCUITest", "appium:bundleId": "org.uk.wwf
.myfootprint", "appium:ignoreUnimportantViews": false, "appium:skipServ
erInstallation": false, "appium:useNewWDA": true, "appium:wdaStartupRetr
ies": 4, "appium:iosInstallPause": 0, "appium:wdaStartupRetryInterval": 2
0000, "a...
[debug] [35m[BaseDriver][39m Event 'newSessionRequested' logged at
1702115136525 (15:15:36 GMT+0530 (India Standard Time))
[info] [35m[Appium][39m Appium v1.22.3 creating new XCUITestDriver
(v3.59.0) session
[info] [35m[Appium][39m Applying relaxed security to
'XCUITestDriver' as per server command line argument. All insecure
features will be enabled unless explicitly disabled by --deny-
insecure
[debug] [35m[BaseDriver][39m W3C capabilities and MJSONWP desired
capabilities were provided
[debug] [35m[BaseDriver][39m Creating session with W3C capabilities:
{
[debug] [35m[BaseDriver][39m   "alwaysMatch": {
[debug] [35m[BaseDriver][39m     "platformName": "iOS",
[debug] [35m[BaseDriver][39m     "appium:platformVersion": "17.1.2",
[debug] [35m[BaseDriver][39m     "appium:udid":
"00008110-001111392163801E",
[debug] [35m[BaseDriver][39m     "appium:deviceName": "iPhone 13",
[debug] [35m[BaseDriver][39m     "appium:automationName":
"XCUITest",
[debug] [35m[BaseDriver][39m     "appium:bundleId":
"org.uk.wwf.myfootprint",
[debug] [35m[BaseDriver][39m     "appium:ignoreUnimportantViews":
false,
[debug] [35m[BaseDriver][39m     "appium:skipServerInstallation":
false,
[debug] [35m[BaseDriver][39m     "appium:useNewWDA": true,
[debug] [35m[BaseDriver][39m     "appium:wdaStartupRetries": 4,
[debug] [35m[BaseDriver][39m     "appium:iosInstallPause": 0,
[debug] [35m[BaseDriver][39m     "appium:wdaStartupRetryInterval":
20000,
```

```
[debug] [35m[BaseDriver][39m      "appium:newCommandTimeout": 60,
[debug] [35m[BaseDriver][39m      "appium:enableMultiWindows": false,
[debug] [35m[BaseDriver][39m      "appium:noReset": true,
[debug] [35m[BaseDriver][39m      "appium:usePrebuiltWDA": true,
[debug] [35m[BaseDriver][39m      "appium:includeSafariInWebviews":
true,
[debug] [35m[BaseDriver][39m      "appium:connectHardwareKeyboard":
true
[debug] [35m[BaseDriver][39m    },
[debug] [35m[BaseDriver][39m    "firstMatch": [
[debug] [35m[BaseDriver][39m      {}
[debug] [35m[BaseDriver][39m    ]
[debug] [35m[BaseDriver][39m  }
[warn] [35m[BaseDriver][39m The following capabilities were
provided, but are not recognized by Appium:
[warn] [35m[BaseDriver][39m   ignoreUnimportantViews
[warn] [35m[BaseDriver][39m   skipServerInstallation
[warn] [35m[BaseDriver][39m   enableMultiWindows
[info] [35m[BaseDriver][39m Session created with session id:
70fa7189-5555-44a6-bce8-c98ca75667c8
[debug] [35m[XCUITest][39m Current user: 'rohittrpathi'
[debug] [35m[XCUITest][39m Available devices:
00008110-001111392163801E
[debug] [35m[XCUITest][39m Creating iDevice object with udid
'00008110-001111392163801E'
[info] [35m[XCUITest][39m Determining device to run tests on: udid:
'00008110-001111392163801E', real device: true
[info] [35m[XCUITest][39m Normalized platformVersion capability
value '17.1.2' to '17.1'
[debug] [35m[BaseDriver][39m Event 'xcodeDetailsRetrieved' logged at
1702115136603 (15:15:36 GMT+0530 (India Standard Time))
[debug] [35m[BaseDriver][39m Event 'appConfigured' logged at
1702115136603 (15:15:36 GMT+0530 (India Standard Time))
[debug] [35m[BaseDriver][39m Event 'resetStarted' logged at
1702115136603 (15:15:36 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Reset: fullReset not set. Leaving as is
[debug] [35m[BaseDriver][39m Event 'resetComplete' logged at
1702115136603 (15:15:36 GMT+0530 (India Standard Time))
[info] [35m[WebDriverAgent][39m Using WDA path: '/Applications/
Appium Server GUI 4729.app/Contents/Resources/app/node_modules/
appium/node_modules/appium-webdriveragent'
[info] [35m[WebDriverAgent][39m Using WDA agent: '/Applications/
Appium Server GUI 4729.app/Contents/Resources/app/node_modules/
appium/node_modules/appium-webdriveragent/
WebDriverAgent.xcodeproj'
[debug] [35m[XCUITest][39m Crash reports
root '/Users/rohittrpathi/Library/Logs/CrashReporter/MobileDevice/
Pocketapp Admin's iPhone' does not exist. Got nothing to gather.
[debug] [35m[BaseDriver][39m Event 'logCaptureStarted' logged at
1702115136799 (15:15:36 GMT+0530 (India Standard Time))
[info] [35m[XCUITest][39m Setting up real device
[debug] [35m[WebDriverAgent][39m No obsolete cached processes from previous
WDA sessions listening on port 8100 have been found
[info] [35m[DevCon Factory][39m Requesting connection for device
00008110-001111392163801E on local port 8100, device port 8100
```

```
[debug] [35m[DevCon Factory][39m Cached connections count: 0
[info] [35m[DevCon Factory][39m Successfully requested the
connection for 00008110-001111392163801E:8100[debug]
[35m[WebDriverAgent][39m Parsed BUILD_DIR configuration value: '/
Users/rohittripathi/Library/Developer/Xcode/DerivedData/
WebDriverAgent-hfzvtfpgjncqtwdkwzghybzlcqp/Build/Products'
[debug] [35m[WebDriverAgent][39m Got derived data root: '/Users/
rohittripathi/Library/Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp'
[debug] [35m[XCUITest][39m Starting WebDriverAgent initialization
with the synchronization key '/Users/rohittripathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp'
[debug] [35m[XCUITest][39m Capability 'useNewWDA' set to true, so
uninstalling WDA before proceeding
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug]
[35m[WebDriverAgent][39m No WDAs on the device.
[debug] [35m[BaseDriver][39m Event 'wdaUninstalled' logged at
1702115138801 (15:15:38 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Trying to start WebDriverAgent 4 times
with 20000ms interval
[debug] [35m[BaseDriver][39m Event 'wdaStartAttempted' logged at
1702115138801 (15:15:38 GMT+0530 (India Standard Time))
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohittripathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m
Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
```

```
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]
[39m xcodebuild exited with code '65' and signal 'null'
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
```



```
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]
[39m xcodebuild exited with code '65' and signal 'null'
[debug] [35m[BaseDriver][39m Event 'wdaStartFailed' logged at
1702115152819 (15:15:52 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Unable to launch WebDriverAgent because
of xcodebuild failure: xcodebuild failed with code 65
```

```
[debug] [35m[XCUITest][39m xcodebuild error message:
[debug] [35m[XCUITest][39m . Make sure you follow the tutorial at
https://github.com/appium/appium-xcuitest-driver/blob/master/docs/
real-device-config.md. Try to remove the WebDriverAgentRunner
application from the device if it is installed and reboot the
device.
[warn] [35m[XCUITest][39m Quitting and uninstalling WebDriverAgent
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug]
[35m[WebDriverAgent][39m No WDAs on the device.[debug]
[35m[BaseDriver][39m Event 'wdaStartAttempted' logged at
1702115173045 (15:16:13 GMT+0530 (India Standard Time))
[info] [35m[XCUITest][39m Retrying WDA startup (2 of 4)
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m
Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
```

```
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]
[39m xcodebuild exited with code '65' and signal 'null'
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WD Proxy][39m Matched
'/status' to command name 'getStatus'
```



```
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]
[39m xcodebuild exited with code '65' and signal 'null'
[debug] [35m[BaseDriver][39m Event 'wdaStartFailed' logged at
1702115187831 (15:16:27 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Unable to launch WebDriverAgent because
of xcodebuild failure: xcodebuild failed with code 65
[debug] [35m[XCUITest][39m xcodebuild error message:
[debug] [35m[XCUITest][39m . Make sure you follow the tutorial at
https://github.com/appium/appium-xcuitest-driver/blob/master/docs/
real-device-config.md. Try to remove the WebDriverAgentRunner
application from the device if it is installed and reboot the
device.
[warn] [35m[XCUITest][39m Quitting and uninstalling WebDriverAgent
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug]
[35m[WebDriverAgent][39m No WDAs on the device.[debug]
[35m[BaseDriver][39m Event 'wdaStartAttempted' logged at
1702115208065 (15:16:48 GMT+0530 (India Standard Time))
[info] [35m[XCUITest][39m Retrying WDA startup (3 of 4)
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
```

```
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...[debug] [35m[WebDriverAgent][39m 'pgrep
-if xcodebuild.*00008110-001111392163801E' didn't detect any
matching processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m
Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent][39m xcodebuild exited with code '65' and signal 'null'
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes 'xcodebuild.*00008110-001111392163801E' for the device 00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if xcodebuild.*00008110-001111392163801E' didn't detect any matching processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command 'xcodebuild test-without-building -project /Applications/Appium Server GUI 4729.app/Contents/Resources/app/node_modules/appium/node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/Developer/Xcode/DerivedData/WebDriverAgent-hfzvtfpgjncqtwdkwzghybzlcqp -destination id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1 GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in directory '/Applications/Appium Server GUI 4729.app/Contents/Resources/app/node_modules/appium/node_modules/appium-webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be logged if any errors are present there. To change this, use 'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
```



```
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body[debug]
[35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body[debug]
[35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body[debug]
[35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body[debug]
[35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
```

```
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug]
[35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up
[error] [35m[WebDriverAgent][39m xcodebuild exited with code '65'
and signal 'null'
[debug] [35m[BaseDriver][39m Event 'wdaStartFailed' logged at
1702115222151 (15:17:02 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Unable to launch WebDriverAgent because
of xcodebuild failure: xcodebuild failed with code 65
[debug] [35m[XCUITest][39m xcodebuild error message:
[debug] [35m[XCUITest][39m . Make sure you follow the tutorial at
https://github.com/appium/appium-xcuitest-driver/blob/master/docs/
real-device-config.md. Try to remove the WebDriverAgentRunner
application from the device if it is installed and reboot the
device.
[warn] [35m[XCUITest][39m Quitting and uninstalling WebDriverAgent
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug]
[35m[WebDriverAgent][39m No WDAs on the device.[debug]
[35m[BaseDriver][39m Event 'wdaStartAttempted' logged at
1702115242384 (15:17:22 GMT+0530 (India Standard Time))
[info] [35m[XCUITest][39m Retrying WDA startup (4 of 4)
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m
Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
```

```
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]
[39m xcodebuild exited with code '65' and signal 'null'
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
```

```
Developer/Xcode/DerivedData/WebDriverAgent-  
hfzvtfpgjncqtwdkwzghybzlcqp -destination  
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1  
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in  
directory '/Applications/Appium Server GUI 4729.app/Contents/  
Resources/app/node_modules/appium/node_modules/appium-  
webdriveragent'  
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be  
logged if any errors are present there. To change this, use  
'showXcodeLog' desired capability[debug] [35m[WD Proxy][39m Matched  
'/status' to command name 'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to  
port 8100  
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WebDriverAgent]  
[39m Waiting up to 60000ms for WebDriverAgent to start  
[debug] [35m[WD Proxy][39m Matched '/status' to command name  
'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to  
port 8100  
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m  
Matched '/status' to command name 'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body[debug]  
[35m[iProxy@00008110:8100][39m Connection was refused to port 8100  
[debug] [35m[WD Proxy][39m Matched '/status' to command name  
'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[info] [35m[WD Proxy][39m socket hang up  
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to  
port 8100  
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m  
Matched '/status' to command name 'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[debug] [35m[WD Proxy][39m Matched '/status' to command name  
'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to  
port 8100  
[info] [35m[WD Proxy][39m socket hang up  
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to  
port 8100  
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m  
Matched '/status' to command name 'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[debug] [35m[WD Proxy][39m Matched '/status' to command name  
'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[info] [35m[WD Proxy][39m socket hang up[info] [35m[HTTP][39m
[37m<-- POST /wd/hub/session [39m[32m-[39m [90m- ms - -[39m
[info] [35m[HTTP][39m [90m[39m
[info] [35m[HTTP][39m [37m-->[39m [37mPOST[39m [37m/wd/hub/
session[39m
[info] [35m[HTTP][39m [90m{"capabilities":{"alwaysMatch":
{"platformName":"iOS","appium:platformVersion":"17.1.2","appium:udid
":"00008110-001111392163801E","appium:deviceName":"iPhone
13","appium:automationName":"XCUIest","appium:bundleId":"org.uk.wwf
.myfootprint","appium:ignoreUnimportantViews":false,"appium:skipServ
erInstallation":false,"appium:useNewWDA":true,"appium:wdaStartupRetr
ies":4,"appium:iosInstallPause":0,"appium:wdaStartupRetryInterval":2
0000,"appium:newCommandTimeout":60,"appium:enableMultiWindows":false
,"appium:noReset":true,"appium:usePrebuiltWDA":true,"appium:includeS
afariInWebviews":true,"appium:connectHardwareKeyboard":true},"firstM
atch":[]},"desiredCapabilities":
{"platformName":"iOS","appium:platformVersion":"17.1.2","appium:udid
":"00008110-001111392163801E","appium:deviceName":"iPhone
13","appium:automationName":"XCUIest","appium:bundleId":"org.uk.wwf
.myfootprint","appium:ignoreUnimportantViews":false,"appium:skipServ
erInstallation":false,"appium:useNewWDA":true,"appium:wdaStartupRetr
```

```
ies":4,"appium:iosInstal... [39m
[debug] [35m[W3C][39m Calling AppiumDriver.createSession() with
args:
[{"platformName":"iOS","appium:platformVersion":"17.1.2","appium:udid":
"00008110-001111392163801E","appium:deviceName":"iPhone
13","appium:automationName":"XCUIest","appium:bundleId":"org.uk.wwf
.myfootprint","appium:ignoreUnimportantViews":false,"appium:skipServ
erInstallation":false,"appium:useNewWDA":true,"appium:wdaStartupRetr
ies":4,"appium:iosInstallPause":0,"appium:wdaStartupRetryInterval":2
0000,"appium:newCommandTimeout":60,"appium:enableMultiWindows":false
,"appium:noReset":true,"appium:usePrebuiltWDA":true,"appium:includes
afariInWebviews":true,"appium:connectHardwareKeyboard":true},null,
{"alwaysMatch":
{"platformName":"iOS","appium:platformVersion":"17.1.2","appium:udid
":"00008110-001111392163801E","appium:deviceName":"iPhone
13","appium:automationName":"XCUIest","appium:bundleId":"org.uk.wwf
.myfootprint","appium:ignoreUnimportantViews":false,"appium:skipServ
erInstallation":false,"appium:useNewWDA":true,"appium:wdaStartupRetr
ies":4,"appium:iosInstallPause":0,"appium:wdaStartupRetryInterval":2
0000,"a...
[debug] [35m[BaseDriver][39m Event 'newSessionRequested' logged at
1702115256566 (15:17:36 GMT+0530 (India Standard Time))
[info] [35m[Appium][39m Appium v1.22.3 creating new XCUIestDriver
(v3.59.0) session
[info] [35m[Appium][39m Applying relaxed security to
'XCUIestDriver' as per server command line argument. All insecure
features will be enabled unless explicitly disabled by --deny-
insecure
[debug] [35m[BaseDriver][39m W3C capabilities and MJSONWP desired
capabilities were provided
[debug] [35m[BaseDriver][39m Creating session with W3C capabilities:
{
[debug] [35m[BaseDriver][39m   "alwaysMatch": {
[debug] [35m[BaseDriver][39m     "platformName": "iOS",
[debug] [35m[BaseDriver][39m     "appium:platformVersion": "17.1.2",
[debug] [35m[BaseDriver][39m     "appium:udid":
"00008110-001111392163801E",
[debug] [35m[BaseDriver][39m     "appium:deviceName": "iPhone 13",
[debug] [35m[BaseDriver][39m     "appium:automationName":
"XCUIest",
[debug] [35m[BaseDriver][39m     "appium:bundleId":
"org.uk.wwf.myfootprint",
[debug] [35m[BaseDriver][39m     "appium:ignoreUnimportantViews":
false,
[debug] [35m[BaseDriver][39m     "appium:skipServerInstallation":
false,
[debug] [35m[BaseDriver][39m     "appium:useNewWDA": true,
[debug] [35m[BaseDriver][39m     "appium:wdaStartupRetries": 4,
[debug] [35m[BaseDriver][39m     "appium:iosInstallPause": 0,
[debug] [35m[BaseDriver][39m     "appium:wdaStartupRetryInterval":
20000,
[debug] [35m[BaseDriver][39m     "appium:newCommandTimeout": 60,
[debug] [35m[BaseDriver][39m     "appium:enableMultiWindows": false,
[debug] [35m[BaseDriver][39m     "appium:noReset": true,
```

```
[debug] [35m[BaseDriver][39m      "appium:usePrebuiltWDA": true,
[debug] [35m[BaseDriver][39m      "appium:includeSafariInWebviews":
true,
[debug] [35m[BaseDriver][39m      "appium:connectHardwareKeyboard":
true
[debug] [35m[BaseDriver][39m    },
[debug] [35m[BaseDriver][39m    "firstMatch": [
[debug] [35m[BaseDriver][39m      {}
[debug] [35m[BaseDriver][39m    ]
[debug] [35m[BaseDriver][39m  }
[warn] [35m[BaseDriver][39m The following capabilities were
provided, but are not recognized by Appium:
[warn] [35m[BaseDriver][39m   ignoreUnimportantViews
[warn] [35m[BaseDriver][39m   skipServerInstallation
[warn] [35m[BaseDriver][39m   enableMultiWindows
[info] [35m[BaseDriver][39m Session created with session id:
bb8a4154-321a-4479-993a-43f59aa784e7
[debug] [35m[XCUITest][39m Current user: 'rohittripathi'
[debug] [35m[XCUITest][39m Available devices:
00008110-001111392163801E
[debug] [35m[XCUITest][39m Creating iDevice object with udid
'00008110-001111392163801E'
[info] [35m[XCUITest][39m Determining device to run tests on: udid:
'00008110-001111392163801E', real device: true
[info] [35m[XCUITest][39m Normalized platformVersion capability
value '17.1.2' to '17.1'
[debug] [35m[BaseDriver][39m Event 'xcodeDetailsRetrieved' logged at
1702115256651 (15:17:36 GMT+0530 (India Standard Time))
[debug] [35m[BaseDriver][39m Event 'appConfigured' logged at
1702115256652 (15:17:36 GMT+0530 (India Standard Time))
[debug] [35m[BaseDriver][39m Event 'resetStarted' logged at
1702115256652 (15:17:36 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Reset: fullReset not set. Leaving as is
[debug] [35m[BaseDriver][39m Event 'resetComplete' logged at
1702115256652 (15:17:36 GMT+0530 (India Standard Time))
[info] [35m[WebDriverAgent][39m Using WDA path: '/Applications/
Appium Server GUI 4729.app/Contents/Resources/app/node_modules/
appium/node_modules/appium-webdriveragent'
[info] [35m[WebDriverAgent][39m Using WDA agent: '/Applications/
Appium Server GUI 4729.app/Contents/Resources/app/node_modules/
appium/node_modules/appium-webdriveragent/
WebDriverAgent.xcodeproj'
[debug] [35m[WD Proxy][39m Matched '/'
status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
```

```
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[XCUITest][39m Crash reports root '/Users/rohittrpathi/
Library/Logs/CrashReporter/MobileDevice/Pocketapp Admin's iPhone'
does not exist. Got nothing to gather.
[debug] [35m[BaseDriver][39m Event 'logCaptureStarted' logged at
1702115256862 (15:17:36 GMT+0530 (India Standard Time))
[info] [35m[XCUITest][39m Setting up real device[error]
[35m[WebDriverAgent][39m xcodebuild exited with code '65' and signal
'null'
[debug] [35m[BaseDriver][39m Event 'wdaStartFailed' logged at
1702115257007 (15:17:37 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Unable to launch WebDriverAgent because
of xcodebuild failure: xcodebuild failed with code 65
[debug] [35m[XCUITest][39m xcodebuild error message:
[debug] [35m[XCUITest][39m . Make sure you follow the tutorial at
https://github.com/appium/appium-xcuitest-driver/blob/master/docs/
real-device-config.md. Try to remove the WebDriverAgentRunner
application from the device if it is installed and reboot the
device.
[warn] [35m[XCUITest][39m Quitting and uninstalling WebDriverAgent
[info] [35m[WebDriverAgent][39m Shutting down sub-processes
[debug] [35m[WebDriverAgent][39m No obsolete cached processes from
previous WDA sessions listening on port 8100 have been found
[info] [35m[DevCon Factory][39m Requesting connection for device
00008110-001111392163801E on local port 8100, device port 8100
[debug] [35m[DevCon Factory][39m Cached connections count: 1
[info] [35m[DevCon Factory][39m Found cached connections on port
#8100: ["00008110-001111392163801E:8100"]
[warn] [35m[DevCon Factory][39m Port #8100 is busy. Did you quit the
previous driver session(s) properly?
[info] [35m[DevCon Factory][39m Trying to release the port
[info] [35m[DevCon Factory][39m Releasing the listener for
'00008110-001111392163801E:8100'
[debug] [35m[iProxy@00008110:8100][39m Closing the connection
[info] [35m[iProxy@00008110:8100][39m The connection has been closed
[info] [35m[DevCon Factory][39m Port #8100 has been successfully
released after 1ms
[info] [35m[DevCon Factory][39m Successfully requested the
connection for 00008110-001111392163801E:8100[debug]
[35m[WebDriverAgent][39m No WDAs on the device.
[error] [35m[XCUITest][39m {}
[info] [35m[DevCon Factory][39m Releasing connections for
00008110-001111392163801E device on any port number
[info] [35m[DevCon Factory][39m Found cached connections to release:
["00008110-001111392163801E:8100"]
[info] [35m[DevCon Factory][39m Releasing the listener for
'00008110-001111392163801E:8100'
[debug] [35m[iProxy@00008110:8100][39m Closing the connection
[debug] [35m[DevCon Factory][39m Cached connections count: 0
[debug] [35m[XCUITest][39m Not clearing log files. Use
`clearSystemFiles` capability to turn on.
[info] [35m[iProxy@00008110:8100][39m The connection has been closed
[debug] [35m[BaseDriver][39m Event 'newSessionStarted' logged at
1702115257240 (15:17:37 GMT+0530 (India Standard Time))
```



```
[debug] [35m[W3C][39m Encountered internal error running command:
Error: Unable to launch WebDriverAgent because of xcodebuild
failure: xcodebuild failed with code 65
[debug] [35m[W3C][39m xcodebuild error message:
[debug] [35m[W3C][39m . Make sure you follow the tutorial at
https://github.com/appium/appium-xcuitest-driver/blob/master/docs/
real-device-config.md. Try to remove the WebDriverAgentRunner
application from the device if it is installed and reboot the
device.
[debug] [35m[W3C][39m      at quitAndUninstall (/Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-xcuitest-driver/lib/driver.js:585:15)
[debug] [35m[W3C][39m      at /Applications/Appium Server GUI
4729.app/Contents/Resources/app/node_modules/appium/node_modules/
appium-xcuitest-driver/lib/driver.js:620:11
[debug] [35m[W3C][39m      at wrapped (/Applications/Appium Server
GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/asyncbox/lib/asyncbox.js:60:13)
[debug] [35m[W3C][39m      at retry (/Applications/Appium Server GUI
4729.app/Contents/Resources/app/node_modules/appium/node_modules/
asyncbox/lib/asyncbox.js:43:13)
[debug] [35m[W3C][39m      at retryInterval (/Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/asyncbox/lib/asyncbox.js:70:10)
[debug] [35m[W3C][39m      at /Applications/Appium Server GUI
4729.app/Contents/Resources/app/node_modules/appium/node_modules/
appium-xcuitest-driver/lib/driver.js:600:7[debug]
[35m[WebDriverAgent][39m Parsed BUILD_DIR configuration value: '/
Users/rohittripathi/Library/Developer/Xcode/DerivedData/
WebDriverAgent-hfzvtfpgjncqtwdkwzghybzlcqp/Build/Products'
[debug] [35m[WebDriverAgent][39m Got derived data root: '/Users/
rohittripathi/Library/Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp'
[debug] [35m[XCUITest][39m Starting WebDriverAgent initialization
with the synchronization key '/Users/rohittripathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp'
[debug] [35m[XCUITest][39m Capability 'useNewWDA' set to true, so
uninstalling WDA before proceeding
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug]
[35m[WebDriverAgent][39m No WDAs on the device.
[debug] [35m[BaseDriver][39m Event 'wdaUninstalled' logged at
1702115258279 (15:17:38 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Trying to start WebDriverAgent 4 times
with 20000ms interval
[debug] [35m[BaseDriver][39m Event 'wdaStartAttempted' logged at
1702115258280 (15:17:38 GMT+0530 (India Standard Time))
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
```

```
[debug] [35m[WebDriverAgent][39m 'pgrep -if
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitripathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m
Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[error]
[35m[WebDriverAgent][39m xcodebuild exited with code '65' and signal
'null'
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
```



```
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[error]
[35m[WebDriverAgent][39m xcodebuild exited with code '65' and signal
'null'
[debug] [35m[BaseDriver][39m Event 'wdaStartFailed' logged at
1702115272090 (15:17:52 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Unable to launch WebDriverAgent because
of xcodebuild failure: xcodebuild failed with code 65
[debug] [35m[XCUITest][39m xcodebuild error message:
[debug] [35m[XCUITest][39m . Make sure you follow the tutorial at
https://github.com/appium/appium-xcuitest-driver/blob/master/docs/
real-device-config.md. Try to remove the WebDriverAgentRunner
application from the device if it is installed and reboot the
device.
[warn] [35m[XCUITest][39m Quitting and uninstalling WebDriverAgent
[info] [35m[WebDriverAgent][39m Shutting down sub-processes
[debug] [35m[WebDriverAgent][39m No WDAs on the device.[debug]
[35m[BaseDriver][39m Event 'wdaStartAttempted' logged at
1702115292319 (15:18:12 GMT+0530 (India Standard Time))
[info] [35m[XCUITest][39m Retrying WDA startup (2 of 4)
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...[debug] [35m[WebDriverAgent][39m 'pgrep
-if xcodebuild.*00008110-001111392163801E' didn't detect any
matching processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
```

```
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/  
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme  
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/  
Developer/Xcode/DerivedData/WebDriverAgent-  
hfzvtfpgjncqtwdkwzghyblzlcqp -destination  
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1  
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in  
directory '/Applications/Appium Server GUI 4729.app/Contents/  
Resources/app/node_modules/appium/node_modules/appium-  
webdriveragent'  
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be  
logged if any errors are present there. To change this, use  
'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m  
Waiting up to 60000ms for WebDriverAgent to start  
[debug] [35m[WD Proxy][39m Matched '/status' to command name  
'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]  
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]  
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]  
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]  
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]  
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[error]  
[35m[WebDriverAgent][39m xcodebuild exited with code '65' and signal  
'null'  
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the  
device  
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a  
cleanup. The sources are up to date (1680522269116 >= 1664354587000)  
[debug] [35m[WebDriverAgent][39m Killing running processes  
'xcodebuild.*00008110-001111392163801E' for the device  
00008110-001111392163801E...  
[debug] [35m[WebDriverAgent][39m 'pgrep -if  
xcodebuild.*00008110-001111392163801E' didn't detect any matching
```

processes. Return code: 1

```
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohittripathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
```

```
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m
Waiting up to 60000ms for WebDriverAgent to start
```

```
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
```

```
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
```

```
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
```

```
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
```

```
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
```

```
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
```

```
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
```

```
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
```

```
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
```

```
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
```

```
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100
[error] [35m[WebDriverAgent][39m xcodebuild exited with code '65'
and signal 'null'
[debug] [35m[BaseDriver][39m Event 'wdaStartFailed' logged at
1702115306278 (15:18:26 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Unable to launch WebDriverAgent because
of xcodebuild failure: xcodebuild failed with code 65
[debug] [35m[XCUITest][39m xcodebuild error message:
[debug] [35m[XCUITest][39m . Make sure you follow the tutorial at
https://github.com/appium/appium-xcuitest-driver/blob/master/docs/
real-device-config.md. Try to remove the WebDriverAgentRunner
application from the device if it is installed and reboot the
device.
[warn] [35m[XCUITest][39m Quitting and uninstalling WebDriverAgent
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug]
[35m[WebDriverAgent][39m No WDAs on the device.[debug]
[35m[BaseDriver][39m Event 'wdaStartAttempted' logged at
1702115326529 (15:18:46 GMT+0530 (India Standard Time))
[info] [35m[XCUITest][39m Retrying WDA startup (3 of 4)
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp -destination
```

```
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m
Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[error]
[35m[WebDriverAgent][39m xcodebuild exited with code '65' and signal
'null'
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...[debug] [35m[WebDriverAgent][39m 'pgrep
-if xcodebuild.*00008110-001111392163801E' didn't detect any
matching processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
```



```
Developer/Xcode/DerivedData/WebDriverAgent-  
hfzvtfpgjncqtwdkwzghybzlcqp -destination  
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1  
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in  
directory '/Applications/Appium Server GUI 4729.app/Contents/  
Resources/app/node_modules/appium/node_modules/appium-  
webdriveragent'  
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be  
logged if any errors are present there. To change this, use  
'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m  
Waiting up to 60000ms for WebDriverAgent to start  
[debug] [35m[WD Proxy][39m Matched '/status' to command name  
'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100  
[debug] [35m[WD Proxy][39m Matched '/status' to command name  
'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]  
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100  
[debug] [35m[WD Proxy][39m Matched '/status' to command name  
'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]  
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100  
[debug] [35m[WD Proxy][39m Matched '/status' to command name  
'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]  
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100  
[debug] [35m[WD Proxy][39m Matched '/status' to command name  
'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100
[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[error]
[35m[WebDriverAgent][39m xcodebuild exited with code '65' and signal 'null'
[debug] [35m[BaseDriver][39m Event 'wdaStartFailed' logged at 1702115340652 (15:19:00 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Unable to launch WebDriverAgent because of xcodebuild failure: xcodebuild failed with code 65
[debug] [35m[XCUITest][39m xcodebuild error message:
[debug] [35m[XCUITest][39m . Make sure you follow the tutorial at https://github.com/appium/appium-xcuitest-driver/blob/master/docs/real-device-config.md. Try to remove the WebDriverAgentRunner application from the device if it is installed and reboot the device.
[warn] [35m[XCUITest][39m Quitting and uninstalling WebDriverAgent
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug]
[35m[WebDriverAgent][39m No WDAs on the device.[debug]
[35m[BaseDriver][39m Event 'wdaStartAttempted' logged at 1702115360896 (15:19:20 GMT+0530 (India Standard Time))
[info] [35m[XCUITest][39m Retrying WDA startup (4 of 4)
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes 'xcodebuild.*00008110-001111392163801E' for the device 00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if xcodebuild.*00008110-001111392163801E' didn't detect any matching processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command 'xcodebuild test-without-building -project /Applications/Appium Server GUI 4729.app/Contents/Resources/app/node_modules/appium/node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
```

```
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m
Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[error]
[35m[WebDriverAgent][39m xcodebuild exited with code '65' and signal
'null'
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
```

```
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/  
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme  
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/  
Developer/Xcode/DerivedData/WebDriverAgent-  
hfzvtfpgjncqtwdkwzghyblzlcqp -destination  
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1  
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in  
directory '/Applications/Appium Server GUI 4729.app/Contents/  
Resources/app/node_modules/appium/node_modules/appium-  
webdriveragent'
```

```
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be  
logged if any errors are present there. To change this, use  
'showXcodeLog' desired capability[debug] [35m[WD Proxy][39m Matched  
'/status' to command name 'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body
```

```
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100
```

```
[debug] [35m[WebDriverAgent][39m Waiting up to 60000ms for  
WebDriverAgent to start
```

```
[debug] [35m[WD Proxy][39m Matched '/status' to command name  
'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body
```

```
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
```

```
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body
```

```
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100
```

```
[debug] [35m[WD Proxy][39m Matched '/status' to command name  
'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body
```

```
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
```

```
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body
```

```
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100
```

```
[debug] [35m[WD Proxy][39m Matched '/status' to command name  
'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body
```

```
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
```

```
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body
```

```
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100
```

```
[debug] [35m[WD Proxy][39m Matched '/status' to command name  
'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body
```

```
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
```

```
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body
```

```
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[debug]
[35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[info] [35m[WD Proxy][39m connect ECONNREFUSED 127.0.0.1:8100[error]
[35m[WebDriverAgent][39m xcodebuild exited with code '65' and signal
'null'
[debug] [35m[BaseDriver][39m Event 'wdaStartFailed' logged at
1702115375504 (15:19:35 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Unable to launch WebDriverAgent because
of xcodebuild failure: xcodebuild failed with code 65
[debug] [35m[XCUITest][39m xcodebuild error message:
[debug] [35m[XCUITest][39m . Make sure you follow the tutorial at
https://github.com/appium/appium-xcuitest-driver/blob/master/docs/
real-device-config.md. Try to remove the WebDriverAgentRunner
application from the device if it is installed and reboot the
device.
[warn] [35m[XCUITest][39m Quitting and uninstalling WebDriverAgent
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug]
[35m[WebDriverAgent][39m No WDAs on the device.
[error] [35m[XCUITest][39m {}
[info] [35m[DevCon Factory][39m Releasing connections for
00008110-001111392163801E device on any port number
[info] [35m[DevCon Factory][39m No cached connections have been
found
[debug] [35m[XCUITest][39m Not clearing log files. Use
`clearSystemFiles` capability to turn on.
[debug] [35m[BaseDriver][39m Event 'newSessionStarted' logged at
1702115375749 (15:19:35 GMT+0530 (India Standard Time))
[debug] [35m[W3C][39m Encountered internal error running command:
Error: Unable to launch WebDriverAgent because of xcodebuild
failure: xcodebuild failed with code 65
[debug] [35m[W3C][39m xcodebuild error message:
[debug] [35m[W3C][39m . Make sure you follow the tutorial at
https://github.com/appium/appium-xcuitest-driver/blob/master/docs/
```

real-device-config.md. Try to remove the WebDriverAgentRunner application from the device if it is installed and reboot the device.

```
[debug] [35m[W3C][39m      at quitAndUninstall (/Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-xcuitest-driver/lib/driver.js:585:15)
[debug] [35m[W3C][39m      at /Applications/Appium Server GUI
4729.app/Contents/Resources/app/node_modules/appium/node_modules/
appium-xcuitest-driver/lib/driver.js:620:11
[debug] [35m[W3C][39m      at wrapped (/Applications/Appium Server
GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/asyncbox/lib/asyncbox.js:60:13)
[debug] [35m[W3C][39m      at retry (/Applications/Appium Server GUI
4729.app/Contents/Resources/app/node_modules/appium/node_modules/
asyncbox/lib/asyncbox.js:43:13)
[debug] [35m[W3C][39m      at retryInterval (/Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/asyncbox/lib/asyncbox.js:70:10)
[debug] [35m[W3C][39m      at /Applications/Appium Server GUI
4729.app/Contents/Resources/app/node_modules/appium/node_modules/
appium-xcuitest-driver/lib/driver.js:600:7
[info] [35m[HTTP][39m [37m<-- POST /wd/hub/session [39m[31m500[39m
[90m119194 ms - 1311[39m
[info] [35m[HTTP][39m [90m[39m[info] [35m[HTTP][39m [37m-->[39m
[37mPOST[39m [37m/wd/hub/session[39m
[info] [35m[HTTP][39m [90m{"capabilities":{"alwaysMatch":
{"platformName":"iOS","appium:platformVersion":"17.1.2","appium:udid
":"00008110-001111392163801E","appium:deviceName":"iPhone
13","appium:automationName":"XCUITest","appium:bundleId":"org.uk.wwf
.myfootprint","appium:ignoreUnimportantViews":false,"appium:skipServ
erInstallation":false,"appium:useNewWDA":true,"appium:wdaStartupRetr
ies":4,"appium:iosInstallPause":0,"appium:wdaStartupRetryInterval":2
0000,"appium:newCommandTimeout":60,"appium:enableMultiWindows":false
,"appium:noReset":true,"appium:usePrebuiltWDA":true,"appium:includeS
afariInWebviews":true,"appium:connectHardwareKeyboard":true},"firstM
atch":{}}},"desiredCapabilities":
{"platformName":"iOS","appium:platformVersion":"17.1.2","appium:udid
":"00008110-001111392163801E","appium:deviceName":"iPhone
13","appium:automationName":"XCUITest","appium:bundleId":"org.uk.wwf
.myfootprint","appium:ignoreUnimportantViews":false,"appium:skipServ
erInstallation":false,"appium:useNewWDA":true,"appium:wdaStartupRetr
ies":4,"appium:iosInstal... [39m
[debug] [35m[W3C][39m Calling AppiumDriver.createSession() with
args:
[{"platformName":"iOS","appium:platformVersion":"17.1.2","appium:udi
d":"00008110-001111392163801E","appium:deviceName":"iPhone
13","appium:automationName":"XCUITest","appium:bundleId":"org.uk.wwf
.myfootprint","appium:ignoreUnimportantViews":false,"appium:skipServ
erInstallation":false,"appium:useNewWDA":true,"appium:wdaStartupRetr
ies":4,"appium:iosInstallPause":0,"appium:wdaStartupRetryInterval":2
0000,"appium:newCommandTimeout":60,"appium:enableMultiWindows":false
,"appium:noReset":true,"appium:usePrebuiltWDA":true,"appium:includeS
afariInWebviews":true,"appium:connectHardwareKeyboard":true},null,
{"alwaysMatch":
```

```
{"platformName":"iOS","appium:platformVersion":"17.1.2","appium:udid":"00008110-001111392163801E","appium:deviceName":"iPhone 13","appium:automationName":"XCUITest","appium:bundleId":"org.uk.wwf.myfootprint","appium:ignoreUnimportantViews":false,"appium:skipServerInstallation":false,"appium:useNewWDA":true,"appium:wdaStartupRetries":4,"appium:iosInstallPause":0,"appium:wdaStartupRetryInterval":20000,"a...
[debug] [35m[BaseDriver][39m Event 'newSessionRequested' logged at 1702116120759 (15:32:00 GMT+0530 (India Standard Time))
[info] [35m[Appium][39m Appium v1.22.3 creating new XCUIWebDriver (v3.59.0) session
[info] [35m[Appium][39m Applying relaxed security to 'XCUIWebDriver' as per server command line argument. All insecure features will be enabled unless explicitly disabled by --deny-insecure
[debug] [35m[BaseDriver][39m W3C capabilities and MJJSONWP desired capabilities were provided
[debug] [35m[BaseDriver][39m Creating session with W3C capabilities:
{
[debug] [35m[BaseDriver][39m   "alwaysMatch": {
[debug] [35m[BaseDriver][39m     "platformName": "iOS",
[debug] [35m[BaseDriver][39m     "appium:platformVersion": "17.1.2",
[debug] [35m[BaseDriver][39m     "appium:udid":
"00008110-001111392163801E",
[debug] [35m[BaseDriver][39m     "appium:deviceName": "iPhone 13",
[debug] [35m[BaseDriver][39m     "appium:automationName":
"XCUITest",
[debug] [35m[BaseDriver][39m     "appium:bundleId":
"org.uk.wwf.myfootprint",
[debug] [35m[BaseDriver][39m     "appium:ignoreUnimportantViews":
false,
[debug] [35m[BaseDriver][39m     "appium:skipServerInstallation":
false,
[debug] [35m[BaseDriver][39m     "appium:useNewWDA": true,
[debug] [35m[BaseDriver][39m     "appium:wdaStartupRetries": 4,
[debug] [35m[BaseDriver][39m     "appium:iosInstallPause": 0,
[debug] [35m[BaseDriver][39m     "appium:wdaStartupRetryInterval":
20000,
[debug] [35m[BaseDriver][39m     "appium:newCommandTimeout": 60,
[debug] [35m[BaseDriver][39m     "appium:enableMultiWindows": false,
[debug] [35m[BaseDriver][39m     "appium:noReset": true,
[debug] [35m[BaseDriver][39m     "appium:usePrebuiltWDA": true,
[debug] [35m[BaseDriver][39m     "appium:includeSafariInWebviews":
true,
[debug] [35m[BaseDriver][39m     "appium:connectHardwareKeyboard":
true
[debug] [35m[BaseDriver][39m   },
[debug] [35m[BaseDriver][39m   "firstMatch": [
[debug] [35m[BaseDriver][39m     {}
[debug] [35m[BaseDriver][39m   ]
[debug] [35m[BaseDriver][39m ]
[warn] [35m[BaseDriver][39m The following capabilities were provided, but are not recognized by Appium:
[warn] [35m[BaseDriver][39m   ignoreUnimportantViews
```

```
[warn] [35m[BaseDriver][39m skipServerInstallation
[warn] [35m[BaseDriver][39m enableMultiWindows
[info] [35m[BaseDriver][39m Session created with session id:
acd7f62f-cd65-496f-b770-51281bb4ed9c[debug] [35m[XCUITest][39m
Current user: 'rohittripathi'
[debug] [35m[XCUITest][39m Available devices:
00008110-001111392163801E
[debug] [35m[XCUITest][39m Creating iDevice object with udid
'00008110-001111392163801E'
[info] [35m[XCUITest][39m Determining device to run tests on: udid:
'00008110-001111392163801E', real device: true
[info] [35m[XCUITest][39m Normalized platformVersion capability
value '17.1.2' to '17.1'
[debug] [35m[BaseDriver][39m Event 'xcodeDetailsRetrieved' logged at
1702116121318 (15:32:01 GMT+0530 (India Standard Time))
[debug] [35m[BaseDriver][39m Event 'appConfigured' logged at
1702116121319 (15:32:01 GMT+0530 (India Standard Time))
[debug] [35m[BaseDriver][39m Event 'resetStarted' logged at
1702116121319 (15:32:01 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Reset: fullReset not set. Leaving as is
[debug] [35m[BaseDriver][39m Event 'resetComplete' logged at
1702116121320 (15:32:01 GMT+0530 (India Standard Time))
[info] [35m[WebDriverAgent][39m Using WDA path: '/Applications/
Appium Server GUI 4729.app/Contents/Resources/app/node_modules/
appium/node_modules/appium-webdriveragent'
[info] [35m[WebDriverAgent][39m Using WDA agent: '/Applications/
Appium Server GUI 4729.app/Contents/Resources/app/node_modules/
appium/node_modules/appium-webdriveragent/
WebDriverAgent.xcodeproj'[debug] [35m[XCUITest][39m Crash reports
root '/Users/rohittripathi/Library/Logs/CrashReporter/MobileDevice/
Pocketapp Admin's iPhone' does not exist. Got nothing to gather.
[debug] [35m[BaseDriver][39m Event 'logCaptureStarted' logged at
1702116121553 (15:32:01 GMT+0530 (India Standard Time))
[info] [35m[XCUITest][39m Setting up real device[debug]
[35m[WebDriverAgent][39m No obsolete cached processes from previous
WDA sessions listening on port 8100 have been found
[info] [35m[DevCon Factory][39m Requesting connection for device
00008110-001111392163801E on local port 8100, device port 8100
[debug] [35m[DevCon Factory][39m Cached connections count: 0
[info] [35m[DevCon Factory][39m Successfully requested the
connection for 00008110-001111392163801E:8100[debug]
[35m[WebDriverAgent][39m Parsed BUILD_DIR configuration value: '/
Users/rohittripathi/Library/Developer/Xcode/DerivedData/
WebDriverAgent-hfzvtfpgjncqtwdkwzghyblzlcqp/Build/Products'
[debug] [35m[WebDriverAgent][39m Got derived data root: '/Users/
rohittripathi/Library/Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghyblzlcqp'
[debug] [35m[XCUITest][39m Starting WebDriverAgent initialization
with the synchronization key '/Users/rohittripathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghyblzlcqp'
[debug] [35m[XCUITest][39m Capability 'useNewWDA' set to true, so
uninstalling WDA before proceeding
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug]
```



```
[35m[WebDriverAgent][39m No WDAs on the device.
[debug] [35m[BaseDriver][39m Event 'wdaUninstalled' logged at
1702116125132 (15:32:05 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Trying to start WebDriverAgent 4 times
with 20000ms interval
[debug] [35m[BaseDriver][39m Event 'wdaStartAttempted' logged at
1702116125132 (15:32:05 GMT+0530 (India Standard Time))
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlzcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m
Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
```

```
127.0.0.1:8100/status] with no body[debug]
[35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]
[39m xcodebuild exited with code '65' and signal 'null'
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WD Proxy][39m Matched
'/status' to command name 'getStatus'
```



```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent][39m xcodebuild exited with code '65' and signal 'null'
[debug] [35m[BaseDriver][39m Event 'wdaStartFailed' logged at 1702116140399 (15:32:20 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Unable to launch WebDriverAgent because of xcodebuild failure: xcodebuild failed with code 65
[debug] [35m[XCUITest][39m xcodebuild error message:
[debug] [35m[XCUITest][39m . Make sure you follow the tutorial at https://github.com/appium/appium-xcuitest-driver/blob/master/docs/real-device-config.md. Try to remove the WebDriverAgentRunner application from the device if it is installed and reboot the device.
[warn] [35m[XCUITest][39m Quitting and uninstalling WebDriverAgent
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug] [35m[WebDriverAgent][39m No WDAs on the device.[debug] [35m[BaseDriver][39m Event 'wdaStartAttempted' logged at 1702116160638 (15:32:40 GMT+0530 (India Standard Time))
```

```
[info] [35m[XCUI Test][39m Retrying WDA startup (2 of 4)
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m
Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
```

```
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]
[39m xcodebuild exited with code '65' and signal 'null'
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WD Proxy][39m Matched
'/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WebDriverAgent][39m Waiting up to 60000ms for
WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
```

```
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
```

```
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body[info] [35m[WD Proxy][39m socket
hang up[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body[debug]
[35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]
[39m xcodebuild exited with code '65' and signal 'null'
[debug] [35m[BaseDriver][39m Event 'wdaStartFailed' logged at
1702116174920 (15:32:54 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Unable to launch WebDriverAgent because
of xcodebuild failure: xcodebuild failed with code 65
[debug] [35m[XCUITest][39m xcodebuild error message:
[debug] [35m[XCUITest][39m . Make sure you follow the tutorial at
https://github.com/appium/appium-xcuitest-driver/blob/master/docs/
real-device-config.md. Try to remove the WebDriverAgentRunner
application from the device if it is installed and reboot the
device.
[warn] [35m[XCUITest][39m Quitting and uninstalling WebDriverAgent
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug]
[35m[WebDriverAgent][39m No WDAs on the device.[debug]
[35m[BaseDriver][39m Event 'wdaStartAttempted' logged at
1702116195150 (15:33:15 GMT+0530 (India Standard Time))
[info] [35m[XCUITest][39m Retrying WDA startup (3 of 4)
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...[debug] [35m[WebDriverAgent][39m 'pgrep
-if xcodebuild.*00008110-001111392163801E' didn't detect any
matching processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp -destination
```



```
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m
Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100[debug] [35m[WD Proxy][39m Matched '/status' to command
name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body[debug]
[35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]
[39m xcodebuild exited with code '65' and signal 'null'
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
```

```
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WD Proxy][39m Matched
'/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WebDriverAgent][39m Waiting up to 60000ms for
WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
```

```
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
```

```
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]
[39m xcodebuild exited with code '65' and signal 'null'
[debug] [35m[BaseDriver][39m Event 'wdaStartFailed' logged at
1702116209553 (15:33:29 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Unable to launch WebDriverAgent because
of xcodebuild failure: xcodebuild failed with code 65
[debug] [35m[XCUITest][39m xcodebuild error message:
[debug] [35m[XCUITest][39m . Make sure you follow the tutorial at
https://github.com/appium/appium-xcuitest-driver/blob/master/docs/
real-device-config.md. Try to remove the WebDriverAgentRunner
application from the device if it is installed and reboot the
device.
[warn] [35m[XCUITest][39m Quitting and uninstalling WebDriverAgent
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug]
[35m[WebDriverAgent][39m No WDAs on the device.[debug]
[35m[BaseDriver][39m Event 'wdaStartAttempted' logged at
1702116229792 (15:33:49 GMT+0530 (India Standard Time))
[info] [35m[XCUITest][39m Retrying WDA startup (4 of 4)
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1[debug] [35m[WebDriverAgent][39m Waiting up
to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent][39m xcodebuild exited with code '65' and signal 'null'
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes 'xcodebuild.*00008110-001111392163801E' for the device 00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if xcodebuild.*00008110-001111392163801E' didn't detect any matching processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command 'xcodebuild test-without-building -project /Applications/Appium Server GUI 4729.app/Contents/Resources/app/node_modules/appium/node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/Developer/Xcode/DerivedData/WebDriverAgent-hfzvtfpgjncqtwdkwzghybzlzcqp -destination id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1 GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in directory '/Applications/Appium Server GUI 4729.app/Contents/Resources/app/node_modules/appium/node_modules/appium-webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be logged if any errors are present there. To change this, use 'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
```

```
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body[debug]
[35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
```

```
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]
[39m xcodebuild exited with code '65' and signal 'null'
[debug] [35m[BaseDriver][39m Event 'wdaStartFailed' logged at
1702116244120 (15:34:04 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Unable to launch WebDriverAgent because
of xcodebuild failure: xcodebuild failed with code 65
[debug] [35m[XCUITest][39m xcodebuild error message:
[debug] [35m[XCUITest][39m . Make sure you follow the tutorial at
https://github.com/appium/appium-xcuitest-driver/blob/master/docs/
real-device-config.md. Try to remove the WebDriverAgentRunner
application from the device if it is installed and reboot the
device.
[warn] [35m[XCUITest][39m Quitting and uninstalling WebDriverAgent
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug]
[35m[WebDriverAgent][39m No WDAs on the device.
[error] [35m[XCUITest][39m {}
[info] [35m[DevCon Factory][39m Releasing connections for
00008110-001111392163801E device on any port number
[info] [35m[DevCon Factory][39m Found cached connections to release:
["00008110-001111392163801E:8100"]
[info] [35m[DevCon Factory][39m Releasing the listener for
'00008110-001111392163801E:8100'
```

```
[debug] [35m[iProxy@00008110:8100][39m Closing the connection
[debug] [35m[DevCon Factory][39m Cached connections count: 0
[debug] [35m[XCUITest][39m Not clearing log files. Use
`clearSystemFiles` capability to turn on.
[info] [35m[iProxy@00008110:8100][39m The connection has been closed
[debug] [35m[BaseDriver][39m Event 'newSessionStarted' logged at
1702116244353 (15:34:04 GMT+0530 (India Standard Time))
[debug] [35m[W3C][39m Encountered internal error running command:
Error: Unable to launch WebDriverAgent because of xcodebuild
failure: xcodebuild failed with code 65
[debug] [35m[W3C][39m xcodebuild error message:
[debug] [35m[W3C][39m . Make sure you follow the tutorial at
https://github.com/appium/appium-xcuitest-driver/blob/master/docs/
real-device-config.md. Try to remove the WebDriverAgentRunner
application from the device if it is installed and reboot the
device.
[debug] [35m[W3C][39m      at quitAndUninstall (/Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-xcuitest-driver/lib/driver.js:585:15)
[debug] [35m[W3C][39m      at /Applications/Appium Server GUI
4729.app/Contents/Resources/app/node_modules/appium/node_modules/
appium-xcuitest-driver/lib/driver.js:620:11
[debug] [35m[W3C][39m      at wrapped (/Applications/Appium Server
GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/asyncbox/lib/asyncbox.js:60:13)
[debug] [35m[W3C][39m      at retry (/Applications/Appium Server GUI
4729.app/Contents/Resources/app/node_modules/appium/node_modules/
asyncbox/lib/asyncbox.js:43:13)
[debug] [35m[W3C][39m      at retryInterval (/Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/asyncbox/lib/asyncbox.js:70:10)
[debug] [35m[W3C][39m      at /Applications/Appium Server GUI
4729.app/Contents/Resources/app/node_modules/appium/node_modules/
appium-xcuitest-driver/lib/driver.js:600:7
[info] [35m[HTTP][39m [37m<-- POST /wd/hub/session [39m[31m500[39m
[90m123606 ms - 1423[39m
[info] [35m[HTTP][39m [90m[39m[info] [35m[HTTP][39m [37m-->[39m
[37mPOST[39m [37m/wd/hub/session[39m
[info] [35m[HTTP][39m [90m{"capabilities":{"alwaysMatch":
{"platformName":"iOS","appium:platformVersion":"17.1.2","appium:udid
":"00008110-001111392163801E","appium:deviceName":"iPhone
13","appium:automationName":"XCUITest","appium:bundleId":"org.uk.wwf
.myfootprint","appium:ignoreUnimportantViews":false,"appium:skipServ
erInstallation":false,"appium:useNewWDA":true,"appium:wdaStartupRetr
ies":4,"appium:iosInstallPause":0,"appium:wdaStartupRetryInterval":2
0000,"appium:newCommandTimeout":60,"appium:enableMultiWindows":false
,"appium:noReset":true,"appium:usePrebuiltWDA":true,"appium:includes
afariInWebviews":true,"appium:connectHardwareKeyboard":true},"firstM
atch":{}}},"desiredCapabilities":
{"platformName":"iOS","appium:platformVersion":"17.1.2","appium:udid
":"00008110-001111392163801E","appium:deviceName":"iPhone
13","appium:automationName":"XCUITest","appium:bundleId":"org.uk.wwf
.myfootprint","appium:ignoreUnimportantViews":false,"appium:skipServ
erInstallation":false,"appium:useNewWDA":true,"appium:wdaStartupRetr
```



```
ies":4,"appium:iosInstal... [39m
[debug] [35m[W3C][39m Calling AppiumDriver.createSession() with
args:
[{"platformName":"iOS","appium:platformVersion":"17.1.2","appium:udid":
"00008110-001111392163801E","appium:deviceName":"iPhone
13","appium:automationName":"XCUIest","appium:bundleId":"org.uk.wwf
.myfootprint","appium:ignoreUnimportantViews":false,"appium:skipServ
erInstallation":false,"appium:useNewWDA":true,"appium:wdaStartupRetr
ies":4,"appium:iosInstallPause":0,"appium:wdaStartupRetryInterval":2
0000,"appium:newCommandTimeout":60,"appium:enableMultiWindows":false
,"appium:noReset":true,"appium:usePrebuiltWDA":true,"appium:includes
afariInWebviews":true,"appium:connectHardwareKeyboard":true},null,
{"alwaysMatch":
{"platformName":"iOS","appium:platformVersion":"17.1.2","appium:udid
":"00008110-001111392163801E","appium:deviceName":"iPhone
13","appium:automationName":"XCUIest","appium:bundleId":"org.uk.wwf
.myfootprint","appium:ignoreUnimportantViews":false,"appium:skipServ
erInstallation":false,"appium:useNewWDA":true,"appium:wdaStartupRetr
ies":4,"appium:iosInstallPause":0,"appium:wdaStartupRetryInterval":2
0000,"a...
[debug] [35m[BaseDriver][39m Event 'newSessionRequested' logged at
1702118105578 (16:05:05 GMT+0530 (India Standard Time))
[info] [35m[Appium][39m Appium v1.22.3 creating new XCUIestDriver
(v3.59.0) session
[info] [35m[Appium][39m Applying relaxed security to
'XCUIestDriver' as per server command line argument. All insecure
features will be enabled unless explicitly disabled by --deny-
insecure
[debug] [35m[BaseDriver][39m W3C capabilities and MJSONWP desired
capabilities were provided
[debug] [35m[BaseDriver][39m Creating session with W3C capabilities:
{
[debug] [35m[BaseDriver][39m     "alwaysMatch": {
[debug] [35m[BaseDriver][39m       "platformName": "iOS",
[debug] [35m[BaseDriver][39m       "appium:platformVersion": "17.1.2",
[debug] [35m[BaseDriver][39m       "appium:udid":
"00008110-001111392163801E",
[debug] [35m[BaseDriver][39m       "appium:deviceName": "iPhone 13",
[debug] [35m[BaseDriver][39m       "appium:automationName":
"XCUIest",
[debug] [35m[BaseDriver][39m       "appium:bundleId":
"org.uk.wwf.myfootprint",
[debug] [35m[BaseDriver][39m       "appium:ignoreUnimportantViews":
false,
[debug] [35m[BaseDriver][39m       "appium:skipServerInstallation":
false,
[debug] [35m[BaseDriver][39m       "appium:useNewWDA": true,
[debug] [35m[BaseDriver][39m       "appium:wdaStartupRetries": 4,
[debug] [35m[BaseDriver][39m       "appium:iosInstallPause": 0,
[debug] [35m[BaseDriver][39m       "appium:wdaStartupRetryInterval":
20000,
[debug] [35m[BaseDriver][39m       "appium:newCommandTimeout": 60,
[debug] [35m[BaseDriver][39m       "appium:enableMultiWindows": false,
[debug] [35m[BaseDriver][39m       "appium:noReset": true,
```

```
[debug] [35m[BaseDriver][39m      "appium:usePrebuiltWDA": true,
[debug] [35m[BaseDriver][39m      "appium:includeSafariInWebviews":
true,
[debug] [35m[BaseDriver][39m      "appium:connectHardwareKeyboard":
true
[debug] [35m[BaseDriver][39m    },
[debug] [35m[BaseDriver][39m    "firstMatch": [
[debug] [35m[BaseDriver][39m      {}
[debug] [35m[BaseDriver][39m    ]
[debug] [35m[BaseDriver][39m  }
[warn] [35m[BaseDriver][39m The following capabilities were
provided, but are not recognized by Appium:
[warn] [35m[BaseDriver][39m   ignoreUnimportantViews
[warn] [35m[BaseDriver][39m   skipServerInstallation
[warn] [35m[BaseDriver][39m   enableMultiWindows
[info] [35m[BaseDriver][39m Session created with session id:
01d78b53-7c5b-41cd-9450-88e99d7f3739[debug] [35m[XCUITest][39m
Current user: 'rohitripathi'
[debug] [35m[XCUITest][39m Available devices:
00008110-001111392163801E
[debug] [35m[XCUITest][39m Creating iDevice object with udid
'00008110-001111392163801E'
[info] [35m[XCUITest][39m Determining device to run tests on: udid:
'00008110-001111392163801E', real device: true
[info] [35m[XCUITest][39m Normalized platformVersion capability
value '17.1.2' to '17.1'
[debug] [35m[BaseDriver][39m Event 'xcodeDetailsRetrieved' logged at
1702118106209 (16:05:06 GMT+0530 (India Standard Time))
[debug] [35m[BaseDriver][39m Event 'appConfigured' logged at
1702118106210 (16:05:06 GMT+0530 (India Standard Time))
[debug] [35m[BaseDriver][39m Event 'resetStarted' logged at
1702118106210 (16:05:06 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Reset: fullReset not set. Leaving as is
[debug] [35m[BaseDriver][39m Event 'resetComplete' logged at
1702118106211 (16:05:06 GMT+0530 (India Standard Time))
[info] [35m[WebDriverAgent][39m Using WDA path: '/Applications/
Appium Server GUI 4729.app/Contents/Resources/app/node_modules/
appium/node_modules/appium-webdriveragent'
[info] [35m[WebDriverAgent][39m Using WDA agent: '/Applications/
Appium Server GUI 4729.app/Contents/Resources/app/node_modules/
appium/node_modules/appium-webdriveragent/
WebDriverAgent.xcodeproj'[debug] [35m[XCUITest][39m Crash reports
root '/Users/rohitripathi/Library/Logs/CrashReporter/MobileDevice/
Pocketapp Admin's iPhone' does not exist. Got nothing to gather.
[debug] [35m[BaseDriver][39m Event 'logCaptureStarted' logged at
1702118106453 (16:05:06 GMT+0530 (India Standard Time))
[info] [35m[XCUITest][39m Setting up real device[debug]
[35m[WebDriverAgent][39m No obsolete cached processes from previous
WDA sessions listening on port 8100 have been found
[info] [35m[DevCon Factory][39m Requesting connection for device
00008110-001111392163801E on local port 8100, device port 8100
[debug] [35m[DevCon Factory][39m Cached connections count: 0
[info] [35m[DevCon Factory][39m Successfully requested the
connection for 00008110-001111392163801E:8100[debug]
```

```
[35m[WebDriverAgent][39m Parsed BUILD_DIR configuration value: '/
Users/rohitrupathi/Library/Developer/Xcode/DerivedData/
WebDriverAgent-hfzvtfpgjncqtwdkwzghybzlcqp/Build/Products'
[debug] [35m[WebDriverAgent][39m Got derived data root: '/Users/
rohitrupathi/Library/Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp'
[debug] [35m[XCUITest][39m Starting WebDriverAgent initialization
with the synchronization key '/Users/rohitrupathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp'
[debug] [35m[XCUITest][39m Capability 'useNewWDA' set to true, so
uninstalling WDA before proceeding
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug]
[35m[WebDriverAgent][39m No WDAs on the device.
[debug] [35m[BaseDriver][39m Event 'wdaUninstalled' logged at
1702118110913 (16:05:10 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Trying to start WebDriverAgent 4 times
with 20000ms interval
[debug] [35m[BaseDriver][39m Event 'wdaStartAttempted' logged at
1702118110913 (16:05:10 GMT+0530 (India Standard Time))
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m
Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent][39m xcodebuild exited with code '65' and signal 'null'
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes 'xcodebuild.*00008110-001111392163801E' for the device 00008110-001111392163801E...[debug] [35m[WebDriverAgent][39m 'pgrep -if xcodebuild.*00008110-001111392163801E' didn't detect any matching processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command 'xcodebuild test-without-building -project /Applications/Appium Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
```

```
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WebDriverAgent]
[39m Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
```

```
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]
[39m xcodebuild exited with code '65' and signal 'null'
[debug] [35m[BaseDriver][39m Event 'wdaStartFailed' logged at
1702118126996 (16:05:26 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Unable to launch WebDriverAgent because
of xcodebuild failure: xcodebuild failed with code 65
[debug] [35m[XCUITest][39m xcodebuild error message:
[debug] [35m[XCUITest][39m . Make sure you follow the tutorial at
https://github.com/appium/appium-xcuitest-driver/blob/master/docs/
real-device-config.md. Try to remove the WebDriverAgentRunner
```

application from the device if it is installed and reboot the device.

```
[warn] [35m[XCUITest][39m Quitting and uninstalling WebDriverAgent
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug]
[35m[WebDriverAgent][39m No WDAs on the device.[debug]
[35m[BaseDriver][39m Event 'wdaStartAttempted' logged at
1702118147228 (16:05:47 GMT+0530 (India Standard Time))
[info] [35m[XCUITest][39m Retrying WDA startup (2 of 4)
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...[debug] [35m[WebDriverAgent][39m 'pgrep
-if xcodebuild.*00008110-001111392163801E' didn't detect any
matching processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohittripathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m
Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body[debug]
[35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
```

```
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]
[39m xcodebuild exited with code '65' and signal 'null'
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WD Proxy][39m Matched
'/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WebDriverAgent][39m Waiting up to 60000ms for
```



```
'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body[debug]  
[35m[iProxy@00008110:8100][39m Connection was refused to port 8100  
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m  
Matched '/status' to command name 'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to  
port 8100  
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m  
Matched '/status' to command name 'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to  
port 8100  
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m  
Matched '/status' to command name 'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to  
port 8100  
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]  
[39m xcodebuild exited with code '65' and signal 'null'  
[debug] [35m[BaseDriver][39m Event 'wdaStartFailed' logged at  
1702118162051 (16:06:02 GMT+0530 (India Standard Time))  
[debug] [35m[XCUITest][39m Unable to launch WebDriverAgent because  
of xcodebuild failure: xcodebuild failed with code 65  
[debug] [35m[XCUITest][39m xcodebuild error message:  
[debug] [35m[XCUITest][39m . Make sure you follow the tutorial at  
https://github.com/appium/appium-xcuitest-driver/blob/master/docs/  
real-device-config.md. Try to remove the WebDriverAgentRunner  
application from the device if it is installed and reboot the  
device.  
[warn] [35m[XCUITest][39m Quitting and uninstalling WebDriverAgent  
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug]  
[35m[WebDriverAgent][39m No WDAs on the device.[debug]  
[35m[BaseDriver][39m Event 'wdaStartAttempted' logged at  
1702118182290 (16:06:22 GMT+0530 (India Standard Time))  
[info] [35m[XCUITest][39m Retrying WDA startup (3 of 4)  
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the  
device[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a  
cleanup. The sources are up to date (1680522269116 >= 1664354587000)  
[debug] [35m[WebDriverAgent][39m Killing running processes  
'xcodebuild.*00008110-001111392163801E' for the device  
00008110-001111392163801E...  
[debug] [35m[WebDriverAgent][39m 'pgrep -if  
xcodebuild.*00008110-001111392163801E' didn't detect any matching
```

```
processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohittrpathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m
Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body[debug]
[35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent][39m xcodebuild exited with code '65' and signal 'null'
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes 'xcodebuild.*00008110-001111392163801E' for the device 00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if xcodebuild.*00008110-001111392163801E' didn't detect any matching processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command 'xcodebuild test-without-building -project /Applications/Appium Server GUI 4729.app/Contents/Resources/app/node_modules/appium/node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/Developer/Xcode/DerivedData/WebDriverAgent-hfzvtfpgjncqtwdkwzghybzlcqp -destination id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1 GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in directory '/Applications/Appium Server GUI 4729.app/Contents/Resources/app/node_modules/appium/node_modules/appium-webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be logged if any errors are present there. To change this, use 'showXcodeLog' desired capability[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WebDriverAgent][39m Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100[debug] [35m[WD Proxy][39m Matched '/status' to command
name 'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body[debug]
[35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent][39m xcodebuild exited with code '65' and signal 'null'
[debug] [35m[BaseDriver][39m Event 'wdaStartFailed' logged at 1702118196985 (16:06:36 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Unable to launch WebDriverAgent because of xcodebuild failure: xcodebuild failed with code 65
[debug] [35m[XCUITest][39m xcodebuild error message:
[debug] [35m[XCUITest][39m . Make sure you follow the tutorial at https://github.com/appium/appium-xcuitest-driver/blob/master/docs/real-device-config.md. Try to remove the WebDriverAgentRunner application from the device if it is installed and reboot the device.
[warn] [35m[XCUITest][39m Quitting and uninstalling WebDriverAgent
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug]
[35m[BaseDriver][39m Event 'wdaStartAttempted' logged at 1702118217218 (16:06:57 GMT+0530 (India Standard Time))
[info] [35m[XCUITest][39m Retrying WDA startup (4 of 4)
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes 'xcodebuild.*00008110-001111392163801E' for the device 00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if xcodebuild.*00008110-001111392163801E' didn't detect any matching processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command 'xcodebuild test-without-building -project /Applications/Appium Server GUI 4729.app/Contents/Resources/app/node_modules/appium/node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/Developer/Xcode/DerivedData/WebDriverAgent-hfzvtfpgjncqtwdkwzghybzlcqp -destination id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1 GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in directory '/Applications/Appium Server GUI 4729.app/Contents/Resources/app/node_modules/appium/node_modules/appium-webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be logged if any errors are present there. To change this, use 'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
```

```
'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to  
port 8100  
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m  
Matched '/status' to command name 'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to  
port 8100  
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m  
Matched '/status' to command name 'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to  
port 8100  
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m  
Matched '/status' to command name 'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to  
port 8100  
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m  
Matched '/status' to command name 'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to  
port 8100  
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m  
Matched '/status' to command name 'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to  
port 8100  
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]  
[39m xcodebuild exited with code '65' and signal 'null'  
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the  
device  
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a  
cleanup. The sources are up to date (1680522269116 >= 1664354587000)  
[debug] [35m[WebDriverAgent][39m Killing running processes  
'xcodebuild.*00008110-001111392163801E' for the device  
00008110-001111392163801E...  
[debug] [35m[WebDriverAgent][39m 'pgrep -if  
xcodebuild.*00008110-001111392163801E' didn't detect any matching  
processes. Return code: 1  
[debug] [35m[WebDriverAgent][39m Beginning test with command
```

```
'xcodebuild test-without-building -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohittripathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlzcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
```

```
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WD Proxy][39m Matched
'/status' to command name 'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
```

```
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
```

```
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WebDriverAgent]
[39m Waiting up to 60000ms for WebDriverAgent to start
```

```
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
```

```
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
```

```
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
```

```
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
```

```
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
```

```
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
```

```
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
```

```
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
```

```
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
```

```
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
```

```
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
```



```
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100[debug] [35m[WD Proxy][39m Matched '/status' to command
name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body[debug]
[35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body[debug]
[35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]
[39m xcodebuild exited with code '65' and signal 'null'
[debug] [35m[BaseDriver][39m Event 'wdaStartFailed' logged at
1702118232052 (16:07:12 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Unable to launch WebDriverAgent because
of xcodebuild failure: xcodebuild failed with code 65
[debug] [35m[XCUITest][39m xcodebuild error message:
[debug] [35m[XCUITest][39m . Make sure you follow the tutorial at
https://github.com/appium/appium-xcuitest-driver/blob/master/docs/
real-device-config.md. Try to remove the WebDriverAgentRunner
application from the device if it is installed and reboot the
device.
[warn] [35m[XCUITest][39m Quitting and uninstalling WebDriverAgent
```

```
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug]
[35m[WebDriverAgent][39m No WDAs on the device.
[error] [35m[XCUITest][39m {}
[info] [35m[DevCon Factory][39m Releasing connections for
00008110-001111392163801E device on any port number
[info] [35m[DevCon Factory][39m Found cached connections to release:
["00008110-001111392163801E:8100"]
[info] [35m[DevCon Factory][39m Releasing the listener for
'00008110-001111392163801E:8100'
[debug] [35m[iProxy@00008110:8100][39m Closing the connection
[debug] [35m[DevCon Factory][39m Cached connections count: 0
[debug] [35m[XCUITest][39m Not clearing log files. Use
`clearSystemFiles` capability to turn on.
[info] [35m[iProxy@00008110:8100][39m The connection has been closed
[debug] [35m[BaseDriver][39m Event 'newSessionStarted' logged at
1702118232286 (16:07:12 GMT+0530 (India Standard Time))
[debug] [35m[W3C][39m Encountered internal error running command:
Error: Unable to launch WebDriverAgent because of xcodebuild
failure: xcodebuild failed with code 65
[debug] [35m[W3C][39m xcodebuild error message:
[debug] [35m[W3C][39m . Make sure you follow the tutorial at
https://github.com/appium/appium-xcuitest-driver/blob/master/docs/
real-device-config.md. Try to remove the WebDriverAgentRunner
application from the device if it is installed and reboot the
device.
[debug] [35m[W3C][39m      at quitAndUninstall (/Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-xcuitest-driver/lib/driver.js:585:15)
[debug] [35m[W3C][39m      at /Applications/Appium Server GUI
4729.app/Contents/Resources/app/node_modules/appium/node_modules/
appium-xcuitest-driver/lib/driver.js:620:11
[debug] [35m[W3C][39m      at wrapped (/Applications/Appium Server
GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/asyncbox/lib/asyncbox.js:60:13)
[debug] [35m[W3C][39m      at retry (/Applications/Appium Server GUI
4729.app/Contents/Resources/app/node_modules/appium/node_modules/
asyncbox/lib/asyncbox.js:43:13)
[debug] [35m[W3C][39m      at retryInterval (/Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/asyncbox/lib/asyncbox.js:70:10)
[debug] [35m[W3C][39m      at /Applications/Appium Server GUI
4729.app/Contents/Resources/app/node_modules/appium/node_modules/
appium-xcuitest-driver/lib/driver.js:600:7
[info] [35m[HTTP][39m [37m<-- POST /wd/hub/session [39m[31m500[39m
[90m126724 ms - 1423[39m
[info] [35m[HTTP][39m [90m[39m[info] [35m[HTTP][39m [37m-->[39m
[37mPOST[39m [37m/wd/hub/session[39m
[info] [35m[HTTP][39m [90m{"capabilities":{"alwaysMatch":
{"platformName":"iOS","appium:platformVersion":"17.1.2","appium:udid
":"00008110-001111392163801E","appium:deviceName":"iPhone
13","appium:automationName":"XCUITest","appium:bundleId":"org.uk.wwf
.myfootprint","appium:ignoreUnimportantViews":false,"appium:skipServ
erInstallation":false,"appium:useNewWDA":true,"appium:wdaStartupRetr
ies":4,"appium:iosInstallPause":0,"appium:wdaStartupRetryInterval":2
```

```
0000,"appium:newCommandTimeout":60,"appium:enableMultiWindows":false
,"appium:noReset":true,"appium:usePrebuiltWDA":true,"appium:allowPro
visioningDeviceRegistration":true,"appium:includeSafariInWebviews":t
rue,"appium:connectHardwareKeyboard":true},"firstMatch":
[{}]},"desiredCapabilities":
{"platformName":"iOS","appium:platformVersion":"17.1.2","appium:udid
":"00008110-001111392163801E","appium:deviceName":"iPhone
13","appium:automationName":"XCUIest","appium:bundleId":"org.uk.wwf
.myfootprint","appium:ignoreUnimportantViews":false,"appium:skipServ
erInstallation":false,"appium:useNewWDA":t... [39m
[debug] [35m[W3C][39m Calling AppiumDriver.createSession() with
args:
[{"platformName":"iOS","appium:platformVersion":"17.1.2","appium:udi
d":"00008110-001111392163801E","appium:deviceName":"iPhone
13","appium:automationName":"XCUIest","appium:bundleId":"org.uk.wwf
.myfootprint","appium:ignoreUnimportantViews":false,"appium:skipServ
erInstallation":false,"appium:useNewWDA":true,"appium:wdaStartupRetr
ies":4,"appium:iosInstallPause":0,"appium:wdaStartupRetryInterval":2
0000,"appium:newCommandTimeout":60,"appium:enableMultiWindows":false
,"appium:noReset":true,"appium:usePrebuiltWDA":true,"appium:allowPro
visioningDeviceRegistration":true,"appium:includeSafariInWebviews":t
rue,"appium:connectHardwareKeyboard":true},null,{"alwaysMatch":
{"platformName":"iOS","appium:platformVersion":"17.1.2","appium:udid
":"00008110-001111392163801E","appium:deviceName":"iPhone
13","appium:automationName":"XCUIest","appium:bundleId":"org.uk.wwf
.myfootprint","appium:ignoreUnimportantViews":false,"appium:skipServ
erInstallation":false,"appium:useNewWDA":true,"appium:wdaStartupRetr
ies":4,"appium:iosInstall...
[debug] [35m[BaseDriver][39m Event 'newSessionRequested' logged at
1702124036988 (17:43:56 GMT+0530 (India Standard Time))
[info] [35m[Appium][39m Appium v1.22.3 creating new XCUIestDriver
(v3.59.0) session
[info] [35m[Appium][39m Applying relaxed security to
'XCUIestDriver' as per server command line argument. All insecure
features will be enabled unless explicitly disabled by --deny-
insecure
[debug] [35m[BaseDriver][39m W3C capabilities and MJSONWP desired
capabilities were provided
[debug] [35m[BaseDriver][39m Creating session with W3C capabilities:
{
[debug] [35m[BaseDriver][39m   "alwaysMatch": {
[debug] [35m[BaseDriver][39m     "platformName": "iOS",
[debug] [35m[BaseDriver][39m     "appium:platformVersion": "17.1.2",
[debug] [35m[BaseDriver][39m     "appium:udid":
"00008110-001111392163801E",
[debug] [35m[BaseDriver][39m     "appium:deviceName": "iPhone 13",
[debug] [35m[BaseDriver][39m     "appium:automationName":
"XCUIest",
[debug] [35m[BaseDriver][39m     "appium:bundleId":
"org.uk.wwf.myfootprint",
[debug] [35m[BaseDriver][39m     "appium:ignoreUnimportantViews":
false,
[debug] [35m[BaseDriver][39m     "appium:skipServerInstallation":
false,
```

```

[debug] [35m[BaseDriver][39m      "appium:useNewWDA": true,
[debug] [35m[BaseDriver][39m      "appium:wdaStartupRetries": 4,
[debug] [35m[BaseDriver][39m      "appium:iosInstallPause": 0,
[debug] [35m[BaseDriver][39m      "appium:wdaStartupRetryInterval":
20000,
[debug] [35m[BaseDriver][39m      "appium:newCommandTimeout": 60,
[debug] [35m[BaseDriver][39m      "appium:enableMultiWindows": false,
[debug] [35m[BaseDriver][39m      "appium:noReset": true,
[debug] [35m[BaseDriver][39m      "appium:usePrebuiltWDA": true,
"appium:allowProvisioningDeviceRegistration": true,
[debug] [35m[BaseDriver][39m      "appium:includeSafariInWebviews":
true,
[debug] [35m[BaseDriver][39m      "appium:connectHardwareKeyboard":
true
[debug] [35m[BaseDriver][39m    },
[debug] [35m[BaseDriver][39m    "firstMatch": [
[debug] [35m[BaseDriver][39m      {}
[debug] [35m[BaseDriver][39m    ]
[debug] [35m[BaseDriver][39m  }
[warn] [35m[BaseDriver][39m The following capabilities were
provided, but are not recognized by Appium:
[warn] [35m[BaseDriver][39m   ignoreUnimportantViews
[warn] [35m[BaseDriver][39m   skipServerInstallation
[warn] [35m[BaseDriver][39m   enableMultiWindows
[info] [35m[BaseDriver][39m Session created with session id:
cdf53d2a-25f5-4789-8838-2ee084c412da[debug] [35m[XCUITest][39m
Current user: 'rohittripathi'
[debug] [35m[XCUITest][39m Available devices:
00008110-001111392163801E
[debug] [35m[XCUITest][39m Creating iDevice object with udid
'00008110-001111392163801E'
[info] [35m[XCUITest][39m Determining device to run tests on: udid:
'00008110-001111392163801E', real device: true
[info] [35m[XCUITest][39m Normalized platformVersion capability
value '17.1.2' to '17.1'
[debug] [35m[BaseDriver][39m Event 'xcodeDetailsRetrieved' logged at
1702124037596 (17:43:57 GMT+0530 (India Standard Time))
[debug] [35m[BaseDriver][39m Event 'appConfigured' logged at
1702124037597 (17:43:57 GMT+0530 (India Standard Time))
[debug] [35m[BaseDriver][39m Event 'resetStarted' logged at
1702124037597 (17:43:57 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Reset: fullReset not set. Leaving as is
[debug] [35m[BaseDriver][39m Event 'resetComplete' logged at
1702124037597 (17:43:57 GMT+0530 (India Standard Time))
[info] [35m[WebDriverAgent][39m Using WDA path: '/Applications/
Appium Server GUI 4729.app/Contents/Resources/app/node_modules/
appium/node_modules/appium-webdriveragent'
[info] [35m[WebDriverAgent][39m Using WDA agent: '/Applications/
Appium Server GUI 4729.app/Contents/Resources/app/node_modules/
appium/node_modules/appium-webdriveragent/
WebDriverAgent.xcodeproj'[debug] [35m[XCUITest][39m Crash reports
root '/Users/rohittripathi/Library/Logs/CrashReporter/MobileDevice/
Pocketapp Admin's iPhone' does not exist. Got nothing to gather.

```

```
[debug] [35m[BaseDriver][39m Event 'logCaptureStarted' logged at
1702124037840 (17:43:57 GMT+0530 (India Standard Time))
[info] [35m[XCUITest][39m Setting up real device[debug]
[35m[WebDriverAgent][39m No obsolete cached processes from previous
WDA sessions listening on port 8100 have been found
[info] [35m[DevCon Factory][39m Requesting connection for device
00008110-001111392163801E on local port 8100, device port 8100
[debug] [35m[DevCon Factory][39m Cached connections count: 0
[info] [35m[DevCon Factory][39m Successfully requested the
connection for 00008110-001111392163801E:8100[debug]
[35m[WebDriverAgent][39m Parsed BUILD_DIR configuration value: '/
Users/rohittripathi/Library/Developer/Xcode/DerivedData/
WebDriverAgent-hfzvtfpgjncqtwdkwzghyblzlcqp/Build/Products'
[debug] [35m[WebDriverAgent][39m Got derived data root: '/Users/
rohittripathi/Library/Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghyblzlcqp'
[debug] [35m[XCUITest][39m Starting WebDriverAgent initialization
with the synchronization key '/Users/rohittripathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghyblzlcqp'
[debug] [35m[XCUITest][39m Capability 'useNewWDA' set to true, so
uninstalling WDA before proceeding
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug]
[35m[WebDriverAgent][39m No WDAs on the device.
[debug] [35m[BaseDriver][39m Event 'wdaUninstalled' logged at
1702124041855 (17:44:01 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Trying to start WebDriverAgent 4 times
with 20000ms interval
[debug] [35m[BaseDriver][39m Event 'wdaStartAttempted' logged at
1702124041855 (17:44:01 GMT+0530 (India Standard Time))
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -allowProvisioningUpdates
-allowProvisioningDeviceRegistration -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohittripathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghyblzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
```

logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m
Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]
[39m xcodebuild exited with code '65' and signal 'null'
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the

```
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -allowProvisioningUpdates
-allowProvisioningDeviceRegistration -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WD Proxy][39m Matched
'/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WebDriverAgent]
[39m Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
```

```
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
```



```
'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to  
port 8100  
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]  
[39m xcodebuild exited with code '65' and signal 'null'  
[debug] [35m[BaseDriver][39m Event 'wdaStartFailed' logged at  
1702124057202 (17:44:17 GMT+0530 (India Standard Time))  
[debug] [35m[XCUITest][39m Unable to launch WebDriverAgent because  
of xcodebuild failure: xcodebuild failed with code 65  
[debug] [35m[XCUITest][39m xcodebuild error message:  
[debug] [35m[XCUITest][39m . Make sure you follow the tutorial at  
https://github.com/appium/appium-xcuitest-driver/blob/master/docs/  
real-device-config.md. Try to remove the WebDriverAgentRunner  
application from the device if it is installed and reboot the  
device.  
[warn] [35m[XCUITest][39m Quitting and uninstalling WebDriverAgent  
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug]  
[35m[WebDriverAgent][39m No WDAs on the device.[debug]  
[35m[BaseDriver][39m Event 'wdaStartAttempted' logged at  
1702124077445 (17:44:37 GMT+0530 (India Standard Time))  
[info] [35m[XCUITest][39m Retrying WDA startup (2 of 4)  
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the  
device  
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a  
cleanup. The sources are up to date (1680522269116 >= 1664354587000)  
[debug] [35m[WebDriverAgent][39m Killing running processes  
'xcodebuild.*00008110-001111392163801E' for the device  
00008110-001111392163801E...[debug] [35m[WebDriverAgent][39m 'pgrep  
-if xcodebuild.*00008110-001111392163801E' didn't detect any  
matching processes. Return code: 1  
[debug] [35m[WebDriverAgent][39m Beginning test with command  
'xcodebuild test-without-building -allowProvisioningUpdates  
-allowProvisioningDeviceRegistration -project /Applications/Appium  
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/  
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme  
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/  
Developer/Xcode/DerivedData/WebDriverAgent-  
hfzvtfpgjncqtwdkwzghybzlcqp -destination  
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1  
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in  
directory '/Applications/Appium Server GUI 4729.app/Contents/  
Resources/app/node_modules/appium/node_modules/appium-  
webdriveragent'  
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be  
logged if any errors are present there. To change this, use  
'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m  
Waiting up to 60000ms for WebDriverAgent to start  
[debug] [35m[WD Proxy][39m Matched '/status' to command name  
'getStatus'  
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://  
127.0.0.1:8100/status] with no body  
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
```

```
port 8100[debug] [35m[WD Proxy][39m Matched '/status' to command
name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]
[39m xcodebuild exited with code '65' and signal 'null'
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1
```

```
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -allowProvisioningUpdates
-allowProvisioningDeviceRegistration -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohittrpathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghyblzcp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m
Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
```

```
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body[debug]
[35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body[debug]
[35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]
[39m xcodebuild exited with code '65' and signal 'null'
[debug] [35m[BaseDriver][39m Event 'wdaStartFailed' logged at
1702124094887 (17:44:54 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Unable to launch WebDriverAgent because
```

```
of xcodebuild failure: xcodebuild failed with code 65
[debug] [35m[XCUITest][39m xcodebuild error message:
[debug] [35m[XCUITest][39m . Make sure you follow the tutorial at
https://github.com/appium/appium-xcuitest-driver/blob/master/docs/
real-device-config.md. Try to remove the WebDriverAgentRunner
application from the device if it is installed and reboot the
device.
[warn] [35m[XCUITest][39m Quitting and uninstalling WebDriverAgent
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug]
[35m[WebDriverAgent][39m No WDAs on the device.[debug]
[35m[BaseDriver][39m Event 'wdaStartAttempted' logged at
1702124115130 (17:45:15 GMT+0530 (India Standard Time))
[info] [35m[XCUITest][39m Retrying WDA startup (3 of 4)
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...
[debug] [35m[WebDriverAgent][39m 'pgrep -if
xcodebuild.*00008110-001111392163801E' didn't detect any matching
processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -allowProvisioningUpdates
-allowProvisioningDeviceRegistration -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghyblzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m
Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
```

```
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent][39m xcodebuild exited with code '65' and signal 'null'
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes 'xcodebuild.*00008110-001111392163801E' for the device 00008110-001111392163801E...[debug] [35m[WebDriverAgent][39m 'pgrep -if xcodebuild.*00008110-001111392163801E' didn't detect any matching processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command 'xcodebuild test-without-building -allowProvisioningUpdates -allowProvisioningDeviceRegistration -project /Applications/Appium Server GUI 4729.app/Contents/Resources/app/node_modules/appium/node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/Developer/Xcode/DerivedData/WebDriverAgent-hfzvtfpgjncqtwdkwzghybzlcqp -destination id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1 GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in directory '/Applications/Appium Server GUI 4729.app/Contents/Resources/app/node_modules/appium/node_modules/appium-webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be logged if any errors are present there. To change this, use
```

```
'showXcodeLog' desired capability
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WebDriverAgent]
[39m Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
```

```
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]
[39m xcodebuild exited with code '65' and signal 'null'
[debug] [35m[BaseDriver][39m Event 'wdaStartFailed' logged at
1702124130429 (17:45:30 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Unable to launch WebDriverAgent because
of xcodebuild failure: xcodebuild failed with code 65
[debug] [35m[XCUITest][39m xcodebuild error message:
[debug] [35m[XCUITest][39m . Make sure you follow the tutorial at
https://github.com/appium/appium-xcuitest-driver/blob/master/docs/
real-device-config.md. Try to remove the WebDriverAgentRunner
application from the device if it is installed and reboot the
device.
[warn] [35m[XCUITest][39m Quitting and uninstalling WebDriverAgent
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug]
[35m[WebDriverAgent][39m No WDAs on the device.[debug]
[35m[BaseDriver][39m Event 'wdaStartAttempted' logged at
1702124150676 (17:45:50 GMT+0530 (India Standard Time))
[info] [35m[XCUITest][39m Retrying WDA startup (4 of 4)
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
```



```
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...[debug] [35m[WebDriverAgent][39m 'pgrep
-if xcodebuild.*00008110-001111392163801E' didn't detect any
matching processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -allowProvisioningUpdates
-allowProvisioningDeviceRegistration -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlcqp -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WebDriverAgent][39m
Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body[debug]
[35m[iProxy@00008110:8100][39m Connection was refused to port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
```

```
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]
[39m xcodebuild exited with code '65' and signal 'null'
[info] [35m[WebDriverAgent][39m Launching WebDriverAgent on the
device
[info] [35m[WebDriverAgent][39m WebDriverAgent does not need a
cleanup. The sources are up to date (1680522269116 >= 1664354587000)
[debug] [35m[WebDriverAgent][39m Killing running processes
'xcodebuild.*00008110-001111392163801E' for the device
00008110-001111392163801E...[debug] [35m[WebDriverAgent][39m 'pgrep
-if xcodebuild.*00008110-001111392163801E' didn't detect any
matching processes. Return code: 1
[debug] [35m[WebDriverAgent][39m Beginning test with command
'xcodebuild test-without-building -allowProvisioningUpdates
-allowProvisioningDeviceRegistration -project /Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-webdriveragent/WebDriverAgent.xcodeproj -scheme
WebDriverAgentRunner -derivedDataPath /Users/rohitrupathi/Library/
Developer/Xcode/DerivedData/WebDriverAgent-
hfzvtfpgjncqtwdkwzghybzlzcpq -destination
id=00008110-001111392163801E IPHONEOS_DEPLOYMENT_TARGET=17.1
GCC_TREAT_WARNINGS_AS_ERRORS=0 COMPILER_INDEX_STORE_ENABLE=NO' in
directory '/Applications/Appium Server GUI 4729.app/Contents/
Resources/app/node_modules/appium/node_modules/appium-
webdriveragent'
[debug] [35m[WebDriverAgent][39m Output from xcodebuild will only be
logged if any errors are present there. To change this, use
'showXcodeLog' desired capability[debug] [35m[WD Proxy][39m Matched
'/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WebDriverAgent]
[39m Waiting up to 60000ms for WebDriverAgent to start
[debug] [35m[WD Proxy][39m Matched '/status' to command name
'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
```



```
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[debug] [35m[WD Proxy][39m
Matched '/status' to command name 'getStatus'
[debug] [35m[WD Proxy][39m Proxying [GET /status] to [GET http://
127.0.0.1:8100/status] with no body
[debug] [35m[iProxy@00008110:8100][39m Connection was refused to
port 8100
[info] [35m[WD Proxy][39m socket hang up[error] [35m[WebDriverAgent]
[39m xcodebuild exited with code '65' and signal 'null'
[debug] [35m[BaseDriver][39m Event 'wdaStartFailed' logged at
1702124168630 (17:46:08 GMT+0530 (India Standard Time))
[debug] [35m[XCUITest][39m Unable to launch WebDriverAgent because
of xcodebuild failure: xcodebuild failed with code 65
[debug] [35m[XCUITest][39m xcodebuild error message:
[debug] [35m[XCUITest][39m . Make sure you follow the tutorial at
https://github.com/appium/appium-xcuitest-driver/blob/master/docs/
real-device-config.md. Try to remove the WebDriverAgentRunner
application from the device if it is installed and reboot the
device.
[warn] [35m[XCUITest][39m Quitting and uninstalling WebDriverAgent
[info] [35m[WebDriverAgent][39m Shutting down sub-processes[debug]
[35m[WebDriverAgent][39m No WDAs on the device.
[error] [35m[XCUITest][39m {}
[info] [35m[DevCon Factory][39m Releasing connections for
00008110-001111392163801E device on any port number
[info] [35m[DevCon Factory][39m Found cached connections to release:
```

```
["00008110-001111392163801E:8100"]
[info] [35m[DevCon Factory][39m Releasing the listener for
'00008110-001111392163801E:8100'
[debug] [35m[iProxy@00008110:8100][39m Closing the connection
[debug] [35m[DevCon Factory][39m Cached connections count: 0
[debug] [35m[XCUITest][39m Not clearing log files. Use
`clearSystemFiles` capability to turn on.
[info] [35m[iProxy@00008110:8100][39m The connection has been closed
[debug] [35m[BaseDriver][39m Event 'newSessionStarted' logged at
1702124168881 (17:46:08 GMT+0530 (India Standard Time))
[debug] [35m[W3C][39m Encountered internal error running command:
Error: Unable to launch WebDriverAgent because of xcodebuild
failure: xcodebuild failed with code 65
[debug] [35m[W3C][39m xcodebuild error message:
[debug] [35m[W3C][39m . Make sure you follow the tutorial at
https://github.com/appium/appium-xcuitest-driver/blob/master/docs/
real-device-config.md. Try to remove the WebDriverAgentRunner
application from the device if it is installed and reboot the
device.
[debug] [35m[W3C][39m      at quitAndUninstall (/Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/appium-xcuitest-driver/lib/driver.js:585:15)
[debug] [35m[W3C][39m      at /Applications/Appium Server GUI
4729.app/Contents/Resources/app/node_modules/appium/node_modules/
appium-xcuitest-driver/lib/driver.js:620:11
[debug] [35m[W3C][39m      at wrapped (/Applications/Appium Server
GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/asyncbox/lib/asyncbox.js:60:13)
[debug] [35m[W3C][39m      at retry (/Applications/Appium Server GUI
4729.app/Contents/Resources/app/node_modules/appium/node_modules/
asyncbox/lib/asyncbox.js:43:13)
[debug] [35m[W3C][39m      at retryInterval (/Applications/Appium
Server GUI 4729.app/Contents/Resources/app/node_modules/appium/
node_modules/asyncbox/lib/asyncbox.js:70:10)
[debug] [35m[W3C][39m      at /Applications/Appium Server GUI
4729.app/Contents/Resources/app/node_modules/appium/node_modules/
appium-xcuitest-driver/lib/driver.js:600:7
[info] [35m[HTTP][39m [37m<-- POST /wd/hub/session [39m[31m500[39m
[90m131904 ms - 1423[39m
[info] [35m[HTTP][39m [90m[39m
```