
qbittorrent-api

Release 2024.12.72.dev10+gef6ae48

Russell Martin

Feb 11, 2025

CONTENTS

1	Introduction	1
	Python Module Index	77
	Index	79

INTRODUCTION

Python client implementation for qBittorrent Web API.

Currently supports qBittorrent v5.0.3 (Web API v2.11.2) released on Dec 15, 2024.

1.1 Features

- The entire qBittorrent Web API is implemented.
- qBittorrent version checking for an endpoint's existence/features is automatically handled.
- If the authentication cookie expires, a new one is automatically requested in line with any API call.

1.2 Installation

- Install via pip from PyPI:

```
python -m pip install qbittorrent-api
```

- Install a specific release (e.g. v2024.3.60):

```
python -m pip install qbittorrent-api==2024.3.60
```

- Install direct from main:

```
pip install git+https://github.com/rmartin16/qbittorrent-api.git@main#egg=qbittorrent-api
```

- Enable WebUI in qBittorrent: Tools -> Preferences -> Web UI
- If the Web API will be exposed to the Internet, follow the recommendations.

1.3 Getting Started

```
import qbittorrentapi

# instantiate a Client using the appropriate WebUI configuration
conn_info = dict(
    host="localhost",
    port=8080,
```

(continues on next page)

(continued from previous page)

```
username="admin",
password="adminadmin",
)
qbt_client = qbittorrentapi.Client(**conn_info)

# the Client will automatically acquire/maintain a logged-in state
# in line with any request. therefore, this is not strictly necessary;
# however, you may want to test the provided login credentials.
try:
    qbt_client.auth_log_in()
except qbittorrentapi.LoginFailed as e:
    print(e)

# if the Client will not be long-lived or many Clients may be created
# in a relatively short amount of time, be sure to log out:
qbt_client.auth_log_out()

# or use a context manager:
with qbittorrentapi.Client(**conn_info) as qbt_client:
    if qbt_client.torrents_add(urls="...") != "Ok.":
        raise Exception("Failed to add torrent.")

# display qBittorrent info
print(f"qBittorrent: {qbt_client.app.version}")
print(f"qBittorrent Web API: {qbt_client.app.web_api_version}")
for k, v in qbt_client.app.build_info.items():
    print(f"{k}: {v}")

# retrieve and show all torrents
for torrent in qbt_client.torrents_info():
    print(f"{torrent.hash[-6:]}: {torrent.name} ({torrent.state})")

# stop all torrents
qbt_client.torrents.stop.all()
```

1.4 Usage

First, the Web API endpoints are organized in to eight namespaces.

- Authentication (auth)
- Application (app)
- Log (log)
- Sync (sync)
- Transfer (transfer)
- Torrent Management (torrents)
- RSS (rss)
- Search (search)

Second, this client has two modes of interaction with the qBittorrent Web API.

Each Web API endpoint is implemented one-to-one as a method of the instantiated client.

```
import qbittorrentapi
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
    ↪ 'adminadmin')
qbt_client.app_version()
qbt_client.rss_rules()
qbt_client.torrents_info()
qbt_client.torrents_resume(torrent_hashes='...')

# and so on
```

However, a more robust interface to the endpoints is available via each namespace. This is intended to provide a more seamless and intuitive interface to the Web API.

```
import qbittorrentapi
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
    ↪ 'adminadmin')
# changing a preference
is_dht_enabled = qbt_client.app.preferences.dht
qbt_client.app.preferences = dict(dht=not is_dht_enabled)
# stopping all torrents
qbt_client.torrents.stop.all()
# retrieve different views of the log
qbt_client.log.main.warning()
qbt_client.log.main.normal()
```

Finally, some of the objects returned by the client support methods of their own. This is most pronounced for torrents themselves.

```
import qbittorrentapi
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
    ↪ 'adminadmin')

for torrent in qbt_client.torrents.info.active():
    torrent.set_location(location='/home/user/torrents/')
    torrent.reannounce()
    torrent.upload_limit = -1
```

1.4.1 Introduction

Python client implementation for qBittorrent Web API.

Currently supports qBittorrent v5.0.3 (Web API v2.11.2) released on Dec 15, 2024.

Features

- The entire qBittorrent Web API is implemented.
- qBittorrent version checking for an endpoint's existence/features is automatically handled.
- If the authentication cookie expires, a new one is automatically requested in line with any API call.

Installation

- Install via pip from PyPI:

```
python -m pip install qbittorrent-api
```

- Install a specific release (e.g. v2024.3.60):

```
python -m pip install qbittorrent-api==2024.3.60
```

- Install direct from main:

```
pip install git+https://github.com/rmartin16/qbittorrent-api.git@main#egg=qbittorrent-api
```

- Enable WebUI in qBittorrent: Tools -> Preferences -> Web UI
- If the Web API will be exposed to the Internet, follow the [recommendations](#).

Getting Started

```
import qbittorrentapi

# instantiate a Client using the appropriate WebUI configuration
conn_info = dict(
    host="localhost",
    port=8080,
    username="admin",
    password="adminadmin",
)
qbt_client = qbittorrentapi.Client(**conn_info)

# the Client will automatically acquire/maintain a logged-in state
# in line with any request. therefore, this is not strictly necessary;
# however, you may want to test the provided login credentials.
try:
    qbt_client.auth_log_in()
except qbittorrentapi.LoginFailed as e:
    print(e)

# if the Client will not be long-lived or many Clients may be created
# in a relatively short amount of time, be sure to log out:
qbt_client.auth_log_out()

# or use a context manager:
with qbittorrentapi.Client(**conn_info) as qbt_client:
    if qbt_client.torrents_add(urls="...") != "Ok.":
        raise Exception("Failed to add torrent.")

# display qBittorrent info
print(f"qBittorrent: {qbt_client.app.version}")
print(f"qBittorrent Web API: {qbt_client.app.web_api_version}")
for k, v in qbt_client.app.build_info.items():
    print(f"{k}: {v}")

# retrieve and show all torrents
```

(continues on next page)

(continued from previous page)

```
for torrent in qbt_client.torrents_info():
    print(f'{torrent.hash[-6:]}: {torrent.name} ({torrent.state})')

# stop all torrents
qbt_client.torrents.stop.all()
```

Usage

First, the Web API endpoints are organized in to eight namespaces.

- Authentication (auth)
- Application (app)
- Log (log)
- Sync (sync)
- Transfer (transfer)
- Torrent Management (torrents)
- RSS (rss)
- Search (search)

Second, this client has two modes of interaction with the qBittorrent Web API.

Each Web API endpoint is implemented one-to-one as a method of the instantiated client.

```
import qbittorrentapi
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
    ↪'adminadmin')
qbt_client.app_version()
qbt_client.rss_rules()
qbt_client.torrents_info()
qbt_client.torrents_resume(torrent_hashes='... ')
# and so on
```

However, a more robust interface to the endpoints is available via each namespace. This is intended to provide a more seamless and intuitive interface to the Web API.

```
import qbittorrentapi
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
    ↪'adminadmin')
# changing a preference
is_dht_enabled = qbt_client.app.preferences.dht
qbt_client.app.preferences = dict(dht=not is_dht_enabled)
# stopping all torrents
qbt_client.torrents.stop.all()
# retrieve different views of the log
qbt_client.log.main.warning()
qbt_client.log.main.normal()
```

Finally, some of the objects returned by the client support methods of their own. This is most pronounced for torrents themselves.

```
import qbittorrentapi
qbt_client = qbittorrentapi.Client(host='localhost:8080', username='admin', password=
    'adminadmin')

for torrent in qbt_client.torrents.info.active():
    torrent.set_location(location='/home/user/torrents/')
    torrent.reannounce()
    torrent.upload_limit = -1
```

1.4.2 Behavior & Configuration

Host, Username and Password

- The authentication credentials can be provided when instantiating `Client`:

```
qbt_client = Client(host="localhost:8080", username='...', password='...')
```

- The credentials can also be specified after `Client` is created but calling `auth_log_in()` is not strictly necessary to authenticate the client; this will happen automatically for any API request.

```
qbt_client.auth_log_in(username='...', password='...')
```

- Alternatively, the credentials can be specified in environment variables:
 - QBITTORRENTAPI_HOST
 - QBITTORRENTAPI_USERNAME
 - QBITTORRENTAPI_PASSWORD

qBittorrent Session Management

- Any time a connection is established with qBittorrent, it instantiates a session to manage authentication for all subsequent API requests.
- This client will transparently manage sessions by ensuring the client is always logged in in-line with any API request including requesting a new session upon expiration of an existing session.
- However, each new `Client` instantiation will create a new session in qBittorrent.
- Therefore, if many `Client` instances will be created be sure to call `auth_log_out` for each instance or use a context manager.
- Otherwise, qBittorrent may experience abnormally high memory usage.

```
with qbittorrentapi.Client(**conn_info) as qbt_client:
    if qbt_client.torrents_add(urls="...") != "Ok.":
        raise Exception("Failed to add torrent.")
```

Untrusted Web API Certificate

- qBittorrent allows you to configure HTTPS with an untrusted certificate; this commonly includes self-signed certificates.
- When using such a certificate, instantiate Client with `VERIFY_WEBUI_CERTIFICATE=False` or set environment variable `QBITTORRENTAPI_DO_NOT_VERIFY_WEBUI_CERTIFICATE` to a non-null value.
- Failure to do this for will cause connections to qBittorrent to fail.

- As a word of caution, doing this actually does turn off certificate verification. Therefore, for instance, potential man-in-the-middle attacks will not be detected and reported (since the error is suppressed). However, the connection will remain encrypted.

```
qbt_client = Client(..., VERIFY_WEBUI_CERTIFICATE=False}
```

Requests Configuration

- The `Requests` package is used to issue HTTP requests to qBittorrent to facilitate this API.
- Much of `Requests` configuration for making HTTP requests can be controlled with parameters passed along with the request payload.
- For instance, HTTP Basic Authorization credentials can be provided via `auth`, timeouts via `timeout`, or Cookies via `cookies`. See `Requests` documentation for full details.
- These parameters are exposed here in two ways; the examples below tell `Requests` to use a connect timeout of 3.1 seconds and a read timeout of 30 seconds.
- When you instantiate `Client`, you can specify the parameters to use in all HTTP requests to qBittorrent:

```
qbt_client = Client(..., REQUESTS_ARGS={'timeout': (3.1, 30)}
```

- Alternatively, parameters can be specified for individual requests:

```
qbt_client.torrents_info(..., requests_args={'timeout': (3.1, 30)})
```

- Additionally, configuration for the `HTTPAdapter` for the `Session` can be specified via the `HTTPADAPTER_ARGS` parameter for `Client`:

```
qbt_client = Client(..., HTTPADAPTER_ARGS={"pool_connections": 100, "pool_maxsize": 100})
```

Additional HTTP Headers

- For consistency, HTTP Headers can be specified using the method above; for backwards compatibility, the methods below are supported as well.
- Either way, these additional headers will be incorporated (using clobbering) into the rest of the headers to be sent.
- To send a custom HTTP header in all requests made from an instantiated client, declare them during instantiation:

```
qbt_client = Client(..., EXTRA_HEADERS={'X-My-Fav-Header': 'header value'})
```

- Alternatively, you can send custom headers in individual requests:

```
qbt_client.torrents.add(..., headers={'X-My-Fav-Header': 'header value'})
```

Unimplemented API Endpoints

- Since the qBittorrent Web API has evolved over time, some endpoints may not be available from the qBittorrent host.
- By default, if a request is made to endpoint that doesn't exist for the version of the qBittorrent host (e.g., the Search endpoints were introduced in Web API v2.1.1), there's a debug logger output and `None` is returned.
- To raise `NotImplementedError` instead, instantiate Client with:

```
qbt_client = Client(..., RAISE_NOTIMPLEMENTEDERROR_FOR_UNIMPLEMENTED_API_ENDPOINTS=True)
```

qBittorrent Version Checking

- It is also possible to either raise an Exception for qBittorrent hosts that are not “fully” supported or manually check for support.
- The most likely situation for this to occur is if the qBittorrent team publishes a new release but its changes have not been incorporated in to this client yet.
- Instantiate Client like below to raise *UnsupportedQbittorrentVersion* exception for versions not fully supported:

```
qbt_client = Client(..., RAISE_ERROR_FOR_UNSUPPORTED_QBITTORRENT_VERSIONS=True)
```

- Additionally, *Version* can be used for manual introspection of the versions.

```
Version.is_app_version_supported(qbt_client.app.version)
```

Disable Logging Debug Output

- Instantiate Client with DISABLE_LOGGING_DEBUG_OUTPUT=True or manually disable logging for the relevant packages:

```
logging.getLogger('qbittorrentapi').setLevel(logging.INFO)
logging.getLogger('requests').setLevel(logging.INFO)
logging.getLogger('urllib3').setLevel(logging.INFO)
```

1.4.3 Async Support

qbittorrent-api does not support Python’s `async/await` functionality for asynchronous programming. However, many use-cases for this client operate within an existing asynchronous application. Therefore, in lieu of being able to await this client’s API calls to qBittorrent, it is still possible to call them without blocking.

Each `asyncio` Event Loop provides a `ThreadPoolExecutor` that can run blocking code that could interfere with async applications. In Python 3.9, a simple interface was introduced in `asyncio` to run synchronous code in this thread pool.

```
async def fetch_torrents() -> TorrentInfoList:
    return await asyncio.to_thread(qbt_client.torrents_info, category="uploaded")
```

In this example, you simply specify the method to call, `torrents_info`, as the first argument and follow it with the arguments for the method to run in the thread.

Below is a full example demonstrating this that can be run in the Python REPL:

```
import asyncio
import qbittorrentapi

qbt_client = qbittorrentapi.Client()

async def fetch_qbt_info():
    return await asyncio.to_thread(qbt_client.app_build_info)

print(asyncio.run(fetch_qbt_info()))
```

1.4.4 Performance

By default, complex objects are returned from some endpoints. These objects allow for accessing the response's items as attributes and include methods for contextually relevant actions (such as `start()` and `stop()` for a torrent, for example).

This comes at the cost of performance, though. Generally, this cost isn't large; however, some endpoints, such as `torrents_files()`, may need to convert a large payload and the cost can be significant.

This client can be configured to always return only the simple JSON if desired. Simply set `SIMPLE_RESPONSES=True` when instantiating the client.

```
qbt_client = qbittorrentapi.Client(
    host='localhost:8080',
    username='admin',
    password='adminadmin',
    SIMPLE_RESPONSES=True,
)
```

Alternatively, `SIMPLE_RESPONSES` can be set to `True` to return the simple JSON only for an individual method call.

```
qbt_client.torrents.files(torrent_hash='...', SIMPLE_RESPONSES=True)
```

1.4.5 Exceptions

`exception APIError`

Bases: `Exception`

Base error for all exceptions from this Client.

`exception UnsupportedQbittorrentVersion`

Bases: `APIError`

Connected qBittorrent is not fully supported by this Client.

`exception FileNotFoundError`

Bases: `OSError, APIError`

Base class for all exceptions for file handling.

`exception TorrentFileError`

Bases: `FileError`

Base class for all exceptions for torrent files.

`exception TorrentFileNotFoundException`

Bases: `TorrentFileError`

Specified torrent file does not appear to exist.

`exception TorrentFilePermissionError`

Bases: `TorrentFileError`

Permission was denied to read the specified torrent file.

`exception APIConnectionError(*args, **kwargs)`

Bases: `RequestException, APIError`

Base class for all communications errors including HTTP errors.

exception LoginFailed(*args, **kwargs)

Bases: *APIConnectionError*

This can technically be raised with any request since log in may be attempted for any request and could fail.

exception HTTPError(*args, **kwargs)

Bases: *HTTPError*, *APIConnectionError*

Base error for all HTTP errors.

All errors following a successful connection to qBittorrent are returned as HTTP statuses.

http_status_code: int

exception HTTP4XXError(*args, **kwargs)

Bases: *HTTPError*

Base error for all HTTP 4XX statuses.

exception HTTP5XXError(*args, **kwargs)

Bases: *HTTPError*

Base error for all HTTP 5XX statuses.

exception HTTP400Error(*args, **kwargs)

Bases: *HTTP4XXError*

HTTP 400 Status.

http_status_code: int = 400

exception HTTP401Error(*args, **kwargs)

Bases: *HTTP4XXError*

HTTP 401 Status.

http_status_code: int = 401

exception HTTP403Error(*args, **kwargs)

Bases: *HTTP4XXError*

HTTP 403 Status.

http_status_code: int = 403

exception HTTP404Error(*args, **kwargs)

Bases: *HTTP4XXError*

HTTP 404 Status.

http_status_code: int = 404

exception HTTP405Error(*args, **kwargs)

Bases: *HTTP4XXError*

HTTP 405 Status.

http_status_code: int = 405

exception HTTP409Error(*args, **kwargs)

Bases: *HTTP4XXError*

HTTP 409 Status.

```
http_status_code: int = 409
exception HTTP415Error(*args, **kwargs)
    Bases: HTTP4XXError
    HTTP 415 Status.

http_status_code: int = 415
exception HTTP500Error(*args, **kwargs)
    Bases: HTTP5XXError
    HTTP 500 Status.

http_status_code: int = 500
exception MissingRequiredParameters400Error(*args, **kwargs)
    Bases: HTTP400Error
    Endpoint call is missing one or more required parameters.

exception InvalidRequest400Error(*args, **kwargs)
    Bases: HTTP400Error
    One or more endpoint arguments are malformed.

exception Unauthorized401Error(*args, **kwargs)
    Bases: HTTP401Error
    Primarily reserved for XSS and host header issues.

exception Forbidden403Error(*args, **kwargs)
    Bases: HTTP403Error
    Not logged in, IP has been banned, or calling an API method that isn't public.

exception NotFound404Error(*args, **kwargs)
    Bases: HTTP404Error
    This should mean qBittorrent couldn't find a torrent for the torrent hash.

exception MethodNotAllowed405Error(*args, **kwargs)
    Bases: HTTP405Error
    HTTP method is not supported for the API endpoint.

exception Conflict409Error(*args, **kwargs)
    Bases: HTTP409Error
    Returned if arguments don't make sense specific to the endpoint.

exception UnsupportedMediaType415Error(*args, **kwargs)
    Bases: HTTP415Error
    torrents/add endpoint will return this for invalid URL(s) or files.

exception InternalServerError500Error(*args, **kwargs)
    Bases: HTTP500Error
    Returned if qBittorrent errors internally while processing the request.
```

1.4.6 API Reference

Application

```
class AppAPIMixIn(host=None, port=None, username=None, password=None, EXTRA_HEADERS=None,
    REQUESTS_ARGS=None, HTTPADAPTER_ARGS=None,
    VERIFY_WEBUI_CERTIFICATE=True, FORCE_SCHEME_FROM_HOST=False,
    RAISE_NOTIMPLEMENTEDERROR_FOR_UNIMPLEMENTED_API_ENDPOINTS=False,
    RAISE_ERROR_FOR_UNSUPPORTED_QBITTORRENT VERSIONS=False,
    VERBOSE_RESPONSE_LOGGING=False, SIMPLE_RESPONSES=False,
    DISABLE_LOGGING_DEBUG_OUTPUT=False) → None
```

Bases: *AuthAPIMixIn*

Implementation of all Application API methods.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host="localhost:8080", username="admin", password=
    ↪"adminadmin")
>>> client.app_version()
>>> client.app_preferences()
```

app_build_info(kwargs)** → *BuildInfoDictionary*

qBittorrent build info.

This method was introduced with qBittorrent v4.2.0 (Web API v2.3).

Return type

BuildInfoDictionary

app_cookies(kwargs)** → *CookieList*

Retrieve current cookies.

Return type

CookieList

app_default_save_path(kwargs)** → *str*

The default path where torrents are saved.

Return type

str

app_get_directory_content(directory_path=None) → *DirectoryContentList*

The contents of a directory file path.

Raises

NotFound404Error – file path not found or not a directory

Parameters

directory_path (*str* | *PathLike[AnyStr]* | *None*) – file system path to directory

Return type

DirectoryContentList

app_network_interface_address_list(interface_name='', **kwargs) → *NetworkInterfaceAddressList*

The addresses for a network interface; omit name for all addresses.

This method was introduced with qBittorrent v4.2.0 (Web API v2.3).

Parameters

interface_name (`str`) – Name of interface to retrieve addresses for

Return type

`NetworkInterfaceAddressList`

app_network_interface_list(`**kwargs`) → `NetworkInterfaceList`

The list of network interfaces on the host.

This method was introduced with qBittorrent v4.2.0 (Web API v2.3).

Return type

`NetworkInterfaceList`

app_preferences(`**kwargs`) → `ApplicationPreferencesDictionary`

Retrieve qBittorrent application preferences.

Return type

`ApplicationPreferencesDictionary`

app_send_test_email() → `None`

Sends a test email using the configured email address.

Return type

`None`

app_set_cookies(`cookies=None, **kwargs`) → `None`

Set cookies.

```
cookies = [
    {
        'domain': 'example.com',
        'path': '/example/path',
        'name': 'cookie name',
        'value': 'cookie value',
        'expirationDate': 1729366667,
    },
]
```

Parameters

cookies (`CookieList` | `Sequence[Mapping[str, str | int]]` | `None`) – list of cookies to set

Return type

`None`

app_set_preferences(`prefs=None, **kwargs`) → `None`

Set one or more preferences in qBittorrent application.

Parameters

prefs (`ApplicationPreferencesDictionary` | `Mapping[str, Any]` | `None`) – dictionary of preferences to set

Return type

`None`

app_shutdown(`**kwargs`) → `None`

Shutdown qBittorrent.

Return type

None

app_version(**kwargs) → str

qBittorrent application version.

Return type

str

app_web_api_version(**kwargs) → str

qBittorrent Web API version.

Return type

str

class Application(*args, client, **kwargs)

Allows interaction with Application API endpoints.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host="localhost:8080", username="admin", password=
    ↳ "adminadmin")
>>> # these are all the same attributes that are available as named in
    ↳ the
>>> # endpoints or the more pythonic names in Client (with or without
    ↳ 'app_' prepended)
>>> webapiVersion = client.application.webapiVersion
>>> web_api_version = client.application.web_api_version
>>> app_web_api_version = client.application.web_api_version
>>> # access and set preferences as attributes
>>> is_dht_enabled = client.application.preferences.dht
>>> # supports sending a just subset of preferences to update
>>> client.application.preferences = dict(dht=(not is_dht_enabled))
>>> prefs = client.application.preferences
>>> prefs["web_ui_clickjacking_protection_enabled"] = True
>>> client.app.preferences = prefs
>>>
>>> client.application.shutdown()
```

property build_info: BuildInfoDictionary

Implements `app_build_info()`.

property cookies: CookieList

Implements `app_cookies()`.

property default_save_path: str

Implements `app_default_save_path()`.

get_directory_content(directory_path=None) → DirectoryContentList

Implements `app_get_directory_content()`.

Return type

`DirectoryContentList`

network_interface_address_list(interface_name='', **kwargs) → NetworkInterfaceAddressList

Implements `app_network_interface_address_list()`.

Return type
NetworkInterfaceAddressList

property network_interface_list: NetworkInterfaceList
Implements *app_network_interface_list()*.

property preferences: ApplicationPreferencesDictionary
Implements *app_preferences()*.

send_test_email() → None
Implements *app_send_test_email()*.

Return type
None

set_cookies(cookies=None, **kwargs) → None
Implements *app_set_cookies()*.

Return type
None

set_preferences(prefs=None, **kwargs) → None
Implements *app_set_preferences()*.

Return type
None

shutdown(kwargs) → None**
Implements *app_shutdown()*.

Return type
None

property version: str
Implements *app_version()*.

property web_api_version: str
Implements *app_web_api_version()*.

class ApplicationPreferencesDictionary(data=None, **kwargs)
Bases: *Dictionary[None | int | str | bool | Sequence[JsonValueT] | Mapping[str, JsonValueT]]*
Response for *app_preferences()*
Definition: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1))
#user-content-get-application-preferences

class BuildInfoDictionary(data=None, **kwargs)
Bases: *Dictionary[str | int]*
Response for *app_build_info()*
Definition: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1))
#user-content-get-build-info

class DirectoryContentList(list_entries, client=None)
Bases: *List[str]*
Response for *app_get_directory_content()*

```
class Cookie(data=None, **kwargs)
    Bases: ListEntry
        Item in CookieList

class CookieList(list_entries, client=None)
    Bases: List[Cookie]
        Response for app_cookies()

class NetworkInterfaceList(list_entries, client=None)
    Bases: List[NetworkInterface]
        Response for app_network_interface_list()

class NetworkInterface(data=None, **kwargs)
    Bases: ListEntry
        Item in NetworkInterfaceList

class NetworkInterfaceAddressList(list_entries, client=None)
    Bases: List[str]
        Response for app_network_interface_address_list()
```

AttrDict (internal)

Copyright (c) 2013 Brendan Curran-Johnson

```
class AttrDict(*args, **kwargs) → None
    Bases: dict[str, V], MutableAttr[V]
        A dict that implements MutableAttr.

class MutableAttr
    Bases: Attr[str, V], MutableMapping[str, V], ABC
        A mixin mapping class that allows for attribute-style access of values.

class Attr
    Bases: Mapping[K, V], ABC
        A mixin class for a mapping that allows for attribute-style access of values.
```

A key may be used as an attribute if:

- It is a string
- It matches ^[A-Za-z] [A-Za-z0-9_]*\$ (i.e., a public attribute)
- The key doesn't overlap with any class attributes (for Attr, those would be get, items, keys, values, mro, and register).

If a value which is accessed as an attribute is a Sequence-type (and is not a string/bytes), it will be converted to a _sequence_type with any mappings within it converted to Attrs.

NOTE:

This means that if _sequence_type is not None, then a sequence accessed as an attribute will be a different object than if accessed as an attribute than if it is accessed as an item.

Authentication

```
class AuthAPIMixIn(host=None, port=None, username=None, password=None, EXTRA_HEADERS=None,
    REQUESTS_ARGS=None, HTTPADAPTER_ARGS=None,
    VERIFY_WEBUI_CERTIFICATE=True, FORCE_SCHEME_FROM_HOST=False,
    RAISE_NOTIMPLEMENTEDERROR_FOR_UNIMPLEMENTED_API_ENDPOINTS=False,
    RAISE_ERROR_FOR_UNSUPPORTED_QBITTORRENT_VERSIONS=False,
    VERBOSE_RESPONSE_LOGGING=False, SIMPLE_RESPONSES=False,
    DISABLE_LOGGING_DEBUG_OUTPUT=False) → None
```

Bases: *Request*

Implementation of all Authorization API methods.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host="localhost:8080", username="admin", password=
    ↪"adminadmin")
>>> _ = client.is_logged_in
>>> client.auth_log_in(username="admin", password="adminadmin")
>>> client.auth_log_out()
```

auth_log_in(username=None, password=None, **kwargs) → None

Log in to qBittorrent host.

Raises

- **LoginFailed** – if credentials failed to log in
- **Forbidden403Error** – if user is banned... or not logged in

Parameters

- **username** (str | None) – username for qBittorrent client
- **password** (str | None) – password for qBittorrent client

Return type

None

auth_log_out(**kwargs) → None

End session with qBittorrent.

Return type

None

property is_logged_in: bool

Returns True if low-overhead API call succeeds; False otherwise.

There isn't a reliable way to know if an existing session is still valid without attempting to use it. qBittorrent invalidates cookies when they expire.

Returns

True/False if current authorization cookie is accepted by qBittorrent

class Authorization(*args, client, **kwargs)

Allows interaction with the Authorization API endpoints.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host="localhost:8080", username="admin", password=
    >>>     "adminadmin")
>>> is_logged_in = client.auth.is_logged_in
>>> client.auth.log_in(username="admin", password="adminadmin")
>>> client.auth.log_out()
```

property is_logged_in: bool

Implements `is_logged_in()`.

log_in(username=None, password=None, **kwargs) → None

Implements `auth_log_in()`.

Return type

`None`

log_out(kwargs) → None**

Implements `auth_log_out()`.

Return type

`None`

Client

```
class Client(host='', port=None, username=None, password=None, *, EXTRA_HEADERS=None,
    REQUESTS_ARGS=None, HTTPADAPTER_ARGS=None,
    VERIFY_WEBUI_CERTIFICATE=True, FORCE_SCHEME_FROM_HOST=False,
    RAISE_NOTIMPLEMENTEDERROR_FOR_UNIMPLEMENTED_API_ENDPOINTS=False,
    RAISE_ERROR_FOR_UNSUPPORTED_QBITTORRENT VERSIONS=False,
    VERBOSE_RESPONSE_LOGGING=False, SIMPLE_RESPONSES=False,
    DISABLE_LOGGING_DEBUG_OUTPUT=False)

Bases:      LogAPIMixIn,      SyncAPIMixIn,      TransferAPIMixIn,      TorrentsAPIMixIn,
TorrentCreatorAPIMixIn, RSSAPIMixIn, SearchAPIMixIn
```

Initialize API for qBittorrent client.

Host must be specified. Username and password can be specified at login. A call to `auth_log_in()` is not explicitly required if username and password are provided during Client construction.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host='localhost:8080', username='admin', password=
    >>>     'adminadmin')
>>> torrents = client.torrents_info()
```

Parameters

- **host** (`str`) – hostname for qBittorrent Web API, `[http[s]://]hostname[:port][/path]`
- **port** (`str | int | None`) – port number for qBittorrent Web API (ignored if host contains a port)
- **username** (`str | None`) – username for qBittorrent Web API
- **password** (`str | None`) – password for qBittorrent Web API

- **SIMPLE_RESPONSES** (`bool`) – By default, complex objects are returned from some endpoints. These objects will allow for accessing responses' items as attributes and include methods for contextually relevant actions. This comes at the cost of performance. Generally, this cost isn't large; however, some endpoints, such as `torrents_files()` method, may need to convert a large payload. Set this to True to return the simple JSON back. Alternatively, set this to True only for an individual method call. For instance, when requesting the files for a torrent: `client.torrents_files(torrent_hash='...', SIMPLE_RESPONSES=True)`
- **VERIFY_WEBUI_CERTIFICATE** (`bool`) – Set to False to skip verify certificate for HTTPS connections; for instance, if the connection is using a self-signed certificate. Not setting this to False for self-signed certs will cause a `APIConnectionError` exception to be raised.
- **EXTRA_HEADERS** (`Mapping[str, str] | None`) – Dictionary of HTTP Headers to include in all requests made to qBittorrent.
- **REQUESTS_ARGS** (`Mapping[str, Any] | None`) – Dictionary of configuration for each HTTP request made by `requests.request`.
- **HTTPADAPTER_ARGS** (`Mapping[str, Any] | None`) – Dictionary of configuration for `HTTPAdapter`.
- **FORCE_SCHEME_FROM_HOST** (`bool`) – If a scheme (i.e. `http` or `https`) is specified in host, it will be used regardless of whether qBittorrent is configured for HTTP or HTTPS communication. Normally, this client will attempt to determine which scheme qBittorrent is actually listening on... but this can cause problems in rare cases. Defaults False.
- **RAISE_NOTIMPLEMENTEDERROR_FOR_UNIMPLEMENTED_API_ENDPOINTS** (`bool`) – Some endpoints may not be implemented in older versions of qBittorrent. Setting this to True will raise a `NotImplementedError` instead of just returning None.
- **RAISE_ERROR_FOR_UNSUPPORTED_QBITTORRENT_VERSIONS** (`bool`) – Raise `UnsupportedQbittorrentVersion` if the connected version of qBittorrent is not fully supported by this client. Defaults False.
- **DISABLE_LOGGING_DEBUG_OUTPUT** (`bool`) – Turn off debug output from logging for this package as well as `requests` & `urllib3`.

Definitions

APIKwargs

Type Any for `kwargs` parameters for API methods.

```
class APINames(value, names=<not given>, *values, module=None, qualname=None, type=None, start=1, boundary=None)
```

Bases: `str, Enum`

API namespaces for API endpoints.

e.g torrents in `http://localhost:8080/api/v2/torrents/addTrackers`

```
Application = 'app'
```

```
Authorization = 'auth'
```

```
EMPTY = ''
```

```
Log = 'log'
```

```
RSS = 'rss'
```

```
Search = 'search'
Sync = 'sync'
TorrentCreator = 'torrentcreator'
Torrents = 'torrents'
Transfer = 'transfer'

class ClientCache(*args, client, **kwargs)
    Bases: Generic[ClientT]
    Caches the client.

    Subclass this for any object that needs access to the Client.

class ClientT
    Type for this API Client.

    alias of TypeVar('ClientT', bound=Request)

class Dictionary(data=None, **kwargs)
    Bases: AttrDict[V]
    Base definition of dictionary-like objects returned from qBittorrent.

FilesToSendT
    Type for Files input to API method.

    alias of Mapping[str, bytes | tuple[str, bytes]]

JsonValueT
    Type to define JSON.

    alias of None | int | str | bool | Sequence[JsonValueT] | Mapping[str, JsonValueT]

class List(list_entries=None, entry_class=None, **kwargs)
    Bases: UserList[ListEntryT]
    Base definition for list-like objects returned from qBittorrent.

class ListEntry(data=None, **kwargs)
    Bases: Dictionary[None | int | str | bool | Sequence[JsonValueT] | Mapping[str, JsonValueT]]
    Base definition for objects within a list returned from qBittorrent.

class ListEntryT
    Type for entry in List from API.

    alias of TypeVar('ListEntryT', bound=ListEntry)

ListInputT
    Type for List input to API method.

    alias of Iterable[Mapping[str, None | int | str | bool | Sequence[JsonValueT] | Mapping[str, JsonValueT]]]

class TorrentState(value, names=<not given>, *values, module=None, qualname=None, type=None, start=1,
                  boundary=None)
    Bases: str, Enum
    Torrent States as defined by qBittorrent.
```

Note: In qBittorrent v5.0.0:

- PAUSED_UPLOAD was renamed to STOPPED_UPLOAD
- PAUSED_DOWNLOAD was renamed to STOPPED_DOWNLOAD

Definitions:

- wiki: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)
#user-content-get-torrent-list](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#user-content-get-torrent-list)
- code: [https://github.com/qbittorrent/qBittorrent/blob/8e6515be2c8cc2b335002ab8913e9dcdd7873204/
src/base/bittorrent/torrent.h#L79](https://github.com/qbittorrent/qBittorrent/blob/8e6515be2c8cc2b335002ab8913e9dcdd7873204/src/base/bittorrent/torrent.h#L79)

Usage

```
>>> from qbittorrentapi import Client, TorrentState
>>> client = Client()
>>> # print torrent hashes for torrents that are downloading
>>> for torrent in client.torrents_info():
>>>     # check if torrent is downloading
>>>     if torrent.state_enum.is_downloading:
>>>         print(f'{torrent.hash} is downloading...')
>>>     # the appropriate enum member can be directly derived
>>>     state_enum = TorrentState(torrent.state)
>>>     print(f'{torrent.hash}: {state_enum.value}')
```

```
ALLOCATING = 'allocating'
CHECKING_DOWNLOAD = 'checkingDL'
CHECKING_RESUME_DATA = 'checkingResumeData'
CHECKING_UPLOAD = 'checkingUP'
DOWNLOADING = 'downloading'
ERROR = 'error'
FORCED_DOWNLOAD = 'forcedDL'
FORCED_METADATA_DOWNLOAD = 'forcedMetaDL'
FORCED_UPLOAD = 'forcedUP'
METADATA_DOWNLOAD = 'metaDL'
MISSING_FILES = 'missingFiles'
MOVING = 'moving'
PAUSED_DOWNLOAD = 'pausedDL'
    pausedDL was renamed to stoppedDL in Web API v2.11.0
PAUSED_UPLOAD = 'pausedUP'
    pausedUP was renamed to stoppedUP in Web API v2.11.0
QUEUED_DOWNLOAD = 'queuedDL'
```

```
QUEUED_UPLOAD = 'queuedUP'
STALLED_DOWNLOAD = 'stalledDL'
STALLED_UPLOAD = 'stalledUP'
STOPPED_DOWNLOAD = 'stoppedDL'
STOPPED_UPLOAD = 'stoppedUP'
UNKNOWN = 'unknown'
UPLOADING = 'uploading'

property is_checking: bool
    Returns True if the State is categorized as Checking.

property is_complete: bool
    Returns True if the State is categorized as Complete.

property is_downloading: bool
    Returns True if the State is categorized as Downloading.

property is_errorred: bool
    Returns True if the State is categorized as Errorred.

property is_paused: bool
    Alias of TorrentState.is_stopped

property is_stopped: bool
    Returns True if the State is categorized as Stopped.

property is_uploading: bool
    Returns True if the State is categorized as Uploading.

class TrackerStatus(value, names=<not given>, *values, module=None, qualname=None, type=None, start=1,
                     boundary=None)
```

Bases: `int, Enum`

Tracker Statuses as defined by qBittorrent.

Definitions:

- wiki: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1))
`#user-content-get-torrent-trackers`
- code: <https://github.com/qbittorrent/qBittorrent/blob/5dcc14153f046209f1067299494a82e5294d883a/src/base/bittorrent/trackerentry.h#L42>

Usage

```
>>> from qbittorrentapi import Client, TrackerStatus
>>> client = Client()
>>> # print torrent hashes for torrents that are downloading
>>> for torrent in client.torrents_info():
>>>     for tracker in torrent.trackers:
>>>         # display status for each tracker
>>>         print(f'{torrent.hash[-6:]}: {TrackerStatus(tracker.status)}')
→display:>13 :{tracker.url}")
```

DISABLED = 0

NOT_CONTACTED = 1

NOT_WORKING = 4

UPDATING = 3

WORKING = 2

property display: str

Returns a descriptive display value for status.

Log

```
class LogAPIMixIn(host=None, port=None, username=None, password=None, EXTRA_HEADERS=None,
                   REQUESTS_ARGS=None, HTTPADAPTER_ARGS=None,
                   VERIFY_WEBUI_CERTIFICATE=True, FORCE_SCHEME_FROM_HOST=False,
                   RAISE_NOTIMPLEMENTEDERROR_FOR_UNIMPLEMENTED_API_ENDPOINTS=False,
                   RAISE_ERROR_FOR_UNSUPPORTED_QBITTORRENT VERSIONS=False,
                   VERBOSE_RESPONSE_LOGGING=False, SIMPLE_RESPONSES=False,
                   DISABLE_LOGGING_DEBUG_OUTPUT=False) → None
```

Bases: *AppAPIMixIn*

Implementation of all Log API methods.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host="localhost:8080", username="admin", password=
   ↴"adminadmin")
>>> client.log_main(info=False)
>>> client.log_peers()
```

log_main(normal=None, info=None, warning=None, critical=None, last_known_id=None, **kwargs) → *LogMainList*

Retrieve the qBittorrent log entries. Iterate over returned object.

Parameters

- **normal** (bool | None) – False to exclude normal entries
- **info** (bool | None) – False to exclude info entries
- **warning** (bool | None) – False to exclude warning entries
- **critical** (bool | None) – False to exclude critical entries
- **last_known_id** (str | int | None) – only entries with an ID greater than this value will be returned

Return type

LogMainList

log_peers(last_known_id=None, **kwargs) → *LogPeersList*

Retrieve qBittorrent peer log.

Parameters

- **last_known_id** (str | int | None) – only entries with an ID greater than this value will be returned

Return type*LogPeersList***class Log(client)**

Allows interaction with Log API endpoints.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host="localhost:8080", username="admin", password=
    ↳"adminadmin")
>>> # this is all the same attributes that are available as named in the
>>> # endpoints or the more pythonic names in Client (with or without
    ↳'log_' prepended)
>>> log_list = client.log.main()
>>> peers_list = client.log.peers(last_known_id="...")
>>> # can also filter log down with additional attributes
>>> log_info = client.log.main.info(last_known_id=1)
>>> log_warning = client.log.main.warning(last_known_id=1)
```

class Main(*args, client, **kwargs)

__call__(normal=True, info=True, warning=True, critical=True, last_known_id=None, **kwargs) → LogMainList

Implements *log_main()*.

Return type*LogMainList*

critical(last_known_id=None, **kwargs) → LogMainList

Implements *log_main()* with info=False, normal=False, and warning=False.

Return type*LogMainList*

info(last_known_id=None, **kwargs) → LogMainList

Implements *log_main()*.

Return type*LogMainList*

normal(last_known_id=None, **kwargs) → LogMainList

Implements *log_main()* with info=False.

Return type*LogMainList*

warning(last_known_id=None, **kwargs) → LogMainList

Implements *log_main()* with info=False and normal=False.

Return type*LogMainList***property main: Main**

Implements *log_main()*.

peers(last_known_id=None, **kwargs) → LogPeersList

Implements *log_peers()*.

Return type*LogPeersList*

```
class LogPeersList(list_entries, client=None)
```

Bases: `List[LogPeer]`

Response for `log_peers()`

```
class LogPeer(data=None, **kwargs)
```

Bases: `ListEntry`

Item in `LogPeersList`

```
class LogMainList(list_entries, client=None)
```

Bases: `List[LogEntry]`

Response to `log_main()`

```
class LogEntry(data=None, **kwargs)
```

Bases: `ListEntry`

Item in `LogMainList`

Request (internal)

```
class QbittorrentSession
```

Bases: `Session`

Wrapper to augment Requests Session.

Requests doesn't allow Session to default certain configuration globally. This gets around that by setting defaults for each request.

```
request(method, url, **kwargs) → Response
```

Constructs a `Request`, prepares it and sends it. Returns Response object.

Parameters

- **method** (`str`) – method for the new `Request` object.
- **url** (`str`) – URL for the new `Request` object.
- **params** – (optional) Dictionary or bytes to be sent in the query string for the `Request`.
- **data** – (optional) Dictionary, list of tuples, bytes, or file-like object to send in the body of the `Request`.
- **json** – (optional) json to send in the body of the `Request`.
- **headers** – (optional) Dictionary of HTTP Headers to send with the `Request`.
- **cookies** – (optional) Dict or CookieJar object to send with the `Request`.
- **files** – (optional) Dictionary of 'filename': file-like-objects for multipart encoding upload.
- **auth** – (optional) Auth tuple or callable to enable Basic/Digest/Custom HTTP Auth.
- **timeout** (`float` or `tuple`) – (optional) How long to wait for the server to send data before giving up, as a float, or a (connect timeout, read timeout) tuple.
- **allow_redirects** (`bool`) – (optional) Set to True by default.
- **proxies** – (optional) Dictionary mapping protocol or protocol and hostname to the URL of the proxy.
- **hooks** – (optional) Dictionary mapping hook name to one event or list of events, event must be callable.

- **stream** – (optional) whether to immediately download the response content. Defaults to `False`.
- **verify** – (optional) Either a boolean, in which case it controls whether we verify the server's TLS certificate, or a string, in which case it must be a path to a CA bundle to use. Defaults to `True`. When set to `False`, requests will accept any TLS certificate presented by the server, and will ignore hostname mismatches and/or expired certificates, which will make your application vulnerable to man-in-the-middle (MitM) attacks. Setting `verify` to `False` may be useful during local development or testing.
- **cert** – (optional) if String, path to ssl client cert file (.pem). If Tuple, ('cert', 'key') pair.

Return type

`Response`

class `QbittorrentURL(client)`

Bases: `object`

Management for the qBittorrent Web API URL.

build(`api_namespace`, `api_method`, `headers=None`, `requests_kwargs=None`, `base_path='api/v2'`) → str

Create a fully qualified URL for the API endpoint.

Parameters

- **api_namespace** (`APINames` | `str`) – the namespace for the API endpoint (e.g. `torrents`)
- **api_method** (`str`) – the specific method for the API endpoint (e.g. `info`)
- **base_path** (`str`) – base path for URL (e.g. `api/v2`)
- **headers** (`Mapping[str, str]` | `None`) – HTTP headers for request
- **requests_kwargs** (`Mapping[str, Any]` | `None`) – kwargs for any calls to Requests

Return type

`str`

Returns

fully qualified URL string for endpoint

build_base_url(`headers`, `requests_kwargs`) → str

Determine the Base URL for the Web API endpoints.

A URL is only actually built here if it's the first time here or the context was re-initialized. Otherwise, the most recently built URL is used.

If the user doesn't provide a scheme for the URL, it will try HTTP first and fall back to HTTPS if that doesn't work. While this is probably backwards, qBittorrent or an intervening proxy can simply redirect to HTTPS and that'll be respected.

Additionally, if users want to augment the path to the API endpoints, any path provided here will be preserved in the returned Base URL and prefixed to all subsequent API calls.

Parameters

- **headers** (`Mapping[str, str]`) – HTTP headers for request
- **requests_kwargs** (`Mapping[str, Any]`) – arguments from user for HTTP HEAD request

Return type

`str`

Returns

base URL as a string for Web API endpoint

detect_scheme(*base_url*, *default_scheme*, *alt_scheme*, *headers*, *requests_kwargs*) → str

Determine if the URL endpoint is using HTTP or HTTPS.

Parameters

- **base_url** (`ParseResult`) – `urllib ParseResult` URL object
- **default_scheme** (str) – default scheme to use for URL
- **alt_scheme** (str) – alternative scheme to use for URL if default doesn't work
- **headers** (`Mapping[str, str]`) – HTTP headers for request
- **requests_kwargs** (`Mapping[str, Any]`) – kwargs for calls to Requests

Return type

str

Returns

scheme (i.e. HTTP or HTTPS)

```
class Request(host=None, port=None, username=None, password=None, EXTRA_HEADERS=None,
    REQUESTS_ARGS=None, HTTPADAPTER_ARGS=None,
    VERIFY_WEBUI_CERTIFICATE=True, FORCE_SCHEME_FROM_HOST=False,
    RAISE_NOTIMPLEMENTEDERROR_FOR_UNIMPLEMENTED_API_ENDPOINTS=False,
    RAISE_ERROR_FOR_UNSUPPORTED_QBITTORRENT VERSIONS=False,
    VERBOSE_RESPONSE_LOGGING=False, SIMPLE_RESPONSES=False,
    DISABLE_LOGGING_DEBUG_OUTPUT=False) → None
```

Bases: `object`

Facilitates HTTP requests to qBittorrent's Web API.

```
_auth_request(http_method, api_namespace, api_method, _retry_backoff_factor=0.3, requests_args=None,
    requests_params=None, headers=None, params=None, data=None, files=None,
    response_class=<class 'requests.models.Response'>, version_introduced="",
    version_removed="", **kwargs) → Any
```

Wraps API call with re-authorization if first attempt is not authorized.

Return type

Any

```
_cast(response, response_class, **response_kwargs) → Any
```

Returns the API response casted to the requested class.

Parameters

- **response** (`Response`) – requests Response from API
- **response_class** (`type`) – class to return response as; if none, response is returned
- **response_kwargs** (Any) – request-specific configuration for response

Return type

Any

```
static _format_payload(http_method, params=None, data=None, files=None, **kwargs) →
    tuple[dict[str, Any], dict[str, Any], Mapping[str, bytes | tuple[str, bytes]]]
```

Determine data, params, and files for the Requests call.

Parameters

- **http_method** (str) – get or post
- **params** (`Mapping[str, Any] | None`) – key value pairs to send with GET calls

- **data** (`Mapping[str, Any] | None`) – key value pairs to send with POST calls
- **files** (`Mapping[str, bytes | tuple[str, bytes]] | None`) – dictionary of files to send with request

Return type

`tuple[dict[str, Any], dict[str, Any], Mapping[str, bytes | tuple[str, bytes]]]`

`_get(_name, _method, requests_args=None, requests_params=None, headers=None, params=None, data=None, files=None, response_class=<class 'requests.models.Response'>, version_introduced='', version_removed='', **kwargs) → Any`

Send GET request.

Parameters

- **api_namespace** – the namespace for the API endpoint (e.g. `APINames` or `torrents`)
- **api_method** – the name for the API endpoint (e.g. `add`)
- **kwargs** (`Any`) – see `_request()`

Return type

`Any`

Returns

Requests `Response`

`_get_cast(_name, _method, response_class, requests_args=None, requests_params=None, headers=None, params=None, data=None, files=None, version_introduced='', version_removed='', **kwargs) → ResponseT`

Send GET request with casted response.

Parameters

- **api_namespace** – the namespace for the API endpoint (e.g. `APINames` or `torrents`)
- **api_method** – the name for the API endpoint (e.g. `add`)
- **kwargs** (`Any`) – see `_request()`

Return type

`TypeVar(ResponseT)`

`static _handle_error_responses(data, params, response) → None`

Raise proper exception if qBittorrent returns Error HTTP Status.

Return type

`None`

`_initialize_context() → None`

Initialize and reset communications context with qBittorrent.

This is necessary on startup or when the authorization cookie needs to be replaced... perhaps because it expired, qBittorrent was restarted, significant settings changes, etc.

Return type

`None`

```
_initialize_settings(EXTRA_HEADERS=None, REQUESTS_ARGS=None,  
    HTTPADAPTER_ARGS=None, VERIFY_WEBUI_CERTIFICATE=True,  
    FORCE_SCHEME_FROM_HOST=False,  
    RAISE_NOTIMPLEMENTEDERROR_FOR_UNIMPLEMENTED_API_ENDPOINTS=False,  
    RAISE_ERROR_FOR_UNSUPPORTED_QBITTORRENT_VERSIONS=False,  
    VERBOSE_RESPONSE_LOGGING=False, SIMPLE_RESPONSES=False,  
    DISABLE_LOGGING_DEBUG_OUTPUT=False) → None
```

Initialize lesser used configuration.

Return type

`None`

```
_is_endpoint_supported_for_version(endpoint, version_introduced, version_removed) → bool
```

Prevent using an API methods that doesn't exist in this version of qBittorrent.

Parameters

- **endpoint** (`str`) – name of the removed endpoint, e.g. torrents/ban_peers
- **version_introduced** (`str`) – the Web API version the endpoint was introduced
- **version_removed** (`str`) – the Web API version the endpoint was removed

Return type

`bool`

```
classmethod _list2string(input_list, delimiter=')') → str | T
```

Convert entries in a list to a concatenated string.

Parameters

- **input_list** (`TypeVar(T)`) – list to convert
- **delimiter** (`str`) – delimiter for concatenation

Return type

`str | TypeVar(T)`

```
_post(_name, _method, requests_args=None, requests_params=None, headers=None, params=None,  
    data=None, files=None, response_class=<class 'requests.models.Response'>, version_introduced='',  
    version_removed='', **kwargs) → Any
```

Send POST request.

Parameters

- **api_namespace** – the namespace for the API endpoint (e.g. `APINames` or `torrents`)
- **api_method** – the name for the API endpoint (e.g. `add`)
- **kwargs** (`Any`) – see `_request()`

Return type

`Any`

```
_post_cast(_name, _method, response_class, requests_args=None, requests_params=None, headers=None,  
    params=None, data=None, files=None, version_introduced='', version_removed='', **kwargs)  
    → ResponseT
```

Send POST request with casted response.

Parameters

- **api_namespace** – the namespace for the API endpoint (e.g. `APINames` or `torrents`)
- **api_method** – the name for the API endpoint (e.g. `add`)

- **kwargs** (`Any`) – see `_request()`

Return type

`TypeVar(ResponseT)`

`_request(http_method, api_namespace, api_method, requests_args=None, requests_params=None, headers=None, params=None, data=None, files=None, response_class=<class 'requests.models.Response'>, **kwargs) → Any`

Meat and potatoes of sending requests to qBittorrent.

Parameters

- **http_method** (`str`) – get or post
- **api_namespace** (`APINames` | `str`) – the namespace for the API endpoint (e.g. `APINames` or `torrents`)
- **api_method** (`str`) – the name for the API endpoint (e.g. add)
- **requests_args** (`Mapping[str, Any] | None`) – default location for Requests kwargs
- **requests_params** (`Mapping[str, Any] | None`) – alternative location for Requests kwargs
- **headers** (`Mapping[str, str] | None`) – HTTP headers to send with the request
- **params** (`Mapping[str, Any] | None`) – key/value pairs to send with a GET request
- **data** (`Mapping[str, Any] | None`) – key/value pairs to send with a POST request
- **files** (`Mapping[str, bytes | tuple[str, bytes]] | None`) – files to be sent with the request
- **response_class** (`type`) – class to use to cast the API response
- **kwargs** (`Any`) – arbitrary keyword arguments to send with the request

Return type

`Any`

`_request_manager(http_method, api_namespace, api_method, _retries=1, _retry_backoff_factor=0.3, requests_args=None, requests_params=None, headers=None, params=None, data=None, files=None, response_class=<class 'requests.models.Response'>, version_introduced='', version_removed='', **kwargs) → Any`

Wrapper to manage request retries and severe exceptions.

This should retry at least once to account for the Web API switching from HTTP to HTTPS. During the second attempt, the URL is rebuilt using HTTP or HTTPS as appropriate.

Return type

`Any`

`property _session: QbittorrentSession`

Create or return existing HTTP session.

`_trigger_session_initialization() → None`

Effectively resets the HTTP session by removing the reference to it.

During the next request, a new session will be created.

Return type

`None`

`_verbose_logging(url, data, params, requests_kwargs, response) → None`

Log verbose information about request; can be useful during development.

Return type

`None`

RSS

```
class RSSAPIMixIn(host=None, port=None, username=None, password=None, EXTRA_HEADERS=None,
                   REQUESTS_ARGS=None, HTTPADAPTER_ARGS=None,
                   VERIFY_WEBUI_CERTIFICATE=True, FORCE_SCHEME_FROM_HOST=False,
                   RAISE_NOTIMPLEMENTEDERROR_FOR_UNIMPLEMENTED_API_ENDPOINTS=False,
                   RAISE_ERROR_FOR_UNSUPPORTED_QBITTORRENT_VERSIONS=False,
                   VERBOSE_RESPONSE_LOGGING=False, SIMPLE_RESPONSES=False,
                   DISABLE_LOGGING_DEBUG_OUTPUT=False) → None
```

Bases: `AppAPIMixIn`

Implementation of all RSS API methods.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host="localhost:8080", username="admin", password=
   ↴ "adminadmin")
>>> rss_rules = client.rss_rules()
>>> client.rss_set_rule(rule_name="...", rule_def={...})
```

`rss_add_feed(url=None, item_path='', **kwargs) → None`

Add new RSS feed. Folders in path must already exist.

Raises

`Conflict409Error` –

Parameters

- `url (str | None)` – URL of RSS feed (e.g. `https://distrowatch.com/news/torrents.xml`)
- `item_path (str)` – Name and/or path for new feed; defaults to the URL. (e.g. `Folder\Subfolder\FeedName`)

Return type

`None`

`rss_add_folder(folder_path=None, **kwargs) → None`

Add an RSS folder. Any intermediate folders in path must already exist.

Raises

`Conflict409Error` –

Parameters

`folder_path (str | None)` – path to new folder (e.g. `Linux\ISOs`)

Return type

`None`

`rss_items(include_feed_data=None, **kwargs) → RSSItemsDictionary`

Retrieve RSS items and optionally feed data.

Parameters

`include_feed_data (bool | None)` – True or false to include feed data

Return type

RSSItemsDictionary

rss_mark_as_read(*item_path*=None, *article_id*=None, ***kwargs*) → None

Mark RSS article as read. If article ID is not provider, the entire feed is marked as read.

This method was introduced with qBittorrent v4.2.5 (Web API v2.5.1).

Raises

NotFound404Error –

Parameters

- **item_path** (str | None) – path to item to be refreshed (e.g. Folder\Subfolder\ItemName)
- **article_id** (str | int | None) – article ID from *rss_items()*

Return type

None

rss_matching_articles(*rule_name*=None, ***kwargs*) → *RSSItemsDictionary*

Fetch all articles matching a rule.

This method was introduced with qBittorrent v4.2.5 (Web API v2.5.1).

Parameters

rule_name (str | None) – Name of rule to return matching articles

Return type

RSSItemsDictionary

rss_move_item(*orig_item_path*=None, *new_item_path*=None, ***kwargs*) → None

Move/rename an RSS item (folder, feed, etc.).

Raises

Conflict409Error –

Parameters

- **orig_item_path** (str | None) – path to item to be removed (e.g. Folder\Subfolder\ItemName)
- **new_item_path** (str | None) – path to item to be removed (e.g. Folder\Subfolder\ItemName)

Return type

None

rss_refresh_item(*item_path*=None, ***kwargs*) → None

Trigger a refresh for an RSS item.

Note: qBittorrent v4.1.5 through v4.1.8 all use Web API v2.2 but this endpoint was introduced with v4.1.8; so, behavior may be undefined for these versions.

Parameters

item_path (str | None) – path to item to be refreshed (e.g. Folder\Subfolder\ItemName)

Return type

None

`rss_remove_item(item_path=None, **kwargs) → None`

Remove an RSS item (folder, feed, etc.).

NOTE: Removing a folder also removes everything in it.

Raises

Conflict409Error –

Parameters

`item_path (str | None)` – path to item to be removed (e.g. Folder\Subfolder\ItemName)

Return type

`None`

`rss_remove_rule(rule_name=None, **kwargs) → None`

Delete a RSS auto-downloading rule.

Parameters

`rule_name (str | None)` – Name of rule to delete

Return type

`None`

`rss_rename_rule(orig_rule_name=None, new_rule_name=None, **kwargs) → None`

Rename an RSS auto-download rule.

This method did not work properly until qBittorrent v4.3.0 (Web API v2.6).

Parameters

- `orig_rule_name (str | None)` – current name of rule
- `new_rule_name (str | None)` – new name for rule

Return type

`None`

`rss_rules(kwargs) → RSSRulesDictionary`**

Retrieve RSS auto-download rule definitions.

Return type

RSSRulesDictionary

`rss_set_feed_url(url=None, item_path=None, **kwargs) → None`

Update the URL for an existing RSS feed.

This method was introduced with qBittorrent v4.6.0 (Web API v2.9.1).

Raises

Conflict409Error –

Parameters

- `url (str | None)` – URL of RSS feed (e.g. <https://distrowatch.com/news/torrents.xml>)
- `item_path (str | None)` – Name and/or path for feed (e.g. Folder\Subfolder\FeedName)

Return type

`None`

`rss_set_rule(rule_name=None, rule_def=None, **kwargs) → None`

Create a new RSS auto-downloading rule.

Parameters

- **rule_name** (str | None) – name for new rule
- **rule_def** (Mapping[str, qbittorrentapi.definitions.JsonValueT] | None) – dictionary with rule fields - [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)
#user-content-set-auto-downloading-rule](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#user-content-set-auto-downloading-rule)

Return type

None

class RSS(client)

Allows interaction with RSS API endpoints.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host="localhost:8080", username="admin", password=
    >>>     "adminadmin")
>>> # this is all the same attributes that are available as named in the
>>> # endpoints or the more pythonic names in Client (with or without
    >>>     'log_' prepended)
>>> rss_rules = client.rss.rules
>>> client.rss.addFolder(folder_path="TPB")
>>> client.rss.addFeed(url="...", item_path="TPB\Top100")
>>> client.rss.remove_item(item_path="TPB") # deletes TPB and Top100
>>> client.rss.set_rule(rule_name="...", rule_def={...})
>>> items = client.rss.items.with_data
>>> items_no_data = client.rss.items.without_data
```

class Items(*args, client, **kwargs)**__call__(include_feed_data=None, **kwargs) → RSSItemsDictionary**Implements `rss_items()`.**Return type**`RSSItemsDictionary`**property with_data: RSSItemsDictionary**Implements `rss_items()` with `include_feed_data=True`.**property without_data: RSSItemsDictionary**Implements `rss_items()` with `include_feed_data=False`.**add_feed(url=None, item_path='', **kwargs) → None**Implements `rss_add_feed()`.**Return type**

None

add_folder(folder_path=None, **kwargs) → NoneImplements `rss_add_folder()`.**Return type**

None

property items: ItemsImplements `rss_items()`.**mark_as_read(item_path=None, article_id=None, **kwargs) → None**Implements `rss_mark_as_read()`.

Return type
None

matching_articles(rule_name=None, **kwargs) → RSSItemsDictionary
Implements `rss_matching_articles()`.

Return type
`RSSItemsDictionary`

move_item(orig_item_path=None, new_item_path=None, **kwargs) → None
Implements `rss_move_item()`.

Return type
None

refresh_item(item_path=None) → None
Implements `rss_refresh_item()`.

Return type
None

remove_item(item_path=None, **kwargs) → None
Implements `rss_remove_item()`.

Return type
None

remove_rule(rule_name=None, **kwargs) → None
Implements `rss_remove_rule()`.

Return type
None

rename_rule(orig_rule_name=None, new_rule_name=None, **kwargs) → None
Implements `rss_rename_rule()`.

Return type
None

property rules: RSSRulesDictionary
Implements `rss_rules()`.

set_feed_url(url=None, item_path=None, **kwargs) → None
Implements `rss_set_feed_url()`.

Return type
None

set_rule(rule_name=None, rule_def=None, **kwargs) → None
Implements `rss_set_rule()`.

Return type
None

class RSSItemsDictionary(data=None, **kwargs)
Bases: `Dictionary[None | int | str | bool | Sequence[JsonValueT] | Mapping[str, JsonValueT]]`
Response for `rss_items()`

```
class RSSRulesDictionary(data=None, **kwargs)
Bases: Dictionary[None | int | str | bool | Sequence[JsonValueT] | Mapping[str, JsonValueT]]
Response for rss\_rules\(\)
```

Search

```
class SearchAPIMixIn(host=None, port=None, username=None, password=None, EXTRA_HEADERS=None,
REQUESTS_ARGS=None, HTTPADAPTER_ARGS=None,
VERIFY_WEBUI_CERTIFICATE=True, FORCE_SCHEME_FROM_HOST=False,
RAISE_NOTIMPLEMENTEDERROR_FOR_UNIMPLEMENTED_API_ENDPOINTS=False,
RAISE_ERROR_FOR_UNSUPPORTED_QBITTORRENT_VERSIONS=False,
VERBOSE_RESPONSE_LOGGING=False, SIMPLE_RESPONSES=False,
DISABLE_LOGGING_DEBUG_OUTPUT=False) → None
```

Bases: [AppAPIMixIn](#)

Implementation for all Search API methods.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host="localhost:8080", username="admin", password=
    "adminadmin")
>>> search_job = client.search_start(pattern="Ubuntu", plugins="all", □
    category="all")
>>> client.search_stop(search_id=search_job.id)
>>> # or
>>> search_job.stop()
```

search_categories(plugin_name=None, **kwargs) → [SearchCategoriesList](#)

Retrieve categories for search.

This method was introduced with qBittorrent v4.1.4 (Web API v2.1.1) and removed with qBittorrent v4.3.0 (Web API v2.6).

Parameters

plugin_name (str | None) – Limit categories returned by plugin(s) (supports all and enabled)

Return type

[SearchCategoriesList](#)

search_delete(search_id=None, **kwargs) → None

Delete a search job.

This method was introduced with qBittorrent v4.1.4 (Web API v2.1.1).

Raises

[NotFound404Error](#) –

Parameters

search_id (str | int | None) – ID of search to delete

Return type

[None](#)

search_download_torrent(url=None, plugin=None, **kwargs) → None

Download a .torrent file or magnet for a search plugin.

This method was introduced with qBittorrent v5.0.0 (Web API v2.11).

Parameters

- **url** (`str` | `None`) – URL for .torrent file or magnet
- **plugin** (`str` | `None`) – Name of the plugin

Return type`None`**search_enable_plugin**(`plugins=None, enable=None, **kwargs`) → `None`

Enable or disable search plugin(s).

This method was introduced with qBittorrent v4.1.4 (Web API v2.1.1).

Parameters

- **plugins** (`str` | `Iterable[str]` | `None`) – list of plugin names
- **enable** (`bool` | `None`) – Defaults to True if `None` or unset; use `False` to disable

Return type`None`**search_install_plugin**(`sources=None, **kwargs`) → `None`

Install search plugins from either URL or file.

This method was introduced with qBittorrent v4.1.4 (Web API v2.1.1).

Parameters`sources` (`str` | `Iterable[str]` | `None`) – list of URLs or filepaths**Return type**`None`**search_plugins**(`**kwargs`) → `SearchPluginsList`

Retrieve details of search plugins.

This method was introduced with qBittorrent v4.1.4 (Web API v2.1.1).

Return type`SearchPluginsList`**search_results**(`search_id=None, limit=None, offset=None, **kwargs`) → `SearchResultsDictionary`

Retrieve the results for the search.

This method was introduced with qBittorrent v4.1.4 (Web API v2.1.1).

Raises

- `NotFound404Error` –
- `Conflict409Error` –

Parameters

- **search_id** (`str` | `int` | `None`) – ID of search job
- **limit** (`str` | `int` | `None`) – number of results to return
- **offset** (`str` | `int` | `None`) – where to start returning results

Return type`SearchResultsDictionary`

search_start(*pattern=None, plugins=None, category=None, **kwargs*) → *SearchJobDictionary*

Start a search. Python must be installed. Host may limit number of concurrent searches.

This method was introduced with qBittorrent v4.1.4 (Web API v2.1.1).

Raises

Conflict409Error –

Parameters

- **pattern** (*str | None*) – term to search for
- **plugins** (*str | Iterable[str] | None*) – list of plugins to use for searching (supports ‘all’ and ‘enabled’)
- **category** (*str | None*) – categories to limit search; dependent on plugins. (supports ‘all’)

Return type

SearchJobDictionary

search_status(*search_id=None, **kwargs*) → *SearchStatusesList*

Retrieve status of one or all searches.

This method was introduced with qBittorrent v4.1.4 (Web API v2.1.1).

Raises

NotFound404Error –

Parameters

search_id (*str | int | None*) – ID of search to get status; leave empty for status of all jobs

Return type

SearchStatusesList

search_stop(*search_id=None, **kwargs*) → *None*

Stop a running search.

This method was introduced with qBittorrent v4.1.4 (Web API v2.1.1).

Raises

NotFound404Error –

Parameters

search_id (*str | int | None*) – ID of search job to stop

Return type

None

search_uninstall_plugin(*names=None, **kwargs*) → *None*

Uninstall search plugins.

This method was introduced with qBittorrent v4.1.4 (Web API v2.1.1).

Parameters

names (*str | Iterable[str] | None*) – names of plugins to uninstall

Return type

None

search_update_plugins(***kwargs*) → *None*

Auto update search plugins.

This method was introduced with qBittorrent v4.1.4 (Web API v2.1.1).

Return type

None

class Search(*args, client, **kwargs)

Allows interaction with Search API endpoints.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host="localhost:8080", username="admin", password=
    <-->"adminadmin")
>>> # this is all the same attributes that are available as named in the
>>> # endpoints or the more pythonic names in Client (with or without
    <-->'search_' prepended)
>>> # initiate searches and retrieve results
>>> search_job = client.search.start(pattern="Ubuntu", plugins="all", u
    <-->category="all")
>>> status = search_job.status()
>>> results = search_job.result()
>>> search_job.delete()
>>> # inspect and manage plugins
>>> plugins = client.search.plugins
>>> cats = client.search.categories(plugin_name="...")
>>> client.search.install_plugin(sources="...")
>>> client.search.update_plugins()
```

categories(plugin_name=None, **kwargs) → SearchCategoriesListImplements `search_categories()`.**Return type**`SearchCategoriesList`**delete(search_id=None, **kwargs) → None**Implements `search_delete()`.**Return type**

None

download_torrent(url=None, plugin=None, **kwargs) → NoneImplements `search_download_torrent()`.**Return type**

None

enable_plugin(plugin=None, enable=None, **kwargs) → NoneImplements `search_enable_plugin()`.**Return type**

None

install_plugin(sources=None, **kwargs) → NoneImplements `search_install_plugin()`.**Return type**

None

property plugins: SearchPluginsListImplements `search_plugins()`.

results(*search_id=None, limit=None, offset=None, **kwargs*) → *SearchResultsDictionary*
Implements *search_results()*.

Return type
SearchResultsDictionary

start(*pattern=None, plugins=None, category=None, **kwargs*) → *SearchJobDictionary*
Implements *search_start()*.

Return type
SearchJobDictionary

status(*search_id=None, **kwargs*) → *SearchStatusesList*
Implements *search_status()*.

Return type
SearchStatusesList

stop(*search_id=None, **kwargs*) → None
Implements *search_stop()*.

Return type
None

uninstall_plugin(*sources=None, **kwargs*) → None
Implements *search_uninstall_plugin()*.

Return type
None

update_plugins(***kwargs*) → None
Implements *search_update_plugins()*.

Return type
None

class SearchJobDictionary(*data, client*)
Bases: *ClientCache[SearchAPIMixIn], Dictionary[None | int | str | bool | Sequence[JsonValueT] | Mapping[str, JsonValueT]]*
Response for *search_start()*

delete(***kwargs*) → None
Implements *search_delete()*.

Return type
None

results(*limit=None, offset=None, **kwargs*) → *SearchResultsDictionary*
Implements *search_results()*.

Return type
SearchResultsDictionary

status(***kwargs*) → *SearchStatusesList*
Implements *search_status()*.

Return type
SearchStatusesList

```
stop(**kwargs) → None
    Implements search_stop().
    Return type
        None

class SearchResultsDictionary(data=None, **kwargs)
    Bases: Dictionary[None | int | str | bool | Sequence[JsonValueT] | Mapping[str, JsonValueT]]
    Response for search_results()
    Definition: https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)
    #user-content-get-search-results

class SearchStatusesList(list_entries, client=None)
    Bases: List[SearchStatus]
    Response for search_status()
    Definition: https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)
    #user-content-get-search-status

class SearchStatus(data=None, **kwargs)
    Bases: ListEntry
    Item in SearchStatusesList

class SearchCategoriesList(list_entries, client=None)
    Bases: List[SearchCategory]
    Response for search_categories()

class SearchCategory(data=None, **kwargs)
    Bases: ListEntry
    Item in SearchCategoriesList

class SearchPluginsList(list_entries, client=None)
    Bases: List[SearchPlugin]
    Response for search_plugins().
    Definition: https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)
    #user-content-get-search-plugins

class SearchPlugin(data=None, **kwargs)
    Bases: ListEntry
    Item in SearchPluginsList
```

Sync

```
class SyncAPIMixIn(host=None, port=None, username=None, password=None, EXTRA_HEADERS=None,
    REQUESTS_ARGS=None, HTTPADAPTER_ARGS=None,
    VERIFY_WEBUI_CERTIFICATE=True, FORCE_SCHEME_FROM_HOST=False,
    RAISE_NOTIMPLEMENTEDERROR_FOR_UNIMPLEMENTED_API_ENDPOINTS=False,
    RAISE_ERROR_FOR_UNSUPPORTED_QBITTORRENT_VERSIONS=False,
    VERBOSE_RESPONSE_LOGGING=False, SIMPLE_RESPONSES=False,
    DISABLE_LOGGING_DEBUG_OUTPUT=False) → None
```

Bases: `AppAPIMixIn`

Implementation of all Sync API Methods.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host="localhost:8080", username="admin", password=
    >>>     "adminadmin")
>>> maindata = client.sync_maindata(rid="...")
>>> torrent_peers = client.sync_torrent_peers(torrent_hash="...", rid="...
    >>>     ...")
```

sync_maindata(*rid*=0, ***kwargs*) → *SyncMainDataDictionary*

Retrieves sync data.

Parameters

rid (*str* | *int*) – response ID

Return type

SyncMainDataDictionary

sync_torrent_peers(*torrent_hash*=None, *rid*=0, ***kwargs*) → *SyncTorrentPeersDictionary*

Retrieves torrent sync data.

Raises

NotFound404Error –

Parameters

- **torrent_hash** (*str* | *None*) – hash for torrent
- **rid** (*str* | *int*) – response ID

Return type

SyncTorrentPeersDictionary

class Sync(*client*) → *None*

Allows interaction with the Sync API endpoints.

Usage:

```
>>> from qbittorrentapi import Client
>>> client = Client(host="localhost:8080", username="admin", password=
    >>>     "adminadmin")
>>> # these are all the same attributes that are available as named in the
>>> # endpoints or the more pythonic names in Client (with or without 'sync_'
    >>>     prepended)
>>> maindata = client.sync.maindata(rid="...")
>>> # for use when continuously calling maindata for changes in torrents
>>> # this will automatically request the changes since the last call
>>> md = client.sync.maindata.delta()
>>> #
>>> torrentPeers = client.sync.torrentPeers(torrent_hash="...", rid="...")
>>> torrent_peers = client.sync.torrent_peers(torrent_hash="...", rid="...")
```

class MainData(*client*) → *None*

__call__(*rid*=0, ***kwargs*) → *SyncMainDataDictionary*

Call self as a function.

Return type

SyncMainDataDictionary

delta(kwargs) → SyncMainDataDictionary**
 Implements `sync_maindata()` to return updates since last call.
Return type
`SyncMainDataDictionary`

reset_rid() → None
 Resets RID so the next request includes everything.
Return type
`None`

class TorrentPeers(client) → None

__call__(torrent_hash=None, rid=0, **kwargs) → SyncTorrentPeersDictionary
 Implements `sync_torrent_peers()`.
Return type
`SyncTorrentPeersDictionary`

delta(torrent_hash=None, **kwargs) → SyncTorrentPeersDictionary
 Implements `sync_torrent_peers()` to return updates since last call.
Return type
`SyncTorrentPeersDictionary`

reset_rid() → None
 Resets RID so the next request includes everything.
Return type
`None`

property maindata: MainData
 Implements `sync_maindata()`.

property torrentPeers: TorrentPeers
 Implements `sync_torrent_peers()`.

property torrent_peers: TorrentPeers
 Implements `sync_torrent_peers()`.

class SyncMainDataDictionary(data=None, **kwargs)
 Bases: `Dictionary[None | int | str | bool | Sequence[JsonValueT] | Mapping[str, JsonValueT]]`
 Response for `sync_maindata()`
 Definition: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1))
`#user-content-get-main-data`

class SyncTorrentPeersDictionary(data=None, **kwargs)
 Bases: `Dictionary[None | int | str | bool | Sequence[JsonValueT] | Mapping[str, JsonValueT]]`
 Response for `sync_torrent_peers()`
 Definition: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1))
`#user-content-get-torrent-peers-data`

Torrent Creator

```
class TorrentCreatorAPIMixIn(host=None, port=None, username=None, password=None,
    EXTRA_HEADERS=None, REQUESTS_ARGS=None,
    HTTPADAPTER_ARGS=None, VERIFY_WEBUI_CERTIFICATE=True,
    FORCE_SCHEME_FROM_HOST=False,
    RAISE_NOTIMPLEMENTEDERROR_FOR_UNIMPLEMENTED_API_ENDPOINTS=False,
    RAISE_ERROR_FOR_UNSUPPORTED_QBITTORRENT_VERSIONS=False,
    VERBOSE_RESPONSE_LOGGING=False, SIMPLE_RESPONSES=False,
    DISABLE_LOGGING_DEBUG_OUTPUT=False) → None
```

Bases: [AppAPIMixIn](#)

Implementation of all TorrentCreator API methods.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host="localhost:8080", username="admin", password=
   ↪ "adminadmin")
>>> task = client.torrentcreator_add_task(source_path="/path/to/data")
>>> if TaskStatus(task.status().status) == TaskStatus.FINISHED:
>>>     torrent_data = task.torrent_file()
>>> task.delete()
>>> # or
>>> client.torrentcreator_delete_task(task_id=task.taskID)
```

```
torrentcreator_add_task(source_path=None, torrent_file_path=None, format=None,
                        start_seeding=None, is_private=None, optimize_alignment=None,
                        padded_file_size_limit=None, piece_size=None, comment=None,
                        trackers=None, url_seeds=None, **kwargs) → TorrentCreatorTaskDictionary
```

Add a task to create a new torrent.

This method was introduced with qBittorrent v5.0.0 (Web API v2.10.4).

Raises

[Conflict409Error](#) – too many existing torrent creator tasks

Parameters

- **source_path** (`str` | `PathLike[Any]` | `None`) – source file path for torrent content
- **torrent_file_path** (`str` | `PathLike[Any]` | `None`) – file path to save torrent
- **format** (`Literal['v1', 'v2', 'hybrid']` | `None`) – BitTorrent V1 or V2; defaults to “hybrid” format if `None`
- **start_seeding** (`bool` | `None`) – should qBittorrent start seeding this torrent?
- **is_private** (`bool` | `None`) – is the torrent private or not?
- **optimize_alignment** (`bool` | `None`) – should optimized alignment be enforced for new torrent?
- **padded_file_size_limit** (`int` | `None`) – size limit for padding files
- **piece_size** (`int` | `None`) – size of the pieces
- **comment** (`str` | `None`) – comment
- **trackers** (`str` | `list[str]` | `None`) – list of trackers to add
- **url_seeds** (`str` | `list[str]` | `None`) – list of URLs seeds to add

Return type*TorrentCreatorTaskDictionary***torrentcreator_delete_task**(task_id=None, **kwargs) → None

Delete a torrent creation task.

This method was introduced with qBittorrent v5.0.0 (Web API v2.10.4).

Raises*NotFound404Error* – task not found**Parameters****task_id** (str | None) – ID of torrent creation task**Return type***None***torrentcreator_status**(task_id=None, **kwargs) → *TorrentCreatorTaskStatusList*

Status for a torrent creation task.

This method was introduced with qBittorrent v5.0.0 (Web API v2.10.4).

Raises*NotFound404Error* – task not found**Parameters****task_id** (str | None) – ID of torrent creation task**Return type***TorrentCreatorTaskStatusList***torrentcreator_torrent_file**(task_id=None, **kwargs) → bytes

Retrieve torrent file for created torrent.

This method was introduced with qBittorrent v5.0.0 (Web API v2.10.4).

Raises

- *NotFound404Error* – task not found
- *Conflict409Error* – torrent creation is not finished or failed

Parameters**task_id** (str | None) – ID of torrent creation task**Return type***bytes***class TorrentCreator(*args, client, **kwargs)**

Allows interaction with TorrentCreator API endpoints.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host="localhost:8080", username="admin", password=
    >>>     "adminadmin")
>>> # this is all the same attributes that are available as named in the
>>> # endpoints or the more pythonic names in Client (with or without
    >>>     'torrentcreator_' prepended)
>>> task = client.torrentcreator.add_task(source_path="/path/to/data")
>>> if TaskStatus(task.status().status) == TaskStatus.FINISHED:
    >>>     torrent_data = task.torrent_file()
```

(continues on next page)

(continued from previous page)

```
>>> task.delete()
>>> # or
>>> client.torrentcreator.delete_task(task_id=task.taskID)
```

add_task(source_path=None, torrent_file_path=None, format=None, start_seeding=None, is_private=None, optimize_alignment=None, padded_file_size_limit=None, piece_size=None, comment=None, trackers=None, url_seeds=None, **kwargs) → TorrentCreatorTaskDictionary

Implements `torrentcreator_add_task()`.

Return type

`TorrentCreatorTaskDictionary`

delete_task(task_id=None, **kwargs) → None

Implements `torrentcreator_delete_task()`.

Return type

`None`

status(task_id=None, **kwargs) → TorrentCreatorTaskStatusList

Implements `torrentcreator_status()`.

Return type

`TorrentCreatorTaskStatusList`

torrent_file(task_id=None, **kwargs) → bytes

Implements `torrentcreator_torrent_file()`.

Return type

`bytes`

class TorrentCreatorTaskDictionary(data, client)

Bases: `ClientCache[TorrentCreatorAPIMixIn]`, `Dictionary[None | int | str | bool | Sequence[JsonValueT] | Mapping[str, JsonValueT]]`

Response for `torrentcreator_add_task()`

delete(**kwargs) → None

Implements `torrentcreator_delete_task()`.

Return type

`None`

status(**kwargs) → TorrentCreatorTaskStatus

Implements `torrentcreator_status()`.

Return type

`TorrentCreatorTaskStatus`

torrent_file(**kwargs) → bytes

Implements `torrentcreator_torrent_file()`.

Return type

`bytes`

class TorrentCreatorTaskStatus(data=None, **kwargs)

Bases: `ListEntry`

Item in `TorrentCreatorTaskStatusList`

Definition: not documented...yet

```
class TaskStatus(value, names=<not given>, *values, module=None, qualname=None, type=None, start=1, boundary=None)
```

Bases: `Enum`

Enumeration of possible task statuses.

```
FAILED = 'Failed'
```

```
FINISHED = 'Finished'
```

```
QUEUED = 'Queued'
```

```
RUNNING = 'Running'
```

```
class TorrentCreatorTaskStatusList(list_entries, client=None)
```

Bases: `List[TorrentCreatorTaskStatus]`

Response for `torrentcreator_status()`

Torrents

```
class TorrentsAPIMixIn(host=None, port=None, username=None, password=None, EXTRA_HEADERS=None, REQUESTS_ARGS=None, HTTPADAPTER_ARGS=None, VERIFY_WEBUI_CERTIFICATE=True, FORCE_SCHEME_FROM_HOST=False, RAISE_NOTIMPLEMENTEDERROR_FOR_UNIMPLEMENTED_API_ENDPOINTS=False, RAISE_ERROR_FOR_UNSUPPORTED_QBITTORRENT_VERSIONS=False, VERBOSE_RESPONSE_LOGGING=False, SIMPLE_RESPONSES=False, DISABLE_LOGGING_DEBUG_OUTPUT=False) → None
```

Bases: `AppAPIMixIn`

Implementation of all Torrents API methods.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host="localhost:8080", username="admin", password=
← "adminadmin")
>>> client.torrents_add(urls="...")
>>> client.torrents_reannounce()
```

```
torrents_add(urls=None, torrent_files=None, save_path=None, cookie=None, category=None, is_skip_checking=None, is_paused=None, is_root_folder=None, rename=None, upload_limit=None, download_limit=None, use_auto_torrent_management=None, is_sequential_download=None, is_first_last_piece_priority=None, tags=None, content_layout=None, ratio_limit=None, seeding_time_limit=None, download_path=None, use_download_path=None, stop_condition=None, add_to_top_of_queue=None, inactive_seeding_time_limit=None, share_limit_action=None, ssl_certificate=None, ssl_private_key=None, ssl_dh_params=None, is_stopped=None, forced=None, **kwargs) → str
```

Add one or more torrents by URLs and/or torrent files.

Returns `Ok`. for success and `Fail`. for failure.

Raises

- `UnsupportedMediaType415Error` – if file is not a valid torrent file
- `TorrentFileNotFoundException` – if a torrent file doesn't exist

- **TorrentFilePermissionError** – if read permission is denied to torrent file

Parameters

- **urls** (`str | Iterable[str] | None`) – single instance or an iterable of URLs (`http://`, `https://`, `magnet://`, `bc://bt/`)
- **torrent_files** (`TypeVar(TorrentFilesT, bytes, str, IO[bytes], Mapping[str, bytes | str | IO[bytes]], Iterable[bytes | str | IO[bytes]]) | None`) – several options are available to send torrent files to qBittorrent:
 - single instance of bytes: useful if torrent file already read from disk or downloaded from internet.
 - single instance of file handle to torrent file: use `open(<filepath>, 'rb')` to open the torrent file.
 - single instance of a filepath to torrent file: e.g. `/home/user/torrent_filename.torrent`
 - an iterable of the single instances above to send more than one torrent file
 - dictionary with key/value pairs of torrent name and single instance of above object
- Note: The torrent name in a dictionary is useful to identify which torrent file errored. qBittorrent provides back that name in the error text. If a torrent name is not provided, then the name of the file will be used. And in the case of bytes (or if filename cannot be determined), the value ‘`torrent_n`’ will be used.
- **save_path** (`str | None`) – location to save the torrent data
- **cookie** (`str | None`) – cookie(s) to retrieve torrents by URL
- **category** (`str | None`) – category to assign to torrent(s)
- **is_skip_checking** (`bool | None`) – True to skip hash checking
- **is_paused** (`bool | None`) – Adds torrent in stopped state; alias for `is_stopped`
- **is_root_folder** (`bool | None`) – True or False to create root folder (superseded by `content_layout` with v4.3.2)
- **rename** (`str | None`) – new name for torrent(s)
- **upload_limit** (`str | int | None`) – upload limit in bytes/second
- **download_limit** (`str | int | None`) – download limit in bytes/second
- **use_auto_torrent_management** (`bool | None`) – True or False to use automatic torrent management
- **is_sequential_download** (`bool | None`) – True or False for sequential download
- **is_first_last_piece_priority** (`bool | None`) – True or False for first and last piece download priority
- **tags** (`str | Iterable[str] | None`) – tag(s) to assign to torrent(s) (added in Web API v2.6.2)
- **content_layout** (`Literal['Original', 'Subfolder', 'NoSubfolder'] | None`) – Original, Subfolder, or NoSubfolder to control filesystem structure for content (added in Web API v2.7)
- **ratio_limit** (`str | float | None`) – share limit as ratio of upload amt over download amt; e.g. 0.5 or 2.0 (added in Web API v2.8.1)

- **seeding_time_limit** (`str | int | None`) – number of minutes to seed torrent (added in Web API v2.8.1)
- **download_path** (`str | None`) – location to download torrent content before moving to `save_path` (added in Web API v2.8.4)
- **use_download_path** (`bool | None`) – True or False whether `download_path` should be used... defaults to True if `download_path` is specified (added in Web API v2.8.4)
- **stop_condition** (`Literal['MetadataReceived', 'FilesChecked'] | None`) – `MetadataReceived` or `FilesChecked` to stop the torrent when started automatically (added in Web API v2.8.15)
- **add_to_top_of_queue** (`bool | None`) – puts torrent at top to the queue(added in Web API v2.8.19)
- **inactive_seeding_time_limit** (`str | int | None`) – limit for seeding while inactive (added in Web API v2.9.2)
- **share_limit_action** (`Literal['Stop', 'Remove', 'RemoveWithContent', 'EnableSuperSeeding'] | None`) – override default action when share limit is reached (added in Web API v2.10.4)
- **ssl_certificate** (`str | None`) – peer certificate (in PEM format) (added in Web API v2.10.4)
- **ssl_private_key** (`str | None`) – peer private key (added in Web API v2.10.4)
- **ssl_dh_params** (`str | None`) – Diffie-Hellman parameters (added in Web API v2.10.4)
- **is_stopped** (`bool | None`) – Adds torrent in stopped state; alias for `is_paused` (added in Web API v2.11.0)
- **forced** (`bool | None`) – add torrent in forced state (added in Web API v2.11.0)

Return type`str`**torrents_add_peers**(`peers=None, torrent_hashes=None, **kwargs`) → `TorrentsAddPeersDictionary`

Add one or more peers to one or more torrents.

This method was introduced with qBittorrent v4.4.0 (Web API v2.3.0).

Raises

`InvalidRequest400Error` – for invalid peers

Parameters

- **peers** (`str | Iterable[str] | None`) – one or more peers to add. each peer should take the form ‘host:port’
- **torrent_hashes** (`str | Iterable[str] | None`) – single torrent hash or list of torrent hashes. Or `all` for all torrents.

Return type`TorrentsAddPeersDictionary`**torrents_add_tags**(`tags=None, torrent_hashes=None, **kwargs`) → `None`

Add one or more tags to one or more torrents.

Note: Tags that do not exist will be created on-the-fly.

This method was introduced with qBittorrent v4.2.0 (Web API v2.3.0).

Parameters

- **tags** (`str | Iterable[str] | None`) – tag name or list of tags
- **torrent_hashes** (`str | Iterable[str] | None`) – single torrent hash or list of torrent hashes. Or all for all torrents.

Return type

`None`

torrents_add_trackers(`torrent_hash=None, urls=None, **kwargs`) → `None`

Add trackers to a torrent.

Raises

`NotFound404Error` –

Parameters

- **torrent_hash** (`str | None`) – hash for torrent
- **urls** (`str | Iterable[str] | None`) – tracker URLs to add to torrent

Return type

`None`

torrents_add_webseeds(`torrent_hash=None, urls=None, **kwargs`) → `None`

Add webseeds to a torrent.

Raises

- `NotFound404Error` – torrent not found
- `InvalidRequest400Error` – invalid URL

Parameters

- **torrent_hash** (`str | None`) – hash for torrent
- **urls** (`str | Iterable[str] | None`) – list of webseed URLs to add to torrent

Return type

`None`

torrents_bottom_priority(`torrent_hashes=None, **kwargs`) → `None`

Set torrent as lowest priority. Torrent Queuing must be enabled.

Raises

`Conflict409Error` –

Parameters

torrent_hashes (`str | Iterable[str] | None`) – single torrent hash or list of torrent hashes. Or all for all torrents.

Return type

`None`

torrents_categories(`**kwargs`) → `TorrentCategoriesDictionary`

Retrieve all category definitions.

This method was introduced with qBittorrent v4.1.4 (Web API v2.1.1).

Note: `torrents/categories` is not available until v2.1.0

Return type

`TorrentCategoriesDictionary`

torrents_count() → `int`

Retrieve count of torrents.

Return type`int`**torrents_create_category(*name=None, save_path=None, download_path=None, enable_download_path=None, **kwargs*)** → `None`

Create a new torrent category.

Raises

`Conflict409Error` – if category name is not valid or unable to create

Parameters

- **name** (`str` | `None`) – name for new category
- **save_path** (`str` | `None`) – location to save torrents for this category (added in Web API 2.1.0)
- **download_path** (`str` | `None`) – download location for torrents with this category
- **enable_download_path** (`bool` | `None`) – True or False to enable or disable download path

Return type`None`**torrents_create_tags(*tags=None, **kwargs*)** → `None`

Create one or more tags.

This method was introduced with qBittorrent v4.2.0 (Web API v2.3.0).

Parameters`tags` (`str` | `Iterable[str]` | `None`) – tag name or list of tags**Return type**`None`**torrents_decrease_priority(*torrent_hashes=None, **kwargs*)** → `None`

Decrease the priority of a torrent. Torrent Queuing must be enabled.

Raises

`Conflict409Error` –

Parameters

`torrent_hashes` (`str` | `Iterable[str]` | `None`) – single torrent hash or list of torrent hashes. Or all for all torrents.

Return type`None`**torrents_delete(*delete_files=False, torrent_hashes=None, **kwargs*)** → `None`

Remove a torrent from qBittorrent and optionally delete its files.

Parameters

- **torrent_hashes** (`str` | `Iterable[str]` | `None`) – single torrent hash or list of torrent hashes. Or all for all torrents.
- **delete_files** (`bool` | `None`) – True to delete the torrent's files

Return type`None`

torrents_delete_tags(tags=None, **kwargs) → None

Delete one or more tags.

This method was introduced with qBittorrent v4.2.0 (Web API v2.3.0).

Parameters

tags (str | Iterable[str] | None) – tag name or list of tags

Return type

None

torrents_download_limit(torrent_hashes=None, **kwargs) → TorrentLimitsDictionary

Retrieve the download limit for one or more torrents.

Return type

TorrentLimitsDictionary

torrents_edit_category(name=None, save_path=None, download_path=None, enable_download_path=None, **kwargs) → None

Edit an existing category.

This method was introduced with qBittorrent v4.1.3 (Web API v2.1.0).

Raises

[Conflict409Error](#) – if category name is not valid or unable to create

Parameters

- name (str | None) – category to edit
- save_path (str | None) – new location to save files for this category
- download_path (str | None) – download location for torrents with this category
- enable_download_path (bool | None) – True or False to enable or disable download path

Return type

None

torrents_edit_tracker(torrent_hash=None, original_url=None, new_url=None, **kwargs) → None

Replace a torrent's tracker with a different one.

This method was introduced with qBittorrent v4.1.4 (Web API v2.2.0).

Raises

- [InvalidRequest400Error](#) –
- [NotFound404Error](#) –
- [Conflict409Error](#) –

Parameters

- torrent_hash (str | None) – hash for torrent
- original_url (str | None) – URL for existing tracker
- new_url (str | None) – new URL to replace

Return type

None

torrents_edit_webseed(*torrent_hash=None, orig_url=None, new_url=None, **kwargs*) → *None*

Edit a webseed for a torrent.

Raises

- *NotFound404Error* – torrent not found
- *Conflict409Error* – *orig_url* is not a webseed for the torrent
- *InvalidRequest400Error* – invalid URL

Parameters

- **torrent_hash** (*str | None*) – hash for torrent
- **orig_url** (*str | None*) – webseed URL to be replaced
- **new_url** (*str | None*) – webseed URL to replace with

Return type

None

torrents_export(*torrent_hash=None, **kwargs*) → *bytes*

Export a .torrent file for the torrent.

This method was introduced with qBittorrent v4.5.0 (Web API v2.8.14).

Raises

- *NotFound404Error* – torrent not found
- *Conflict409Error* – unable to export .torrent file

Parameters

torrent_hash (*str | None*) – hash for torrent

Return type

bytes

torrents_file_priority(*torrent_hash=None, file_ids=None, priority=None, **kwargs*) → *None*

Set priority for one or more files.

Raises

- *InvalidRequest400Error* – if priority is invalid or at least one file ID is not an integer
- *NotFound404Error* –
- *Conflict409Error* – if torrent metadata has not finished downloading or at least one file was not found

Parameters

- **torrent_hash** (*str | None*) – hash for torrent
- **file_ids** (*str | int | Iterable[str | int] | None*) – single file ID or a list.
- **priority** (*str | int | None*) – priority for file(s) - [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#user-content-set-file-priority](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#user-content-set-file-priority)

Return type

None

torrents_files(*torrent_hash=None, **kwargs*) → *TorrentFilesList*

Retrieve individual torrent's files.

Raises

NotFound404Error –

Parameters

torrent_hash (`str | None`) – hash for torrent

Return type

TorrentFilesList

torrents_increase_priority(*torrent_hashes=None*, ***kwargs*) → `None`

Increase the priority of a torrent. Torrent Queuing must be enabled.

Raises

Conflict409Error –

Parameters

torrent_hashes (`str | Iterable[str] | None`) – single torrent hash or list of torrent hashes.

Or all for all torrents.

Return type

`None`

torrents_info(*status_filter=None*, *category=None*, *sort=None*, *reverse=None*, *limit=None*, *offset=None*, *torrent_hashes=None*, *tag=None*, *private=None*, *include_trackers=None*, ***kwargs*) → *TorrentInfoList*

Retrieves list of info for torrents.

Parameters

- **status_filter** (`Literal['all', 'downloading', 'seeding', 'completed', 'paused', 'stopped', 'active', 'inactive', 'resumed', 'running', 'stalled', 'stalled_uploading', 'stalled_downloading', 'checking', 'moving', 'errored'] | None`) – Filter list by torrent status:
 - Original options: all, downloading, seeding, completed, paused, active, inactive, resumed, errored
 - Added in Web API v2.4.1: stalled, stalled_uploading, and stalled_downloading
 - Added in Web API v2.8.4: checking
 - Added in Web API v2.8.18: moving
 - Added in Web API v2.11.0: stopped (replaced paused), running (replaced resumed)
- **category** (`str | None`) – Filter list by category
- **sort** (`str | None`) – Sort list by any property returned
- **reverse** (`bool | None`) – Reverse sorting
- **limit** (`str | int | None`) – Limit length of list
- **offset** (`str | int | None`) – Start of list (if < 0, offset from end of list)
- **torrent_hashes** (`str | Iterable[str] | None`) – Filter list by hash (separate multiple hashes with a '|') (added in Web API v2.0.1)
- **tag** (`str | None`) – Filter list by tag (empty string means “untagged”; no “tag” parameter means “any tag”; added in Web API v2.8.3)
- **private** (`bool | None`) – Filter list by private flag - use None to ignore; (added in Web API v2.11.1)

- **include_trackers** (bool | None) – Include trackers in response; default False; (added in Web API v2.11.4)

Return type*TorrentInfoList***torrents_pause**(*torrent_hashes=None*, ***kwargs*) → *None*

Stop one or more torrents in qBittorrent.

Parameters

torrent_hashes (str | Iterable[str] | None) – single torrent hash or list of torrent hashes.
Or all for all torrents.

Return type*None***torrents_piece_hashes**(*torrent_hash=None*, ***kwargs*) → *TorrentPieceInfoList*

Retrieve individual torrent's pieces' hashes.

Raises*NotFound404Error* –**Parameters**

torrent_hash (str | None) – hash for torrent

Return type*TorrentPieceInfoList***torrents_piece_states**(*torrent_hash=None*, ***kwargs*) → *TorrentPieceInfoList*

Retrieve individual torrent's pieces' states.

Raises*NotFound404Error* –**Parameters**

torrent_hash (str | None) – hash for torrent

Return type*TorrentPieceInfoList***torrents_properties**(*torrent_hash=None*, ***kwargs*) → *TorrentPropertiesDictionary*

Retrieve individual torrent's properties.

Raises*NotFound404Error* –**Parameters**

torrent_hash (str | None) – hash for torrent

Return type*TorrentPropertiesDictionary***torrents_reannounce**(*torrent_hashes=None*, ***kwargs*) → *None*

Reannounce a torrent.

This method was introduced with qBittorrent v4.1.2 (Web API v2.0.2).

Parameters

torrent_hashes (str | Iterable[str] | None) – single torrent hash or list of torrent hashes.
Or all for all torrents.

Return type*None*

torrents_recheck(*torrent_hashes=None*, ***kwargs*) → *None*

Recheck a torrent in qBittorrent.

Parameters

torrent_hashes (*str* | *Iterable[str]* | *None*) – single torrent hash or list of torrent hashes.
Or all for all torrents.

Return type

None

torrents_remove_categories(*categories=None*, ***kwargs*) → *None*

Delete one or more categories.

Parameters

categories (*str* | *Iterable[str]* | *None*) – categories to delete

Return type

None

torrents_remove_tags(*tags=None*, *torrent_hashes=None*, ***kwargs*) → *None*

Add one or more tags to one or more torrents.

This method was introduced with qBittorrent v4.2.0 (Web API v2.3.0).

Parameters

- **tags** (*str* | *Iterable[str]* | *None*) – tag name or list of tags
- **torrent_hashes** (*str* | *Iterable[str]* | *None*) – single torrent hash or list of torrent hashes. Or all for all torrents.

Return type

None

torrents_remove_trackers(*torrent_hash=None*, *urls=None*, ***kwargs*) → *None*

Remove trackers from a torrent.

This method was introduced with qBittorrent v4.1.4 (Web API v2.2.0).

Raises

- *NotFound404Error* –
- *Conflict409Error* –

Parameters

- **torrent_hash** (*str* | *None*) – hash for torrent
- **urls** (*str* | *Iterable[str]* | *None*) – tracker URLs to removed from torrent

Return type

None

torrents_remove_webseeds(*torrent_hash=None*, *urls=None*, ***kwargs*) → *None*

Remove webseeds from a torrent.

Raises

- *NotFound404Error* –
- *InvalidRequest400Error* – invalid URL

Parameters

- **torrent_hash** (*str* | *None*) – hash for torrent

- **urls** (`str` | `Iterable[str]` | `None`) – list of webseed URLs to add to torrent

Return type`None`**torrents_rename**(*torrent_hash=None, new_torrent_name=None, **kwargs*) → `None`

Rename a torrent.

Raises[`NotFound404Error`](#) –**Parameters**

- **torrent_hash** (`str` | `None`) – hash for torrent
- **new_torrent_name** (`str` | `None`) – new name for torrent

Return type`None`**torrents_rename_file**(*torrent_hash=None, file_id=None, new_file_name=None, old_path=None, new_path=None, **kwargs*) → `None`

Rename a torrent file.

This method was introduced with qBittorrent v4.2.1 (Web API v2.4.0).

Raises

- [`MissingRequiredParameters400Error`](#) –
- [`NotFound404Error`](#) –
- [`Conflict409Error`](#) –

Parameters

- **torrent_hash** (`str` | `None`) – hash for torrent
- **file_id** (`str` | `int` | `None`) – id for file (removed in Web API v2.7)
- **new_file_name** (`str` | `None`) – new name for file (removed in Web API v2.7)
- **old_path** (`str` | `None`) – path of file to rename (added in Web API v2.7)
- **new_path** (`str` | `None`) – new path of file to rename (added in Web API v2.7)

Return type`None`**torrents_rename_folder**(*torrent_hash=None, old_path=None, new_path=None, **kwargs*) → `None`

Rename a torrent folder.

This method was introduced with qBittorrent v4.3.2 (Web API v2.7).

Raises

- [`MissingRequiredParameters400Error`](#) –
- [`NotFound404Error`](#) –
- [`Conflict409Error`](#) –

Parameters

- **torrent_hash** (`str` | `None`) – hash for torrent
- **old_path** (`str` | `None`) – path of file to rename (added in Web API v2.7)

- **new_path** (`str | None`) – new path of file to rename (added in Web API v2.7)

Return type

`None`

torrents_resume(`torrent_hashes=None, **kwargs`) → `None`

Start one or more torrents in qBittorrent.

Parameters

- **torrent_hashes** (`str | Iterable[str] | None`) – single torrent hash or list of torrent hashes.
Or all for all torrents.

Return type

`None`

torrents_set_auto_management(`enable=None, torrent_hashes=None, **kwargs`) → `None`

Enable or disable automatic torrent management for one or more torrents.

Parameters

- **torrent_hashes** (`str | Iterable[str] | None`) – single torrent hash or list of torrent hashes. Or all for all torrents.
- **enable** (`bool | None`) – Defaults to True if `None` or unset; use `False` to disable

Return type

`None`

torrents_set_category(`category=None, torrent_hashes=None, **kwargs`) → `None`

Set a category for one or more torrents.

Raises

`Conflict409Error` – for bad category

Parameters

- **torrent_hashes** (`str | Iterable[str] | None`) – single torrent hash or list of torrent hashes. Or all for all torrents.
- **category** (`str | None`) – category to assign to torrent

Return type

`None`

torrents_set_download_limit(`limit=None, torrent_hashes=None, **kwargs`) → `None`

Set the download limit for one or more torrents.

Parameters

- **torrent_hashes** (`str | Iterable[str] | None`) – single torrent hash or list of torrent hashes. Or all for all torrents.
- **limit** (`str | int | None`) – bytes/second (-1 sets the limit to infinity)

Return type

`None`

torrents_set_download_path(`download_path=None, torrent_hashes=None, **kwargs`) → `None`

Set the Download Path for one or more torrents.

This method was introduced with qBittorrent v4.4.0 (Web API v2.8.4).

Raises

- `Forbidden403Error` – cannot write to directory

- *Conflict409Error* – cannot create directory

Parameters

- **download_path** (`str | None`) – file path to save torrent contents before torrent finishes downloading
- **torrent_hashes** (`str | Iterable[str] | None`) – single torrent hash or list of torrent hashes. Or all for all torrents.

Return type

`None`

torrents_set_force_start(`enable=None, torrent_hashes=None, **kwargs`) → `None`

Force start one or more torrents.

Parameters

- **torrent_hashes** (`str | Iterable[str] | None`) – single torrent hash or list of torrent hashes. Or all for all torrents.
- **enable** (`bool | None`) – Defaults to True if None or unset; False is equivalent to `torrents_resume()`.

Return type

`None`

torrents_set_location(`location=None, torrent_hashes=None, **kwargs`) → `None`

Set location for torrents' files.

Raises

- *Forbidden403Error* – if the user doesn't have permissions to write to the location (only before v4.5.2 - write check was removed.)
- *Conflict409Error* – if the directory cannot be created at the location

Parameters

- **torrent_hashes** (`str | Iterable[str] | None`) – single torrent hash or list of torrent hashes. Or all for all torrents.
- **location** (`str | None`) – disk location to move torrent's files

Return type

`None`

torrents_set_save_path(`save_path=None, torrent_hashes=None, **kwargs`) → `None`

Set the Save Path for one or more torrents.

This method was introduced with qBittorrent v4.4.0 (Web API v2.8.4).

Raises

- *Forbidden403Error* – cannot write to directory
- *Conflict409Error* – cannot create directory

Parameters

- **save_path** (`str | None`) – file path to save torrent contents
- **torrent_hashes** (`str | Iterable[str] | None`) – single torrent hash or list of torrent hashes. Or all for all torrents.

Return type

None

torrents_set_share_limits(*ratio_limit=None*, *seeding_time_limit=None*,
inactive_seeding_time_limit=None, *torrent_hashes=None*, ***kwargs*) →
None

Set share limits for one or more torrents.

This method was introduced with qBittorrent v4.1.1 (Web API v2.0.1).

Parameters

- **torrent_hashes** (*str | Iterable[str] | None*) – single torrent hash or list of torrent hashes. Or `all` for all torrents.
- **ratio_limit** (*str | int | None*) – max ratio to seed a torrent. (-2 means use the global value and -1 is no limit)
- **seeding_time_limit** (*str | int | None*) – minutes (-2 means use the global value and -1 is no limit)
- **inactive_seeding_time_limit** (*str | int | None*) – minutes (-2 means use the global value and -1 is no limit) (added in Web API v2.9.2)

Return type

None

torrents_set_super_seeding(*enable=None*, *torrent_hashes=None*, ***kwargs*) → None

Set one or more torrents as super seeding.

Parameters

- **torrent_hashes** (*str | Iterable[str] | None*) – single torrent hash or list of torrent hashes. Or `all` for all torrents.
- **enable** (*bool | None*) – Defaults to True if None or unset; False to disable

Return type

None

torrents_set_tags(*tags=None*, *torrent_hashes=None*, ***kwargs*) → None

Upsert one or more tags to one or more torrents.

Note: Tags that do not exist will be created on-the-fly.

This method was introduced with qBittorrent v5.1.0 (Web API v2.11.4).

Parameters

- **tags** (*str | Iterable[str] | None*) – tag name or list of tags
- **torrent_hashes** (*str | Iterable[str] | None*) – single torrent hash or list of torrent hashes. Or `all` for all torrents.

Return type

None

torrents_set_upload_limit(*limit=None*, *torrent_hashes=None*, ***kwargs*) → None

Set the upload limit for one or more torrents.

Parameters

- **torrent_hashes** (*str | Iterable[str] | None*) – single torrent hash or list of torrent hashes. Or `all` for all torrents.

- **limit** (`str | int | None`) – bytes/second (-1 sets the limit to infinity)

Return type`None`**torrents_start**(*torrent_hashes=None, **kwargs*) → `None`

Start one or more torrents in qBittorrent.

Parameters**torrent_hashes** (`str | Iterable[str] | None`) – single torrent hash or list of torrent hashes.
Or all for all torrents.**Return type**`None`**torrents_stop**(*torrent_hashes=None, **kwargs*) → `None`

Stop one or more torrents in qBittorrent.

Parameters**torrent_hashes** (`str | Iterable[str] | None`) – single torrent hash or list of torrent hashes.
Or all for all torrents.**Return type**`None`**torrents_tags**(***kwargs*) → `TagList`

Retrieve all tag definitions.

This method was introduced with qBittorrent v4.2.0 (Web API v2.3.0).

Return type`TagList`**torrents_toggle_first_last_piece_priority**(*torrent_hashes=None, **kwargs*) → `None`

Toggle priority of first/last piece downloading.

Parameters**torrent_hashes** (`str | Iterable[str] | None`) – single torrent hash or list of torrent hashes.
Or all for all torrents.**Return type**`None`**torrents_toggle_sequential_download**(*torrent_hashes=None, **kwargs*) → `None`

Toggle sequential download for one or more torrents.

Parameters**torrent_hashes** (`str | Iterable[str] | None`) – single torrent hash or list of torrent hashes.
Or all for all torrents.**Return type**`None`**torrents_top_priority**(*torrent_hashes=None, **kwargs*) → `None`

Set torrent as highest priority. Torrent Queuing must be enabled.

Raises`Conflict409Error` –**Parameters****torrent_hashes** (`str | Iterable[str] | None`) – single torrent hash or list of torrent hashes.
Or all for all torrents.

Return type`None`**torrents_trackers**(*torrent_hash=None*, ***kwargs*) → `TrackersList`Retrieve individual torrent's trackers. Tracker status is defined in `TrackerStatus`.**Raises**`NotFound404Error` –**Parameters**`torrent_hash`(`str` | `None`) – hash for torrent**Return type**`TrackersList`**torrents_upload_limit**(*torrent_hashes=None*, ***kwargs*) → `TorrentLimitsDictionary`

Retrieve the upload limit for one or more torrents.

Parameters`torrent_hashes`(`str` | `Iterable[str]` | `None`) – single torrent hash or list of torrent hashes.

Or all for all torrents.

Return type`TorrentLimitsDictionary`**torrents_webseeds**(*torrent_hash=None*, ***kwargs*) → `WebSeedsList`

Retrieve individual torrent's web seeds.

Raises`NotFound404Error` – torrent not found**Parameters**`torrent_hash`(`str` | `None`) – hash for torrent**Return type**`WebSeedsList`**class Torrents**(*client*) → `None`

Allows interaction with the Torrents API endpoints.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host="localhost:8080", username="admin", password=
    ↳ "adminadmin")
>>> # these are all the same attributes that are available as named in
    ↳ the
>>> # endpoints or the more pythonic names in Client (with or without
    ↳ 'torrents_' prepended)
>>> torrent_list = client.torrents.info()
>>> torrent_list_active = client.torrents.info.active()
>>> torrent_list_active_partial = client.torrents.info.active(limit=100,
    ↳ offset=200)
>>> torrent_list_downloading = client.torrents.info.downloading()
>>> # torrent looping
>>> for torrent in client.torrents.info.completed()
>>> # all torrents endpoints with a 'hashes' parameters support all_
    ↳ method to apply action to all torrents
>>> client.torrents.stop.all()
```

(continues on next page)

(continued from previous page)

```
>>> client.torrents.start.all()
>>> # or specify the individual hashes
>>> client.torrents.downloadLimit(torrent_hashes=["...", "..."])
```

add(urls=None, torrent_files=None, save_path=None, cookie=None, category=None, is_skip_checking=None, is_paused=None, is_root_folder=None, rename=None, upload_limit=None, download_limit=None, use_auto_torrent_management=None, is_sequential_download=None, is_first_last_piece_priority=None, tags=None, content_layout=None, ratio_limit=None, seeding_time_limit=None, download_path=None, use_download_path=None, stop_condition=None, add_to_top_of_queue=None, inactive_seeding_time_limit=None, share_limit_action=None, ssl_certificate=None, ssl_private_key=None, ssl_dh_params=None, is_stopped=None, **kwargs) → str
 Implements `torrents_add()`.

Return type`str`

add_trackers(torrent_hash=None, urls=None, **kwargs) → None

Implements `torrents_add_trackers()`.

Return type`None`

add_webseeds(torrent_hash=None, urls=None, **kwargs) → None

Implements `torrents_add_webseeds()`.

Return type`None`

count() → int

Implements `torrents_count()`.

Return type`int`

edit_tracker(torrent_hash=None, original_url=None, new_url=None, **kwargs) → None

Implements `torrents_edit_tracker()`.

Return type`None`

edit_webseed(torrent_hash=None, orig_url=None, new_url=None, **kwargs) → None

Implements `torrents_edit_webseed()`.

Return type`None`

export(torrent_hash=None, **kwargs) → bytes

Implements `torrents_export()`.

Return type`bytes`

file_priority(torrent_hash=None, file_ids=None, priority=None, **kwargs) → None

Implements `torrents_file_priority()`.

Return type`None`

files(torrent_hash=None, **kwargs) → TorrentFilesList

Implements `torrents_files()`.

Return type

TorrentFilesList

piece_hashes(torrent_hash=None, **kwargs) → TorrentPieceInfoList

Implements `torrents_piece_hashes()`.

Return type

TorrentPieceInfoList

piece_states(torrent_hash=None, **kwargs) → TorrentPieceInfoList

Implements `torrents_piece_states()`.

Return type

TorrentPieceInfoList

properties(torrent_hash=None, **kwargs) → TorrentPropertiesDictionary

Implements `torrents_properties()`.

Return type

TorrentPropertiesDictionary

remove_trackers(torrent_hash=None, urls=None, **kwargs) → None

Implements `torrents_remove_trackers()`.

Return type

None

remove_webseeds(torrent_hash=None, urls=None, **kwargs) → None

Implements `torrents_remove_webseeds()`.

Return type

None

rename(torrent_hash=None, new_torrent_name=None, **kwargs) → None

Implements `torrents_rename()`.

Return type

None

rename_file(torrent_hash=None, file_id=None, new_file_name=None, old_path=None, new_path=None, **kwargs) → None

Implements `torrents_rename_file()`.

Return type

None

rename_folder(torrent_hash=None, old_path=None, new_path=None, **kwargs) → None

Implements `torrents_rename_folder()`.

Return type

None

trackers(torrent_hash=None, **kwargs) → TrackersList

Implements `torrents_trackers()`.

Return type

TrackersList

webseeds(*torrent_hash=None*, ***kwargs*) → *WebSeedsList*

Implements *torrents_webseeds()*.

Return type

WebSeedsList

class TorrentDictionary(*data, client*) → *None*

Bases: *ClientCache[TorrentsAPIMixIn], ListEntry*

Item in *TorrentInfoList*. Allows interaction with individual torrents via the Torrents API endpoints.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host="localhost:8080", username="admin", password=
    >>>     "adminadmin")
>>> # these are all the same attributes that are available as named in
    >>> the
>>> # endpoints or the more pythonic names in Client (with or without
    >>>     'transfer_' prepended)
>>> torrent = client.torrents.info()[0]
>>> torrent_hash = torrent.info.hash
>>> # Attributes without inputs and a return value are properties
>>> properties = torrent.properties
>>> trackers = torrent.trackers
>>> files = torrent.files
>>> # Action methods
>>> torrent.edit_tracker(original_url="...", new_url="...")
>>> torrent.remove_trackers(urls="http://127.0.0.2/")
>>> torrent.rename(new_torrent_name="...")
>>> torrent.start()
>>> torrent.stop()
>>> torrent.recheck()
>>> torrent.torrents_top_priority()
>>> torrent.setLocation(location="/home/user/torrents/")
>>> torrent.setCategory(category="video")
```

add_tags(*tags=None*, ***kwargs*) → *None*

Implements *torrents_add_tags()*.

Return type

None

add_trackers(*urls=None*, ***kwargs*) → *None*

Implements *torrents_add_trackers()*.

Return type

None

add_webseeds(*urls*, ***kwargs*) → *None*

Implements *torrents_add_webseeds()*.

Return type

None

bottom_priority(***kwargs*) → *None*

Implements *torrents_bottom_priority()*.

Return type

None

decrease_priority(kwargs) → None**

Implements `torrents_decrease_priority()`.

Return type

None

delete(delete_files=None, **kwargs) → None

Implements `torrents_delete()`.

Return type

None

property download_limit: int

Implements `torrents_download_limit()`.

edit_tracker(orig_url=None, new_url=None, **kwargs) → None

Implements `torrents_edit_tracker()`.

Return type

None

edit_webseed(orig_url=None, new_url=None, **kwargs) → None

Implements `torrents_edit_webseed()`.

Return type

None

export(kwargs) → bytes**

Implements `torrents_export()`.

Return type

bytes

file_priority(file_ids=None, priority=None, **kwargs) → None

Implements `torrents_file_priority()`.

Return type

None

property files: TorrentFilesList

Implements `torrents_files()`.

increase_priority(kwargs) → None**

Implements `torrents_increase_priority()`.

Return type

None

property info: TorrentDictionary

Returns data from `torrents_info()` for the torrent.

pause(kwargs) → None**

Implements `torrents_stop()`.

Return type

None

```

property piece_hashes: TorrentPieceInfoList
    Implements torrents_piece_hashes().

property piece_states: TorrentPieceInfoList
    Implements torrents_piece_states().

property properties: TorrentPropertiesDictionary
    Implements torrents_properties().

reannounce(**kwargs) → None
    Implements torrents_reannounce().

    Return type
        None

recheck(**kwargs) → None
    Implements torrents_recheck().

    Return type
        None

remove_tags(tags=None, **kwargs) → None
    Implements torrents_remove_tags().

    Return type
        None

remove_trackers(urls=None, **kwargs) → None
    Implements torrents_remove_trackers().

    Return type
        None

remove_webseeds(urls=None, **kwargs) → None
    Implements torrents_remove_webseeds().

    Return type
        None

rename(new_name=None, **kwargs) → None
    Implements torrents_rename().

    Return type
        None

rename_file(file_id=None, new_file_name=None, old_path=None, new_path=None, **kwargs) → None
    Implements torrents_rename_file().

    Return type
        None

rename_folder(old_path=None, new_path=None, **kwargs) → None
    Implements torrents_rename_folder().

    Return type
        None

resume(**kwargs) → None
    Implements torrents_start().

```

Return type

None

`set_auto_management(enable=None, **kwargs) → None`

Implements `torrents_set_auto_management()`.

Return type

None

`set_category(category=None, **kwargs) → None`

Implements `torrents_set_category()`.

Return type

None

`set_download_limit(limit=None, **kwargs) → None`

Implements `torrents_set_download_limit()`.

Return type

None

`set_download_path(download_path=None, **kwargs) → None`

Implements `torrents_set_download_path()`.

Return type

None

`set_force_start(enable=None, **kwargs) → None`

Implements `torrents_set_force_start()`.

Return type

None

`set_location(location=None, **kwargs) → None`

Implements `torrents_set_location()`.

Return type

None

`set_save_path(save_path=None, **kwargs) → None`

Implements `torrents_set_save_path()`.

Return type

None

`set_share_limits(ratio_limit=None, seeding_time_limit=None, inactive_seeding_time_limit=None, **kwargs) → None`

Implements `torrents_set_share_limits()`.

Return type

None

`set_super_seeding(enable=None, **kwargs) → None`

Implements `torrents_set_super_seeding()`.

Return type

None

`set_tags(tags=None, **kwargs) → None`

Implements `torrents_set_tags()`.

Return type
None

set_upload_limit(*limit=None, **kwargs*) → None
Implements `torrents_set_upload_limit()`.

Return type
None

start(***kwargs*) → None
Implements `torrents_start()`.

Return type
None

property state_enum: `TorrentState`
Torrent state enum.

stop(***kwargs*) → None
Implements `torrents_stop()`.

Return type
None

sync_local() → None
Update local cache of torrent info.

Return type
None

toggle_first_last_piece_priority(***kwargs*) → None
Implements `torrents_toggle_first_last_piece_priority()`.

Return type
None

toggle_sequential_download(***kwargs*) → None
Implements `torrents_toggle_sequential_download()`.

Return type
None

top_priority(***kwargs*) → None
Implements `torrents_top_priority()`.

Return type
None

property trackers: `TrackersList`
Implements `torrents_trackers()`.

property upload_limit: `int`
Implements `torrents_upload_limit()`.

property webseeds: `WebSeedsList`
Implements `torrents_webseeds()`.

class TorrentCategories(*args, *client, **kwargs*)
Bases: `ClientCache[TorrentsAPIMixIn]`
Allows interaction with torrent categories within the Torrents API endpoints.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host="localhost:8080", username="admin", password=
    >>>     "adminadmin")
>>> # these are all the same attributes that are available as named in
    >>> the
>>> # endpoints or the more pythonic names in Client (with or without
    >>>     'torrents_' prepended)
>>> categories = client.torrent_categories.categories
>>> # create or edit categories
>>> client.torrent_categories.create_category(name="Video", save_path="/
    >>>     home/user/torrents/Video")
>>> client.torrent_categories.edit_category(name="Video", save_path="/
    >>>     data/torrents/Video")
>>> # edit or create new by assignment
>>> client.torrent_categories.categories = dict(name="Video", save_path=
    >>>     "/home/user/")
>>> # delete categories
>>> client.torrent_categories.removeCategories(categories="Video")
>>> client.torrent_categories.removeCategories(categories=["Audio",
    >>>     "ISOS"])
```

property categories: TorrentCategoriesDictionary

Implements `torrents_categories()`.

create_category(name=None, save_path=None, download_path=None, enable_download_path=None, **kwargs) → None

Implements `torrents_create_category()`.

Return type

`None`

edit_category(name=None, save_path=None, download_path=None, enable_download_path=None, **kwargs) → None

Implements `torrents_edit_category()`.

Return type

`None`

remove_categories(categories=None, **kwargs) → None

Implements `torrents_remove_categories()`.

Return type

`None`

class TorrentTags(*args, client, **kwargs)

Bases: `ClientCache[TorrentsAPIMixIn]`

Allows interaction with torrent tags within the “Torrent” API endpoints.

Usage:

```
>>> from qbittorrentapi import Client
>>> client = Client(host="localhost:8080", username="admin", password=
    >>>     "adminadmin")
>>> tags = client.torrent_tags.tags
```

(continues on next page)

(continued from previous page)

```
>>> client.torrent_tags.tags = "tv show" # create category
>>> client.torrent_tags.create_tags(tags=["tv show", "linux distro"])
>>> client.torrent_tags.delete_tags(tags="tv show")
```

add_tags(tags=None, torrent_hashes=None, **kwargs) → NoneImplements `torrents_add_tags()`.**Return type**

None

create_tags(tags=None, **kwargs) → NoneImplements `torrents_create_tags()`.**Return type**

None

delete_tags(tags=None, **kwargs) → NoneImplements `torrents_delete_tags()`.**Return type**

None

remove_tags(tags=None, torrent_hashes=None, **kwargs) → NoneImplements `torrents_remove_tags()`.**Return type**

None

set_tags(tags=None, torrent_hashes=None, **kwargs) → NoneImplements `torrents_set_tags()`.**Return type**

None

property tags: TagListImplements `torrents_tags()`.**class TorrentPropertiesDictionary**(data=None, **kwargs)Bases: `Dictionary[None | int | str | bool | Sequence[JsonValueT] | Mapping[str, JsonValueT]]`Response to `torrents_properties()`Definition: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1))
`#user-content-get-torrent-generic-properties`**class TorrentLimitsDictionary**(data=None, **kwargs)Bases: `Dictionary[None | int | str | bool | Sequence[JsonValueT] | Mapping[str, JsonValueT]]`Response to `torrents_download_limit()`**class TorrentCategoriesDictionary**(data=None, **kwargs)Bases: `Dictionary[None | int | str | bool | Sequence[JsonValueT] | Mapping[str, JsonValueT]]`Response to `torrents_categories()`**class TorrentsAddPeersDictionary**(data=None, **kwargs)Bases: `Dictionary[None | int | str | bool | Sequence[JsonValueT] | Mapping[str, JsonValueT]]`Response to `torrents_add_peers()`

```
class TorrentFilesList(list_entries, client=None)
Bases: List[TorrentFile]
Response to torrents_files()
Definition: https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)
#user-content-get-torrent-contents

class TorrentFile(data=None, **kwargs)
Bases: ListEntry
Item in TorrentFilesList

class WebSeedsList(list_entries, client=None)
Bases: List[WebSeed]
Response to torrents_webseeds()
Definition: https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)
#user-content-get-torrent-web-seeds

class WebSeed(data=None, **kwargs)
Bases: ListEntry
Item in WebSeedsList

class TrackersList(list_entries, client=None)
Bases: List[Tracker]
Response to torrents_trackers()
Definition: https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)
#user-content-get-torrent-trackers

class Tracker(data=None, **kwargs)
Bases: ListEntry
Item in TrackersList

class TorrentInfoList(list_entries, client=None)
Bases: List[TorrentDictionary]
Response to torrents_info()
Definition: https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)
#user-content-get-torrent-list

class TorrentPieceInfoList(list_entries, client=None)
Bases: List[TorrentPieceData]
Response to torrents_piece_states() and torrents_piece_hashes()

class TorrentPieceData(data=None, **kwargs)
Bases: ListEntry
Item in TorrentPieceInfoList

class TagList(list_entries, client=None)
Bases: List[Tag]
Response to torrents_tags()
```

```
class Tag(data=None, **kwargs)
```

Bases: *ListEntry*

Item in *TagList*

Transfer

```
class TransferAPIMixIn(host=None, port=None, username=None, password=None,  

    EXTRA_HEADERS=None, REQUESTS_ARGS=None, HTTPADAPTER_ARGS=None,  

    VERIFY_WEBUI_CERTIFICATE=True, FORCE_SCHEME_FROM_HOST=False,  

    RAISE_NOTIMPLEMENTEDERROR_FOR_UNIMPLEMENTED_API_ENDPOINTS=False,  

    RAISE_ERROR_FOR_UNSUPPORTED_QBITTORRENT_VERSIONS=False,  

    VERBOSE_RESPONSE_LOGGING=False, SIMPLE_RESPONSES=False,  

    DISABLE_LOGGING_DEBUG_OUTPUT=False) → None
```

Bases: *AppAPIMixIn*

Implementation of all Transfer API methods.

Usage

```
>>> from qbittorrentapi import Client  
>>> client = Client(host="localhost:8080", username="admin", password=  
    → "adminadmin")  
>>> transfer_info = client.transfer_info()  
>>> client.transfer_set_download_limit(limit=1024000)
```

transfer_ban_peers(*peers=None*, ***kwargs*) → *None*

Ban one or more peers.

This method was introduced with qBittorrent v4.2.0 (Web API v2.3.0).

Parameters

peers (*str* | *Iterable[str]* | *None*) – one or more peers to ban. each peer should take the form ‘host:port’

Return type

None

transfer_download_limit(***kwargs*) → *int*

Retrieves download limit; 0 is unlimited.

Return type

int

transfer_info(***kwargs*) → *TransferInfoDictionary*

Retrieves the global transfer info found in qBittorrent status bar.

Return type

TransferInfoDictionary

transfer_setSpeedLimitsMode(*intended_state=None*, ***kwargs*) → *None*

Sets whether alternative speed limits are enabled.

Parameters

intended_state (*bool* | *None*) – True to enable alt speed and False to disable. Leaving None will toggle the current state.

Return type

None

transfer_set_download_limit(*limit=None*, ***kwargs*) → *None*

Set the global download limit in bytes/second.

Parameters

limit (*str* | *int* | *None*) – download limit in bytes/second (0 or -1 for no limit)

Return type

None

transfer_set_speed_limits_mode(*intended_state=None*, ***kwargs*) → *None*

Sets whether alternative speed limits are enabled.

Parameters

intended_state (*bool* | *None*) – True to enable alt speed and False to disable. Leaving *None* will toggle the current state.

Return type

None

transfer_set_upload_limit(*limit=None*, ***kwargs*) → *None*

Set the global upload limit in bytes/second.

Parameters

limit (*str* | *int* | *None*) – upload limit in bytes/second (0 or -1 for no limit)

Return type

None

transfer_speed_limits_mode(***kwargs*) → *str*

Returns 1 if alternative speed limits are currently enabled, 0 otherwise.

Return type

str

transfer_toggle_speed_limits_mode(*intended_state=None*, ***kwargs*) → *None*

Sets whether alternative speed limits are enabled.

Parameters

intended_state (*bool* | *None*) – True to enable alt speed and False to disable. Leaving *None* will toggle the current state.

Return type

None

transfer_upload_limit(***kwargs*) → *int*

Retrieves upload limit; 0 is unlimited.

Return type

int

class Transfer(*args, client, **kwargs)

Allows interaction with the Transfer API endpoints.

Usage

```
>>> from qbittorrentapi import Client
>>> client = Client(host="localhost:8080", username="admin", password=
    "adminadmin")
>>> # these are all the same attributes that are available as named in
    the
```

(continues on next page)

(continued from previous page)

```
>>> # endpoints or the more pythonic names in Client (with or without
   ↵'transfer_' prepended)
>>> transfer_info = client.transfer.info
>>> # access and set download/upload limits as attributes
>>> dl_limit = client.transfer.download_limit
>>> # this updates qBittorrent in real-time
>>> client.transfer.download_limit = 1024000
>>> # update speed limits mode to alternate or not
>>> client.transfer.speedLimitsMode = True
```

ban_peers(*peers=None, **kwargs*) → NoneImplements `transfer_ban_peers()`.**Return type**

None

property download_limit: intImplements `transfer_download_limit()`.**property info: TransferInfoDictionary**Implements `transfer_info()`.**set_download_limit**(*limit=None, **kwargs*) → NoneImplements `transfer_set_download_limit()`.**Return type**

None

set_speed_limits_mode(*intended_state=None, **kwargs*) → NoneImplements `transfer_set_speed_limits_mode()`.**Return type**

None

set_upload_limit(*limit=None, **kwargs*) → NoneImplements `transfer_set_upload_limit()`.**Return type**

None

property speed_limits_mode: strImplements `transfer_speed_limits_mode()`.**toggle_speed_limits_mode**(*intended_state=None, **kwargs*) → NoneImplements `transfer_set_speed_limits_mode()`.**Return type**

None

property upload_limit: intImplements `transfer_upload_limit()`.**class TransferInfoDictionary**(*data=None, **kwargs*)Bases: `Dictionary[None | int | str | bool | Sequence[JsonValueT] | Mapping[str, JsonValueT]]`Response to `transfer_info()`Definition: [https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)
#user-content-get-global-transfer-info](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#user-content-get-global-transfer-info)

Version

class Version

Allows introspection for whether this Client supports different versions of the qBittorrent application and its Web API.

Note that if a version is not listed as “supported” here, many (if not all) methods are likely to function properly since the Web API is largely backwards and forward compatible... albeit with some notable exceptions.

classmethod `is_api_version_supported(api_version)` → `bool`

Returns whether a version of the qBittorrent Web API is fully supported by this API client.

Parameters

`api_version (str)` – version of qBittorrent Web API version such as `2.8.4`

Return type

`bool`

Returns

True or False for whether version is supported

classmethod `is_app_version_supported(app_version)` → `bool`

Returns whether a version of the qBittorrent application is fully supported by this API client.

Parameters

`app_version (str)` – version of qBittorrent application such as `v4.4.0`

Return type

`bool`

Returns

True or False for whether version is supported

classmethod `latest_supported_api_version()` → `str`

Returns the most recent version of qBittorrent Web API that is supported.

Return type

`str`

classmethod `latest_supported_app_version()` → `str`

Returns the most recent version of qBittorrent that is supported.

Return type

`str`

classmethod `supported_api_versions()` → `set[str]`

Set of all supported qBittorrent Web API versions.

Return type

`set[str]`

classmethod `supported_app_versions()` → `set[str]`

Set of all supported qBittorrent application versions.

Return type

`set[str]`

PYTHON MODULE INDEX

Q

`qbittorrentapi.definitions`, 19
`qbittorrentapi.exceptions`, 9
`qbittorrentapi.request`, 25

INDEX

Symbols

`__call__()` (*Log.Main method*), 24
`__call__()` (*RSS.Items method*), 34
`__call__()` (*Sync.MainData method*), 42
`__call__()` (*Sync.TorrentPeers method*), 43
`_auth_request()` (*Request method*), 27
`_cast()` (*Request method*), 27
`_format_payload()` (*Request static method*), 27
`_get()` (*Request method*), 28
`_get_cast()` (*Request method*), 28
`_handle_error_responses()` (*Request static method*), 28
`_initialize_context()` (*Request method*), 28
`_initialize_settings()` (*Request method*), 28
`_is_endpoint_supported_for_version()` (*Request method*), 29
`_list2string()` (*Request class method*), 29
`_post()` (*Request method*), 29
`_post_cast()` (*Request method*), 29
`_request()` (*Request method*), 30
`_request_manager()` (*Request method*), 30
`_session` (*Request property*), 30
`_trigger_session_initialization()` (*Request method*), 30
`_verbose_logging()` (*Request method*), 30

A

`add()` (*Torrents method*), 63
`add_feed()` (*RSS method*), 34
`add_folder()` (*RSS method*), 34
`add_tags()` (*TorrentDictionary method*), 65
`add_tags()` (*TorrentTags method*), 71
`add_task()` (*TorrentCreator method*), 46
`add_trackers()` (*TorrentDictionary method*), 65
`add_trackers()` (*Torrents method*), 63
`add_webseeds()` (*TorrentDictionary method*), 65
`add_webseeds()` (*Torrents method*), 63
`ALLOCATING` (*TorrentState attribute*), 21
`APIConnectionError`, 9
`APIError`, 9
`APIKwargsT` (*in module qbittorrentapi.definitions*), 19
`APINames` (*class in qbittorrentapi.definitions*), 19

`app_build_info()` (*AppAPIMixIn method*), 12
`app_cookies()` (*AppAPIMixIn method*), 12
`app_default_save_path()` (*AppAPIMixIn method*), 12
`app_get_directory_content()` (*AppAPIMixIn method*), 12
`app_network_interface_address_list()` (*AppAPIMixIn method*), 12
`app_network_interface_list()` (*AppAPIMixIn method*), 13
`app_preferences()` (*AppAPIMixIn method*), 13
`app_send_test_email()` (*AppAPIMixIn method*), 13
`app_set_cookies()` (*AppAPIMixIn method*), 13
`app_set_preferences()` (*AppAPIMixIn method*), 13
`app_shutdown()` (*AppAPIMixIn method*), 13
`app_version()` (*AppAPIMixIn method*), 14
`app_web_api_version()` (*AppAPIMixIn method*), 14
`AppAPIMixIn` (*class in qbittorrentapi.app*), 12
`Application` (*APINames attribute*), 19
`Application` (*class in qbittorrentapi.app*), 14
`ApplicationPreferencesDictionary` (*class in qbittorrentapi.app*), 15
`Attr` (*class in qbittorrentapi._attrdict*), 16
`AttrDict` (*class in qbittorrentapi._attrdict*), 16
`auth_log_in()` (*AuthAPIMixIn method*), 17
`auth_log_out()` (*AuthAPIMixIn method*), 17
`AuthAPIMixIn` (*class in qbittorrentapi.auth*), 17
`Authorization` (*APINames attribute*), 19
`Authorization` (*class in qbittorrentapi.auth*), 17

B

`ban_peers()` (*Transfer method*), 75
`bottom_priority()` (*TorrentDictionary method*), 65
`build()` (*QbittorrentURL method*), 26
`build_base_url()` (*QbittorrentURL method*), 26
`build_info` (*Application property*), 14
`BuildInfoDictionary` (*class in qbittorrentapi.app*), 15

C

`categories` (*TorrentCategories property*), 70
`categories()` (*Search method*), 39
`CHECKING_DOWNLOAD` (*TorrentState attribute*), 21

CHECKING_RESUME_DATA (*TorrentState attribute*), 21
CHECKING_UPLOAD (*TorrentState attribute*), 21
Client (*class in qbittorrentapi.client*), 18
ClientCache (*class in qbittorrentapi.definitions*), 20
ClientT (*class in qbittorrentapi.definitions*), 20
Conflict409Error, 11
Cookie (*class in qbittorrentapi.app*), 15
CookieList (*class in qbittorrentapi.app*), 16
cookies (*Application property*), 14
count () (*Torrents method*), 63
create_category () (*TorrentCategories method*), 70
create_tags () (*TorrentTags method*), 71
critical () (*Log.Main method*), 24

D

decrease_priority () (*TorrentDictionary method*), 66
default_save_path (*Application property*), 14
delete () (*Search method*), 39
delete () (*SearchJobDictionary method*), 40
delete () (*TorrentCreatorTaskDictionary method*), 46
delete () (*TorrentDictionary method*), 66
delete_tags () (*TorrentTags method*), 71
delete_task () (*TorrentCreator method*), 46
delta () (*Sync.MainData method*), 42
delta () (*Sync.TorrentPeers method*), 43
detect_scheme () (*QbittorrentURL method*), 27
Dictionary (*class in qbittorrentapi.definitions*), 20
DirectoryContentList (*class in qbittorrentapi.app*), 15
DISABLED (*TrackerStatus attribute*), 22
display (*TrackerStatus property*), 23
download_limit (*TorrentDictionary property*), 66
download_limit (*Transfer property*), 75
download_torrent () (*Search method*), 39
DOWNLOADING (*TorrentState attribute*), 21

E

edit_category () (*TorrentCategories method*), 70
edit_tracker () (*TorrentDictionary method*), 66
edit_tracker () (*Torrents method*), 63
edit_webseed () (*TorrentDictionary method*), 66
edit_webseed () (*Torrents method*), 63
EMPTY (*APINames attribute*), 19
enable_plugin () (*Search method*), 39
ERROR (*TorrentState attribute*), 21
export () (*TorrentDictionary method*), 66
export () (*Torrents method*), 63

F

FAILED (*TaskStatus attribute*), 47
file_priority () (*TorrentDictionary method*), 66
file_priority () (*Torrents method*), 63
FileError, 9
files (*TorrentDictionary property*), 66

files () (*Torrents method*), 63
FileToSendT (*in module qbittorrentapi.definitions*), 20
FINISHED (*TaskStatus attribute*), 47
Forbidden403Error, 11
FORCED_DOWNLOAD (*TorrentState attribute*), 21
FORCED_METADATA_DOWNLOAD (*TorrentState attribute*), 21
FORCED_UPLOAD (*TorrentState attribute*), 21

G

get_directory_content () (*Application method*), 14

H

HTTP400Error, 10
HTTP401Error, 10
HTTP403Error, 10
HTTP404Error, 10
HTTP405Error, 10
HTTP409Error, 10
HTTP415Error, 11
HTTP4XXError, 10
HTTP500Error, 11
HTTP5XXError, 10
http_status_code (*HTTP400Error attribute*), 10
http_status_code (*HTTP401Error attribute*), 10
http_status_code (*HTTP403Error attribute*), 10
http_status_code (*HTTP404Error attribute*), 10
http_status_code (*HTTP405Error attribute*), 10
http_status_code (*HTTP409Error attribute*), 10
http_status_code (*HTTP415Error attribute*), 11
http_status_code (*HTTP500Error attribute*), 11
http_status_code (*HTTPError attribute*), 10
HTTPError, 10

I

increase_priority () (*TorrentDictionary method*), 66
info (*TorrentDictionary property*), 66
info (*Transfer property*), 75
info () (*Log.Main method*), 24
install_plugin () (*Search method*), 39
InternalServerError500Error, 11
InvalidRequest400Error, 11
is_api_version_supported () (*Version class method*), 76
is_app_version_supported () (*Version class method*), 76
is_checking (*TorrentState property*), 22
is_complete (*TorrentState property*), 22
is_downloading (*TorrentState property*), 22
is_errorred (*TorrentState property*), 22
is_logged_in (*AuthAPIMixIn property*), 17
is_logged_in (*Authorization property*), 18
is_paused (*TorrentState property*), 22
is_stopped (*TorrentState property*), 22

`is_uploading` (*TorrentState property*), 22
`items` (*RSS property*), 34

J

`JsonValueT` (*in module qbittorrentapi.definitions*), 20

L

`latest_supported_api_version()` (*Version class method*), 76
`latest_supported_app_version()` (*Version class method*), 76
`List` (*class in qbittorrentapi.definitions*), 20
`ListEntry` (*class in qbittorrentapi.definitions*), 20
`ListEntryT` (*class in qbittorrentapi.definitions*), 20
`ListInputT` (*in module qbittorrentapi.definitions*), 20
`Log` (*APINames attribute*), 19
`Log` (*class in qbittorrentapi.log*), 24
`Log.Main` (*class in qbittorrentapi.log*), 24
`log_in()` (*Authorization method*), 18
`log_main()` (*LogAPIMixIn method*), 23
`log_out()` (*Authorization method*), 18
`log_peers()` (*LogAPIMixIn method*), 23
`LogAPIMixIn` (*class in qbittorrentapi.log*), 23
`LogEntry` (*class in qbittorrentapi.log*), 25
`LoginFailed`, 9
`LogMainList` (*class in qbittorrentapi.log*), 25
`LogPeer` (*class in qbittorrentapi.log*), 25
`LogPeersList` (*class in qbittorrentapi.log*), 24

M

`main` (*Log property*), 24
`maindata` (*Sync property*), 43
`mark_as_read()` (*RSS method*), 34
`matching_articles()` (*RSS method*), 35
`METADATA_DOWNLOAD` (*TorrentState attribute*), 21
`MethodNotAllowed405Error`, 11
`MISSING_FILES` (*TorrentState attribute*), 21
`MissingRequiredParameters400Error`, 11
`module`
 `qbittorrentapi.definitions`, 19
 `qbittorrentapi.exceptions`, 9
 `qbittorrentapi.request`, 25
`move_item()` (*RSS method*), 35
`MOVING` (*TorrentState attribute*), 21
`MutableAttr` (*class in qbittorrentapi._attrdict*), 16

N

`network_interface_address_list()` (*Application method*), 14
`network_interface_list` (*Application property*), 15
`NetworkInterface` (*class in qbittorrentapi.app*), 16
`NetworkInterfaceAddressList` (*class in qbittorrentapi.app*), 16

`NetworkInterfaceList` (*class in qbittorrentapi.app*), 16
`normal()` (*Log.Main method*), 24
`NOT_CONTACTED` (*TrackerStatus attribute*), 23
`NOT_WORKING` (*TrackerStatus attribute*), 23
`NotFound404Error`, 11

P

`pause()` (*TorrentDictionary method*), 66
`PAUSED_DOWNLOAD` (*TorrentState attribute*), 21
`PAUSED_UPLOAD` (*TorrentState attribute*), 21
`peers()` (*Log method*), 24
`piece_hashes` (*TorrentDictionary property*), 66
`piece_hashes()` (*Torrents method*), 64
`piece_states` (*TorrentDictionary property*), 67
`piece_states()` (*Torrents method*), 64
`plugins` (*Search property*), 39
`preferences` (*Application property*), 15
`properties` (*TorrentDictionary property*), 67
`properties()` (*Torrents method*), 64

Q

`qbittorrentapi.definitions`
 `module`, 19
`qbittorrentapi.exceptions`
 `module`, 9
`qbittorrentapi.request`
 `module`, 25
`QbittorrentSession` (*class in qbittorrentapi.request*), 25
`QbittorrentURL` (*class in qbittorrentapi.request*), 26
`QUEUED` (*TaskStatus attribute*), 47
`QUEUED_DOWNLOAD` (*TorrentState attribute*), 21
`QUEUED_UPLOAD` (*TorrentState attribute*), 21

R

`reannounce()` (*TorrentDictionary method*), 67
`recheck()` (*TorrentDictionary method*), 67
`refresh_item()` (*RSS method*), 35
`remove_categories()` (*TorrentCategories method*), 70
`remove_item()` (*RSS method*), 35
`remove_rule()` (*RSS method*), 35
`remove_tags()` (*TorrentDictionary method*), 67
`remove_tags()` (*TorrentTags method*), 71
`remove_trackers()` (*TorrentDictionary method*), 67
`remove_trackers()` (*Torrents method*), 64
`remove_webseeds()` (*TorrentDictionary method*), 67
`remove_webseeds()` (*Torrents method*), 64
`rename()` (*TorrentDictionary method*), 67
`rename()` (*Torrents method*), 64
`rename_file()` (*TorrentDictionary method*), 67
`rename_file()` (*Torrents method*), 64
`rename_folder()` (*TorrentDictionary method*), 67
`rename_folder()` (*Torrents method*), 64

rename_rule() (*RSS method*), 35
Request (*class in qbittorrentapi.request*), 27
request() (*QbittorrentSession method*), 25
reset_rid() (*Sync.MainData method*), 43
reset_rid() (*Sync.TorrentPeers method*), 43
results() (*Search method*), 39
results() (*SearchJobDictionary method*), 40
resume() (*TorrentDictionary method*), 67
RSS (*APINames attribute*), 19
RSS (*class in qbittorrentapi.rss*), 34
RSS.Items (*class in qbittorrentapi.rss*), 34
rss_add_feed() (*RSSAPIMixIn method*), 31
rss_add_folder() (*RSSAPIMixIn method*), 31
rss_items() (*RSSAPIMixIn method*), 31
rss_mark_as_read() (*RSSAPIMixIn method*), 32
rss_matching_articles() (*RSSAPIMixIn method*), 32
rss_move_item() (*RSSAPIMixIn method*), 32
rss_refresh_item() (*RSSAPIMixIn method*), 32
rss_remove_item() (*RSSAPIMixIn method*), 32
rss_remove_rule() (*RSSAPIMixIn method*), 33
rss_rename_rule() (*RSSAPIMixIn method*), 33
rss_rules() (*RSSAPIMixIn method*), 33
rss_set_feed_url() (*RSSAPIMixIn method*), 33
rss_set_rule() (*RSSAPIMixIn method*), 33
RSSAPIMixIn (*class in qbittorrentapi.rss*), 31
RSSItemsDictionary (*class in qbittorrentapi.rss*), 35
RSSRulesDictionary (*class in qbittorrentapi.rss*), 35
rules (*RSS property*), 35
RUNNING (*TaskStatus attribute*), 47

S

Search (*APINames attribute*), 19
Search (*class in qbittorrentapi.search*), 39
search_categories() (*SearchAPIMixIn method*), 36
search_delete() (*SearchAPIMixIn method*), 36
search_download_torrent() (*SearchAPIMixIn method*), 36
search_enable_plugin() (*SearchAPIMixIn method*), 37
search_install_plugin() (*SearchAPIMixIn method*), 37
search_plugins() (*SearchAPIMixIn method*), 37
search_results() (*SearchAPIMixIn method*), 37
search_start() (*SearchAPIMixIn method*), 37
search_status() (*SearchAPIMixIn method*), 38
search_stop() (*SearchAPIMixIn method*), 38
search_uninstall_plugin() (*SearchAPIMixIn method*), 38
search_update_plugins() (*SearchAPIMixIn method*), 38
SearchAPIMixIn (*class in qbittorrentapi.search*), 36
SearchCategoriesList (*class in qbittorrentapi.search*), 41

SearchCategory (*class in qbittorrentapi.search*), 41
SearchJobDictionary (*class in qbittorrentapi.search*), 40
SearchPlugin (*class in qbittorrentapi.search*), 41
SearchPluginsList (*class in qbittorrentapi.search*), 41
SearchResultsDictionary (*class in qbittorrentapi.search*), 41
SearchStatus (*class in qbittorrentapi.search*), 41
SearchStatusesList (*class in qbittorrentapi.search*), 41
send_test_email() (*Application method*), 15
set_auto_management() (*TorrentDictionary method*), 68
set_category() (*TorrentDictionary method*), 68
set_cookies() (*Application method*), 15
set_download_limit() (*TorrentDictionary method*), 68
set_download_limit() (*Transfer method*), 75
set_download_path() (*TorrentDictionary method*), 68
set_feed_url() (*RSS method*), 35
set_force_start() (*TorrentDictionary method*), 68
set_location() (*TorrentDictionary method*), 68
set_preferences() (*Application method*), 15
set_rule() (*RSS method*), 35
set_save_path() (*TorrentDictionary method*), 68
set_share_limits() (*TorrentDictionary method*), 68
set_speed_limits_mode() (*Transfer method*), 75
set_super_seeding() (*TorrentDictionary method*), 68
set_tags() (*TorrentDictionary method*), 68
set_tags() (*TorrentTags method*), 71
set_upload_limit() (*TorrentDictionary method*), 69
set_upload_limit() (*Transfer method*), 75
shutdown() (*Application method*), 15
speed_limits_mode (*Transfer property*), 75
STALLED_DOWNLOAD (*TorrentState attribute*), 22
STALLED_UPLOAD (*TorrentState attribute*), 22
start() (*Search method*), 40
start() (*TorrentDictionary method*), 69
state_enum (*TorrentDictionary property*), 69
status() (*Search method*), 40
status() (*SearchJobDictionary method*), 40
status() (*TorrentCreator method*), 46
status() (*TorrentCreatorTaskDictionary method*), 46
stop() (*Search method*), 40
stop() (*SearchJobDictionary method*), 40
stop() (*TorrentDictionary method*), 69
STOPPED_DOWNLOAD (*TorrentState attribute*), 22
STOPPED_UPLOAD (*TorrentState attribute*), 22
supported_api_versions() (*Version class method*), 76
supported_app_versions() (*Version class method*), 76
Sync (*APINames attribute*), 20
Sync (*class in qbittorrentapi.sync*), 42

`Sync.MainData` (*class in qbittorrentapi.sync*), 42
`Sync.TorrentPeers` (*class in qbittorrentapi.sync*), 43
`sync_local()` (*TorrentDictionary method*), 69
`sync_maindata()` (*SyncAPIMixIn method*), 42
`sync_torrent_peers()` (*SyncAPIMixIn method*), 42
`SyncAPIMixIn` (*class in qbittorrentapi.sync*), 41
`SyncMainDataDictionary` (*class in qbittorrentapi.sync*), 43
`SyncTorrentPeersDictionary` (*class in qbittorrentapi.sync*), 43

T

`Tag` (*class in qbittorrentapi.torrents*), 72
`TagList` (*class in qbittorrentapi.torrents*), 72
`tags` (*TorrentTags property*), 71
`TaskStatus` (*class in qbittorrentapi.torrentcreator*), 47
`toggle_first_last_piece_priority()` (*TorrentDictionary method*), 69
`toggle_sequential_download()` (*TorrentDictionary method*), 69
`toggle_speed_limits_mode()` (*Transfer method*), 75
`top_priority()` (*TorrentDictionary method*), 69
`torrent_file()` (*TorrentCreator method*), 46
`torrent_file()` (*TorrentCreatorTaskDictionary method*), 46
`torrent_peers` (*Sync property*), 43
`TorrentCategories` (*class in qbittorrentapi.torrents*), 69
`TorrentCategoriesDictionary` (*class in qbittorrentapi.torrents*), 71
`TorrentCreator` (*APINames attribute*), 20
`TorrentCreator` (*class in qbittorrentapi.torrentcreator*), 45
`torrentcreator_add_task()` (*TorrentCreatorAPIMixIn method*), 44
`torrentcreator_delete_task()` (*TorrentCreatorAPIMixIn method*), 45
`torrentcreator_status()` (*TorrentCreatorAPIMixIn method*), 45
`torrentcreator_torrent_file()` (*TorrentCreatorAPIMixIn method*), 45
`TorrentCreatorAPIMixIn` (*class in qbittorrentapi.torrentcreator*), 43
`TorrentCreatorTaskDictionary` (*class in qbittorrentapi.torrentcreator*), 46
`TorrentCreatorTaskStatus` (*class in qbittorrentapi.torrentcreator*), 46
`TorrentCreatorTaskStatusList` (*class in qbittorrentapi.torrentcreator*), 47
`TorrentDictionary` (*class in qbittorrentapi.torrents*), 65
`TorrentFile` (*class in qbittorrentapi.torrents*), 72
`TorrentFileError`, 9
`TorrentFileNotFoundException`, 9

`TorrentFilePermissionError`, 9
`TorrentFilesList` (*class in qbittorrentapi.torrents*), 71
`TorrentInfoList` (*class in qbittorrentapi.torrents*), 72
`TorrentLimitsDictionary` (*class in qbittorrentapi.torrents*), 71
`torrentPeers` (*Sync property*), 43
`TorrentPieceData` (*class in qbittorrentapi.torrents*), 72
`TorrentPieceInfoList` (*class in qbittorrentapi.torrents*), 72
`TorrentPropertiesDictionary` (*class in qbittorrentapi.torrents*), 71
`Torrents` (*APINames attribute*), 20
`Torrents` (*class in qbittorrentapi.torrents*), 62
`torrents_add()` (*TorrentsAPIMixIn method*), 47
`torrents_add_peers()` (*TorrentsAPIMixIn method*), 49
`torrents_add_tags()` (*TorrentsAPIMixIn method*), 49
`torrents_add_trackers()` (*TorrentsAPIMixIn method*), 50
`torrents_add_webseeds()` (*TorrentsAPIMixIn method*), 50
`torrents_bottom_priority()` (*TorrentsAPIMixIn method*), 50
`torrents_categories()` (*TorrentsAPIMixIn method*), 50
`torrents_count()` (*TorrentsAPIMixIn method*), 50
`torrents_create_category()` (*TorrentsAPIMixIn method*), 51
`torrents_create_tags()` (*TorrentsAPIMixIn method*), 51
`torrents_decrease_priority()` (*TorrentsAPIMixIn method*), 51
`torrents_delete()` (*TorrentsAPIMixIn method*), 51
`torrents_delete_tags()` (*TorrentsAPIMixIn method*), 51
`torrents_download_limit()` (*TorrentsAPIMixIn method*), 52
`torrents_edit_category()` (*TorrentsAPIMixIn method*), 52
`torrents_edit_tracker()` (*TorrentsAPIMixIn method*), 52
`torrents_edit_webseed()` (*TorrentsAPIMixIn method*), 52
`torrents_export()` (*TorrentsAPIMixIn method*), 53
`torrents_file_priority()` (*TorrentsAPIMixIn method*), 53
`torrents_files()` (*TorrentsAPIMixIn method*), 53
`torrents_increase_priority()` (*TorrentsAPIMixIn method*), 54
`torrents_info()` (*TorrentsAPIMixIn method*), 54
`torrents_pause()` (*TorrentsAPIMixIn method*), 55
`torrents_piece_hashes()` (*TorrentsAPIMixIn method*), 55
`torrents_piece_states()` (*TorrentsAPIMixIn*

method), 55
torrents_properties() (*TorrentsAPIMixIn method*), 55
torrents_reannounce() (*TorrentsAPIMixIn method*), 55
torrents_recheck() (*TorrentsAPIMixIn method*), 55
torrents_remove_categories() (*TorrentsAPIMixIn method*), 56
torrents_remove_tags() (*TorrentsAPIMixIn method*), 56
torrents_remove_trackers() (*TorrentsAPIMixIn method*), 56
torrents_remove_webseeds() (*TorrentsAPIMixIn method*), 56
torrents_rename() (*TorrentsAPIMixIn method*), 57
torrents_rename_file() (*TorrentsAPIMixIn method*), 57
torrents_rename_folder() (*TorrentsAPIMixIn method*), 57
torrents_resume() (*TorrentsAPIMixIn method*), 58
torrents_set_auto_management() (*TorrentsAPIMixIn method*), 58
torrents_set_category() (*TorrentsAPIMixIn method*), 58
torrents_set_download_limit() (*TorrentsAPIMixIn method*), 58
torrents_set_download_path() (*TorrentsAPIMixIn method*), 58
torrents_set_force_start() (*TorrentsAPIMixIn method*), 59
torrents_set_location() (*TorrentsAPIMixIn method*), 59
torrents_set_save_path() (*TorrentsAPIMixIn method*), 59
torrents_set_share_limits() (*TorrentsAPIMixIn method*), 60
torrents_set_super_seeding() (*TorrentsAPIMixIn method*), 60
torrents_set_tags() (*TorrentsAPIMixIn method*), 60
torrents_set_upload_limit() (*TorrentsAPIMixIn method*), 60
torrents_start() (*TorrentsAPIMixIn method*), 61
torrents_stop() (*TorrentsAPIMixIn method*), 61
torrents_tags() (*TorrentsAPIMixIn method*), 61
torrents_toggle_first_last_piece_priority() (*TorrentsAPIMixIn method*), 61
torrents_toggle_sequential_download() (*TorrentsAPIMixIn method*), 61
torrents_top_priority() (*TorrentsAPIMixIn method*), 61
torrents_trackers() (*TorrentsAPIMixIn method*), 62
torrents_upload_limit() (*TorrentsAPIMixIn method*), 62
torrents_webseeds() (*TorrentsAPIMixIn method*), 62

 TorrentsAddPeersDictionary (*class in qbittorrentapi.torrents*), 71
 TorrentsAPIMixIn (*class in qbittorrentapi.torrents*), 47
 TorrentState (*class in qbittorrentapidefinitions*), 20
 TorrentTags (*class in qbittorrentapi.torrents*), 70
 Tracker (*class in qbittorrentapi.torrents*), 72
 trackers (*TorrentDictionary property*), 69
 trackers() (*Torrents method*), 64
 TrackersList (*class in qbittorrentapi.torrents*), 72
 TrackerStatus (*class in qbittorrentapidefinitions*), 22
 Transfer (*APINames attribute*), 20
 Transfer (*class in qbittorrentapi.transfer*), 74
 transfer_ban_peers() (*TransferAPIMixIn method*), 73
 transfer_download_limit() (*TransferAPIMixIn method*), 73
 transfer_info() (*TransferAPIMixIn method*), 73
 transfer_set_download_limit() (*TransferAPIMixIn method*), 73
 transfer_set_speed_limits_mode() (*TransferAPIMixIn method*), 74
 transfer_set_upload_limit() (*TransferAPIMixIn method*), 74
 transfer_setSpeedLimitsMode() (*TransferAPIMixIn method*), 73
 transfer_speed_limits_mode() (*TransferAPIMixIn method*), 74
 transfer_toggle_speed_limits_mode() (*TransferAPIMixIn method*), 74
 transfer_upload_limit() (*TransferAPIMixIn method*), 74
 TransferAPIMixIn (*class in qbittorrentapi.transfer*), 73
 TransferInfoDictionary (*class in qbittorrentapi.transfer*), 75

U

Unauthorized401Error, 11
 uninstall_plugin() (*Search method*), 40
 UNKNOWN (*TorrentState attribute*), 22
 UnsupportedMediaType415Error, 11
 UnsupportedQbittorrentVersion, 9
 update_plugins() (*Search method*), 40
 UPDATING (*TrackerStatus attribute*), 23
 upload_limit (*TorrentDictionary property*), 69
 upload_limit (*Transfer property*), 75
 UPLOADING (*TorrentState attribute*), 22

V

version (*Application property*), 15
 Version (*class in qbittorrentapi._version_support*), 76

W

warning() (*Log.Main method*), 24
 web_api_version (*Application property*), 15

`WebSeed` (*class in qbittorrentapi.torrents*), 72
`webseeds` (*TorrentDictionary property*), 69
`webseeds()` (*Torrents method*), 64
`WebSeedsList` (*class in qbittorrentapi.torrents*), 72
`with_data` (*RSS.Items property*), 34
`without_data` (*RSS.Items property*), 34
`WORKING` (*TrackerStatus attribute*), 23